

S-8700 Interior Floor Finish Wax

TECHNICAL DATA SHEET

DESCRIPTION:

S-8700 INTERIOR FLOOR FINISH WAX is an interior floor polish designed to provide extreme durability, thereby reducing maintenance cycles. INTERIOR FLOOR FINISH WAX also provides a rich gloss, non-yellowing film which resists soiling and black marking. INTERIOR FLOOR FINISH WAX is the product of choice for high use, low maintenance floors. INTERIOR FLOOR FINISH WAX exceeds the Coefficient of Friction safety standards of ASTM Designation D-2047.

APPLICATION:

Use standard application procedures with a good quality rayon or synthetic blend string mop, applying thin to medium coats of INTERIOR FLOOR FINISH WAX.

ROUTINE MAINTENANCE:

Use Super-Krete S-12000 Heavy Duty Degreaser for damp mopping or scrubbing prior to high speed buffing. Routine use of Heavy Duty Degreaser with high speed buffing will increase the safety and durability of the floor polish, extending the time between coats. High speed buffing INTERIOR FLOOR FINISH WAX will prolong the life of the polish and increase safety and durability, as well as increase shine and appearance. A propane buffer equipped with natural hog hair pads will achieve optimum buffing results, but any good quality high speed (1000+ rpm) buffer will achieve excellent results.



RECOAT:

Scrub the floor with a low speed buffer or automatic scrubber and blue or green (medium scrub) pads using S-12000 Heavy Duty Degreaser to achieve a clean surface. Rinse the floor with clean water and let dry, then apply one or more coats of INTERIOR FLOOR FINISH WAX, allowing each coat to dry before applying subsequent coats. Upon drying, high speed buff the last coat applied for optimum results.

SPECIFICATIONS::

COLOR:	Milky white, stable emulsion, dries clear.
ODOR:	Sweet
pH:	8.2 + 0.1
HMIS RATING:	Health = 1 Flammability = 0 Physical Hazard = 0
REFRACTOMETER SOLIDS:	22%
FLASH POINT:	None (C.O.C. Method)
DRYING TIME:	30 minutes at 20°C. (68°F.), 50% relative humidity.
GLOSS:	92 (A.S.T.M. Test D-523, 60°)
SURFACE TENSION:	29 dynes per cm.
SAFETY (slip resistance):	Exceeds requirements (A.S.T.M. Test D-2047)
LEVELING:	Excellent (A.S.T.M. Test D-2801)
SPECIFIC GRAVITY:	1.07
DENSITY:	8.9 pounds per gallon
POWDERING RESISTANCE:	Excellent (A.S.T.M. Test D-2048-82)
RECOATABILITY:	Excellent (A.S.T.M. Test D-3153-78)
PACKAGE SIZES:	4 x 1 gallon jugs

S-8700 Interior Floor Finish Wax

TECHNICAL DATA SHEET

CAUTION:

Keep away from children. Do not take internally. Always use safety gloves, the appropriate eye protection, and appropriate OSHA/NIOSH approved respirator in areas with poor ventilation and when exposed to spray mist, both indoors and outdoors. If ingested, seek medical attention immediately.

LIMITATIONS:

Super-Krete products are to be applied only when surface temperatures are above 55°F and rising and not to exceed 100°F. Super-Krete products are not to be applied when precipitation is expected within 24 hours following completion of application. Do not allow materials to freeze. Each Super-Krete product acts as an inherent part of a proven system. Super-Krete products are professional, contractor grade products. Training in the use of these products is available. Consult Super-Krete for information and assistance locating approved contractors in your area or for training class dates.

NOTE: Super-Krete International, Inc. believes this information to be true to the best of our knowledge and products are of the highest quality and uniform within manufacturing tolerances. Since no control is exercised over product use, no warranty, expressed or implied is made as to the effect of such use and no liability is assumed directly or indirectly, from their use. Buyers and users are encouraged to conduct their own test prior to application.

WARRANTY:

Super-Krete products are warranted only when applied by Super-Krete Certified Applicators in accordance with Super-Krete specifications. No warranty applies to products applied over concrete substrates with moisture vapor transmissions exceeding (3 lbs.)/(1,000 sf) of surface area. Super-Krete provides a 5 year warranty when products are applied by Certified Applicators. To apply for warranty, refer to the Super-Krete Limited Warranty and form filing at www.super-krete.com.