

# GRIDSTONE® BRAND GYPSUM CEILING PANELS

## MANUFACTURER

National Gypsum Company  
2001 Rexford Road  
Charlotte, NC 28211  
(704) 365-7300

Technical Information:  
1-800-NATIONAL  
(1-800-628-4662)

Fax: 1-800-FAX NGC1  
(1-800-329-6421)

Internet Home Page:  
www.nationalgypsum.com

09250/NGC BuyLine: 1100

## DESCRIPTION

Gridstone BRAND prefinished ceiling panels have a non-combustible, Fire-Shield G gypsum core. The 2-mil. white, stipple-textured vinyl laminate combines high light reflectance with easy cleanability.

## APPLICATIONS

Gridstone panels are ideal for interior and unexposed exterior ceiling applications such as soffits, parking garages, kitchens and baths.

Gridstone panels are accepted by the USDA for use in food service and food processing areas.

## ADVANTAGES

- *Quick, dry installation.* Gridstone Ceiling Panels install easily in standard exposed grid systems.
- *Fire-resistant.* A noncombustible gypsum core assures fire safety with 1 1/2- and 2-hour fire rating achievable depending on installation.
- *Pre-decorated.* The sturdy white vinyl laminate eliminates additional finishing.
- The product shall be maintained at a temperature between 60° and 104° Fahrenheit (16° - 40° Centigrade) and not exceed 90% relative humidity prior to, during and after installation.

## LIMITATIONS

- Do not install panels in areas exposed to extreme or continuous moisture.

- For exterior application, protect grid panels from direct exposure to weather, water and continuous high humidity. Under no circumstances should water be in contact with the back of the panels.

- Can support 1.3 #/sq. ft. of insulation.

- Overlaid insulation may cause excessive panel deflection and is not recommended where high humidity is likely to occur.

- Extreme lighting conditions may distort texture appearance.

- The use of strong organic solvents (such as ketones), harsh abrasive cleansers or steel wool are not recommended. These materials may cause dulling, discoloration, softening and other permanent damage to the vinyl surface.

## FINISH

2 mil. white stipple vinyl laminate

## APPLICABLE STANDARDS

ASTM C 36, Type X  
ASTM E 1264, Type XX,  
Patterns E, G  
ASTM C 960 Type X Class I

USDA Acceptance: Gridstone panels are accepted by the USDA for use in food service and food processing areas.

## FIRE RATINGS BY TYPE & SIZE (ASTM E 119)

Type	Size	Design	Rating
1/2" (12.7 mm) Fire-Shield G	2' X 2' (Actual size: 23 3/4" x 23 3/4") (610 mm x 610 mm)	UL G222 FM FC 299	2 hr.
1/2" (12.7 mm) Fire-Shield G	2' X 4' (Actual size: 23 3/4" x 47 3/4") (610 mm x 1219 mm)	UL G259 FM FC 300	1 1/2 hr.

## TECHNICAL DATA

### SURFACE BURNING CHARACTERISTICS

ASTM E 84  
Flame Spread: 5  
Smoke Developed: 0

### SOUND ATTENUATION

(ASTM E 1414 Test Method)  
Ceiling Attenuation Class (CAC)-46 dB  
NGC Report #6098001

### LIGHT REFLECTANCE

LR 1 (75% or greater)

## INSTALLATION

### APPLICABLE STANDARDS AND REFERENCES

National Gypsum Co. *Gypsum Construction Guide*

Gridstone ceiling panels are designed to be mounted in standard 15/16" exposed

tee grid systems or environmental type grids for severe conditions, with grids either 2' by 2' or 2' by 4'. Grid installation should be conducted according to manufacturer's specification.

Each panel must be supported on all four (4) edges.

Cross ventilation must be provided in unheated or enclosed space above ceiling panels.

## RECOMMENDATIONS

*General:* Install panels in lay-in suspension systems with edges concealed by flanges of suspension members. Cut panels to fit tightly at borders and penetrations so that cut edges are concealed by trim pieces and escutcheons.

(Continued next page)

Job Name \_\_\_\_\_

Contractor \_\_\_\_\_ Date \_\_\_\_\_

Submittal Approvals: (Stamps or Signatures)

*Cleaning:* Common dirt and stains on the vinyl surface can be removed with mild soap or detergent in luke-warm water. Use a light scrubbing action with a cloth, sponge or soft brush.

If the suitability of any cleaning agent is unknown, check its effect on the Gridstone panel surface in a hidden area or on a scrap piece before attempting to remove a field stain.

NOTE: Vinyl laminate on face of 2' x 2' Gridstone panel is directional. Install with all factory edges parallel (same direction).

### **DECORATION**

Gridstone Gypsum Ceiling

Panels are factory-finished decorative products which do not require painting. However, if desired, Gridstone can be painted with the following products:

1. Two coats of an alkyd or latex enamel.
2. Oil primer with finish coat of oil or latex paint.
3. Two coats of latex paint.

**National**   
**Gypsum**®

**Excellence Across The Board** 