

# **MOVEO® Operable Partitions**

Modernfold announces the next generation of operable partitions-MOVEO Glass. No longer is it necessary to choose between acoustics and glass. MOVEO Glass provides a sound solution with proven 45 STC lab performance. ComforTronic® Automatic Seals top and bottom are standard on MOVEO. Standard MOVEO Glass panels are double-pane glazed and available with optional designer glass solutions. Built-in, automatic venetian blinds are also available. Standard MOVEO panels can be integrated into a run to provide for work surfaces, design flexibility, and pass doors.



## Moveable Glass Wall System



#### Modernfold GWS

Available in a variety of configurations to fit the design requirements of any space, Modernfold Glass Walls or a custom Acousti-Seal Partition can provide the differentiation desired.

- · Single source provider of moveable glass wall systems.
- Multiple rail finishes available.
- Typically used in conference rooms, sky boxes, restaurants, and retail applications.

## **Accordion Doors and Partitions**

Modernfold's accordion products provide quick sight and sound division. Quick to install, easy to operate, and simple to maintain, they are an economical answer for many space division applications.


#### Soundmaster®

Soundmaster provides costeffective space division with sound attenuation. For versatility and durability, Soundmaster

offers a broad range of vinyl, carpet, and fabric choices to complement any room decor.

#### Modernfold®

A Modernfold accordion partition is ideal for sight and traffic separation. With their durability, replaceable outer coverings, and easy operation, Modernfold partitions are designed to give you many years of easy and trouble free operation.





# Acousti-Seal® Operable Partitions

# Single Panel Systems: 931, 911, 941

Single panel systems provide the ultimate in versatility and flexibility and offer multiple room setups, changes in the location of pass doors and work surfaces, and remote storage.

- Solves complex layout challenges.
- Satisfies high ceiling requirements with custom engineered panels up to 50-feet high.
- Accommodates wide variations in floor conditions.
- Simplifies setup and storage using the Smart Track™ suspension system.
- Often used in conference, multi-purpose, hospitality, and convention facilities.

# Paired Panel Systems: 932, 932FS, 912, 942

Available in top-supported or floor-supported configurations, the center-hung, paired panels are perfect for straight-line openings and offer quick, easy setup.

- Hinged together in groups of two, facilitating quick, easy setup.
- No auxiliary storage track or support required.
- Economical overhead support of straight-line track.
- SOSS Invisible Hinges or Standard Heavy Duty Barrel Hinges with lifetime guarantee.
- Simple automatic bottom seals for efficient operation.



Ultra sound separation with guaranteed field sound ratings up to 46 NIC. The Ultra-Seal operable partition is designed with added attention to field acoustical performance and is ideal for environments where

superior sound separation is needed. Ultra-Seal is ideal for hotel ballrooms, training facilities, and office environments with the need for acoustically secure spaces.

**Modernfold®** 

- Suited for applications that require exceptional durability, acoustic control, and frequent
- Panels are designed to be stored at either or both ends of an opening.
- Frequently used to divide classrooms, meeting rooms, or office spaces.



# Continuously Hinged Electric System: 933E

Electrically operated continuously hinged panels are connected together in a train, extending as one complete unit.

- Ideal for straight-line openings and simple operation.
- Setup is quick and effortless.
- Bottom seals are set automatically when the partition is fully extended.
- Keyed switches prevent unauthorized operation.
- Integrated safety systems ensure safe operation.
- Lifetime guarantee on heavy duty barrel hinges.
- Electrically operated partitions are frequently used in school gyms, classrooms, hotels, and board rooms.





### Acousti-Seal® and Ultra-Seal® Operable Partitions

| Single Panel             | Model                           | Operation                                 | Nominal Panel<br>Thickness | STC Options           | Skin Options                       | Max Opening<br>Width   | Max<br>Height+      | Track Options                        |
|--------------------------|---------------------------------|---|----------------------------|-----------------------|------------------------------------|--|---------------------|--------------------------------------|
|                          | Acousti-Seal<br>931             | Single Panel<br>Manual                    | 3 inches<br>(76 mm)        | 41, 45,<br>47, 50, 52 | Steel, MDF, Gypsum,<br>Wood Veneer | Unlimited  | 28 feet<br>(8.5 m)  | 17, 14,<br>RT100, RT200              |
|                          | Acousti-Seal<br>911, Fire Rated | Single Panel<br>Manual                    | 3 inches<br>(76 mm)        | 45, 50, 52            | Steel                              | Unlimited  | 28 feet<br>(8.5 m)  | 17, 14                               |
|                          | Acousti-Seal<br>941             | Single Panel<br>Manual                    | 4-1/4 inches<br>(108 mm)   | 55                    | Steel                              | Unlimited  | 50 feet<br>(15.2 m) | 17, 14,<br>RT100, RT200              |
|                          | Ultra-Seal                      | Single Panel<br>Manual                    | 4-1/4 inches<br>(108 mm)   | 46 NIC                | Steel                              | Unlimited  | 30 feet<br>(9.1 m)  | 17, 14,<br>RT100, RT200              |
| Paired Panel             | Acousti-Seal<br>932             | Paired Panel<br>Manual                    | 3 inches<br>(76 mm)        | 41, 45,<br>47, 50, 52 | Steel, MDF, Gypsum,<br>Wood Veneer | Unlimited  | 18 feet<br>(5.5 m)  | 17, 14, 30                           |
|                          | Acousti-Seal<br>932FS           | Paired Panel<br>Manual<br>Floor Supported | 3 inches<br>(76 mm)        | 41, 45,<br>47, 50, 52 | Steel, MDF, Gypsum,<br>Wood Veneer | 80'-9"<br>(24.6 m)   | 12 feet<br>(3.7 m)  | 17 w/ Stainless<br>Steel Floor Plate |
|                          | Acousti-Seal<br>912, Fire Rated | Paired Panel<br>Manual                    | 3 inches<br>(76 mm)        | 45, 50, 52            | Steel                              | Unlimited  | 18 feet<br>(5.5 m)  | 17, 14                               |
|                          | Acousti-Seal<br>942             | Paired Panel<br>Manual                    | 4-1/4 inches<br>(108 mm)   | 55                    | Steel                              | Unlimited  | 18 feet<br>(5.5 m)  | 17, 14, 30                           |
| Continuously<br>Hinged   | Acousti-Seal<br>933E            | Continuously<br>Hinged<br>Electric        | 3 inches<br>(76 mm)        | 41, 45,<br>47, 50, 52 | Steel, MDF,<br>Wood Veneer         | single:<br>109'-9"<br>(33.5 m)<br>pair:<br>201'-6"<br>(61.4 m) | 24 feet<br>(7.3 m)  | 14, 30                               |
|                          | Acousti-Seal<br>933             | Continuously<br>Hinged<br>Manual          | 3 inches<br>(76 mm)        | 41, 45,<br>47, 50, 52 | Steel, MDF, Gypsum,<br>Wood Veneer | 38'-6"<br>(11.7 m)   | 12 feet<br>(3.7 m)  | 17, 14, 30                           |
| Hanging                  | 41 STC @                        | 45 STC @                                  | 47 STC                     | 50                    | STC @ 52 STC                       | @ 55 S   | STC @               | 46 NIC @                             |
| Weight/sq ft<br>(by STC) | 6.5 lb/sq.ft.                   | 8 lb/sq.ft.                               | 7 lb/sq                    | .ft. 8 lb             | o/sq.ft. 11 lb/sq                  | .ft. 13 lb   | o/sq.ft.            | 13 lb/sq.ft.                         |

<sup>+</sup>Custom solutions available beyond maximum height.

 $^{++} \#14$  Suspension system available for custom solutions above maximum height.

### **MOVEO® Operable Partitions**

| MOVEO<br>Operable<br>Partitions | Model          | Operation                              | Nominal Panel<br>Thickness | STC | Skin/Face Options  | Max Panel<br>Width     | Max<br>Height      | Panel<br>Weight | Track Options             |
|---------------------------------|----------------|--|----------------------------|-----|--|------------------------|--------------------|-----------------|---------------------------|
|                                 | MOVEO<br>Glass | Single Panel<br>Manual w/<br>Auto Seal | 4 inches<br>(100 mm)       | 45  | Glass  | 48 inches<br>(1219 mm) | 13 feet<br>(4 m)   | 10 lb/sq.ft.    | Programmable<br>K-Track   |
|                                 | MOVEO          | Single Panel<br>Manual w/<br>Auto Seal | 4 inches<br>(100 mm)       | 45  | MDF with plastic<br>laminate, veneer, or<br>work surface | 48 inches<br>(1219 mm) | 13 feet<br>(4 m)++ | 5 lb/sq.ft.     | Programmable<br>K-Track++ |

### Modernfold GWS Moveable Glass Walls

| Models  | Operation                 | Max Panel Width        | Max<br>Opening Width | Max Height        | Max Panel Weight     | Track Options         |
|---|---------------------------|------------------------|----------------------|-------------------|----------------------|-----------------------|
| 362SR/TR-DRS<br>600SR-DRS<br>800SR-DRS<br>1000SR-DRS<br>100SR-G | Single<br>Panel<br>Manual | 48 inches<br>(1219 mm) | Unlimited            | 10'-2"<br>(3.1 m) | 330 lb<br>(149.7 kg) | 17G, G150,<br>K-Track |

### **Accordion Doors and Partitions**

| Soundmaster/<br>Modernfold | Model           | Operation             | Stack<br>Width            | Stack<br>Depth*         | Max<br>Width**      | Max<br>Height+     | STC | Hanging Weight  | Track Options |
|----------------------------|-----------------|-----------------------|---------------------------|-------------------------|---------------------|--------------------|-----|-----------------|---------------|
|                            | Soundmaster 8   | Manual or<br>Electric | 9 inches<br>(229 mm)      | 2-1/8 inches<br>(54 mm) | 50 feet<br>(15.2 m) | 16 feet<br>(4.9 m) | 39  | 4-1/4 lb/sq.ft. | 5, 6, 7       |
|                            | Soundmaster 12  | Manual or<br>Electric | 12-5/8 inches<br>(321 mm) | 1-3/4 inches<br>(45 mm) | 60 feet<br>(18.3 m) | 16 feet<br>(4.9 m) | 40  | 5 lb/sq.ft.     | 6, 7          |
|                            | Modernfold 800  | Manual or<br>Electric | 9 inches<br>(229 mm)      | 2-1/8 inches<br>(54 mm) | 50 feet<br>(15.2 m) | 16 feet<br>(4.9 m) | N/A | 2 lb/sq.ft.     | 5, 6, 7       |
|                            | Modernfold 1200 | Manual or<br>Electric | 12-5/8 inches<br>(321 mm) | 1-3/4 inches<br>(45 mm) | 60 feet<br>(18.3 m) | 16 feet<br>(4.9 m) | N/A | 2-3/4 lb/sq.ft. | 6, 7          |

\*Custom solutions available beyond maximum height.

\*Per lineal feet of opening width, plus posts.

\*\*Paired partitions double maximum width.

Modernfold, Inc. • 215 West New Road, Greenfield, IN 46140 • (Tel) 800-869-9685 (Fax) 866-410-5016 • (e-mail) info@modernfold.com • www.modernfold.com

Moveable Glass Walls