

Wall & Ceiling Spray Textures

DESCRIPTION

ProFin® Wall and Ceiling Spray Textures provide a decorative appearance over gypsum panels and most other interior wall and ceiling surfaces. They are formulated to provide for a variety of decorative options including splatter, knockdown and orange peel designs.

- PROFIN MEDIUM-TEX POWDER
- PROFIN COARSE-TEX POWDER
- PROFIN HIGH HIDING TEX POWDER
- PROFIN SOLID SURFACE TEX POWDER
- PROFIN SPANISH TEX POWDER
- PROFIN HAND-TEX R/M
- PROFIN REINFORCED LITE TEX R/M
- PROFIN HEAVY-TEX POWDER
- PROFIN MULTI-TEX POWDER
- PROFIN EASI-TEX POWDER
- PROFIN SPRAY-LITE TEX R/M

- SHELF LIFE:** Ready-Mixed 12 months from production code date, when stored properly.
- Powders 24 months from production code date, when stored properly.

DRYING TIME: 24 hours in normal conditions.

STORAGE: ProFin Wall and Ceiling Textures should be stored in a dry, temperate location where there can be no contact with moisture. Rotate stock. Opened bags should be closed tightly before storage. Protect Ready-Mixed textures from freezing.

TECHNICAL REFERENCES:

For additional information on the application of ProFin Brand products please consult:

- ASTM C 475: Standard Specification for Joint Compound and Joint Tape for Finishing Gypsum Board.
- ASTM C 840: Standard Specification for Application and Finishing of Gypsum Board.
- GA-214: Gypsum Association publication "Levels of Gypsum Board Finish."
- GA-216: Gypsum Association publication "Recommended Specifications for the Application and Finishing of Gypsum Board."

WORKING WITH THE PRODUCT

SITE CONDITIONS:

The room temperature and wallboard should be maintained at 13°C (55°F) for 48 hours prior to application and continuously thereafter until completely dry. Continuous ventilation must be provided to ensure proper drying. When using temporary heating, care should be taken to avoid overheating and high humidity conditions.

SURFACE PREPARATION:

Ensure that surfaces to be decorated are thoroughly dry and free of dirt, oils, mildew and other contaminants.

PRIMING:

All surfaces to be textured should be primed with BPB ProFin Texture Primer prior to application to ensure uniform porosity and texture. Primer should be dry prior to applying texture. Adhere to all manufacturers' specific directions for painting and decorating materials.

SUBMITTAL APPROVAL STAMPS/SIGNATURES

Please check the appropriate products above which are being submitted for approval

Date:

Project:

PRODUCT DATA

- MATERIAL:** Powder or Ready-Mixed
- COLOUR:** Off white
- PACKAGING:** Powder 15 kg - 25 kg (33 lbs - 55 lbs) bags
Ready-Mix 15.5 L - 17 L (4 - 4.4 US GAL) cartons
- COVERAGE:** The coverage of ProFin Wall and Ceiling Textures varies greatly depending on formula base, type of pattern, the condition of the substrate, and the application technique. Please contact your local BPB sales representative for further information.



Wall & Ceiling Spray Textures

MIXING (POWDER)

Use a clean vessel equipped with powder agitator. For initial mix, stir powder into recommended amount of water, agitating during powder addition. Allow to soak for at least 15 minutes – longer in cold water. Remix until a creamy, lump-free mix is obtained. Adjust to spray consistency by adding small amounts of water, if necessary. Over thinning can create an undesirable finish or "soft wall" or chalky condition. Over dilution can also entrain excessive air and foam. Note that the air and mix temperature will affect viscosity.

MIXING (READY MIX)

Prethinning may be necessary; the amount of water added will determine the type of texture achieved.

APPLICATION:

Texture should not be applied until the primer coat is thoroughly dry. Products are specifically designed for hand and spray applications. The desired pattern can be achieved by varying the viscosity of the mix, the orifice opening at the spray tip, or the air supply pressure.

DECORATING:

This product can be painted after drying. Adhere to all manufacturers' specific directions for painting and decorating materials.

LIMITATIONS:

- Application below grade or in high-humidity areas is not recommended.
- May contribute to sagging of gypsum board ceilings in humid conditions. The potential for sagging can be minimized by taking the following precautions:
 - Use ProRoc Interior Ceiling board or gypsum board applied perpendicular to the framing at the proper spacing recommendation for the board thickness (see GA-216, Tables 1 and 4.)
 - Excessive amounts of insulation should not be added without additional support (GA-216, Table 2). Where the gypsum board supports ceiling insulation and is finished with a water-based texture material, either spray or hand applied, only 15.9 mm (5/8") gypsum board, or 12.7 mm (1/2") gypsum ceiling board, application perpendicular to the framing members shall be used.
 - The relative humidity should be controlled by providing adequate ventilation before, during and after gypsum board and finish application.
 - Temperatures should be maintained between 13°C and 21°C (55°F and 70°F).

- Gypsum board should be thoroughly dry and at ambient temperature before application.
- Joint treatment should be thoroughly dry before applying any decoration.
- Individual coats of primer and paint shall be dry before the application of successive coats.
- Texture is not washable unless painted.

MSDS:

MSDS Material Safety Data Sheets are available on our web site, www.bpb-na.com.

WARNING:

Dust generated from sanding product may cause eye, skin, nose, throat or respiratory irritation. Use wet-sanding to avoid creating dust. Avoid inhalation of dust and eye contact. Product contains silica. Inhalation of respirable silica dust can cause silicosis, a potentially disabling lung disease, and is known to the State of California to cause lung cancer.

When sanding, drilling or abrading product during installation or handling: (1) Ensure adequate ventilation. (2) Wear a dust mask or, if dust may exceed PEL, use NIOSH/MSHA approved respirator. (3) Warn others in area. (4) Wear eye protection.

If eye contact occurs, flush thoroughly with water for 15 minutes. For further information, refer to Material Safety Data Sheet or consult manufacturer by calling 1-866-427-2872.

KEEP OUT OF REACH OF CHILDREN.

WARRANTY:

Since methods and condition of application such as temperature, humidity and over thinning are beyond our control, BPB Canada Inc. (BPB) will not be responsible for the failure of this product when not used according to directions and specifications and accepted standards of procedure inherent in drywall application; or when reasonable allowance is not made by the user for adverse weather and job conditions. However, if this product proves to be defective, maximum liability shall be limited to replacement of the material only or refund of the purchase price. This shall be the full limit whatsoever of BPB's liability. All claims shall be submitted in writing to BPB within thirty days from the date of discovery. State or federal laws may provide rights in addition to this warranty that cannot be modified or excluded.

Canada

BPB Canada Inc.

2424 Lakeshore Road West,
Mississauga, Ontario L5J 1K4
Telephone: (905) 823-9881
Fax: (905) 823-4860
E-mail: info@bpb-na.com
Web: www.bpb-na.com

Distributed by:

Characteristics, properties or performance of materials or systems manufactured by BPB herein described are derived from data obtained under controlled test conditions. BPB makes no warranties, expressed or implied, as to their characteristics, properties or performance under any variations from such conditions in actual construction. BPB assumes no responsibility for the effects of structural movement.

©™ Trademarks are the property of BPB plc or its affiliates and related companies

NOTICE: The information in this document is subject to change without notice. BPB assumes no responsibility for any errors that may inadvertently appear in this document.

© 2005 BPB Canada Inc. Printed in Canada on recycled paper. ♻ Rev 1- April 2005 Form #: L-SD-003-E

