



J200



LR



LC



LG



LV



LF

**DORMA By Choice™**



The quality management system at the Reamstown, PA and Steeleville, IL facilities are certified to ISO 9001\*.  
\*DORMA Door Controls, Inc., dba: DORMA Architectural Hardware  
0208





## DORMA J200 GRADE 2 INTERCONNECTED LOCKSETS

### Applications:

DORMA J200 Series Grade 2 interconnected locksets are especially suited for multifamily residential apartments, condominiums, and assisted living applications where heavy-duty certified Grade 2 products are required. The broad range of designs and finishes will satisfy most architectural requirements and applications.

### Listings & Approvals:

- BHMA certified to meet ANSI/BHMA A156.12-2005 Grade 2 requirements.
- U.L. and C.U.L. listed for 3-hour fire rated doors 4'0" x 8'0".
- J200 Series interconnected locks meet ANSI 117.1 and ADA requirements for barrier-free accessibility.

### Warranty:

Five (5) year limited warranty.

### Exposed Trim:

Brass, bronze, or stainless steel. Levers are pressure cast zinc, plated to match finish symbols.

### Finishes:

Brass: 605 (Bright).  
Bronze: 613 (Dark Oxidized Satin).  
Nickel<sup>1</sup>: 619 (Satin).  
Chrome<sup>2</sup>: 626 (Satin).

1. 619 finish only available on LF and LV lever designs.
2. 626 finish only available on LR, LC, and LG lever designs.

### Door Ranges:

Lever designs fit 1-3/8"–1-7/8" (35 mm–48 mm) standard. Consult factory for special door ranges.

### Backset:

2-3/8" (60 mm) and 2-3/4" (70 mm) adjustable backset standard.

### Keying:

- 6-pin brass cylinders with two (2) nickel silver keys.
- Keying options available from factory include master keying, grandmaster keying, and construction keying.
- 6-pin and 7-pin small format interchangeable core cylinders.

### Features:

- All DORMA J200 Series locks feature advanced design concepts, providing exceptional reliability and are manufactured with the finest materials, delivering enhanced durability.
- DORMA J200 Series locksets are easy to install in both wood or hollow metal doors with ANSI Standard A156.115-2006 door preparations for interconnected locks.
- All J200 Series locks are easily adjustable to accommodate door thickness from 1-3/8" to 1-7/8" thick.

### Functions:

ANSI	DORMA	Description
—	J290	Dummy Trim
F95	J210	Single Entry
F97	J253	Double Entry

### Contact Information:

DORMA Architectural Hardware  
Dorma Drive, Drawer AC  
Reamstown, PA 17567-0411  
Tel: 800-523-8483  
Fax: 800-274-9724  
Email: archdw@dorma-usa.com

### A DORMA Group Company

www.dorma-usa.com