



DRYWALL "C" PROFILE

16 GAUGE ONLY

2" FACE STANDARD - 1-1/2" AND 1-3/4" AVAILABLE

JAMB DEPTHS -

UNEQUAL RABBET - 4-1/2" THROUGH 8-3/4"

EQUAL RABBET - 4-7/8" THROUGH 8-3/4"

SILL FACE 1-1/2" THROUGH 6" AVAILABLE

COMPRESSION ANCHORS

BASE ANCHORS - 2" FACE HAS STANDARD BASE ANCHOR (PUNCH FACE)

1-1/2" AND 1-3/4" FACE HAS OPTIONAL BASE ANCHOR

4'0" X 8'0" MAXIMUM DOOR OPENING

8'0" X 8'0" MAXIMUM ELEVATION OPENING SIZE AVAILABLE IN SINGLE AND DOUBLE SIDELIGHT. NO HORIZONTAL MULLIONS ALLOWED

SINGLE DOOR OPENING ONLY

NON-RATED ONLY

ROUGH OPENING REQUIREMENTS:

THE ROUGH OPENING HEIGHT EQUALS THE FINISHED OPENING HEIGHT +1".

THE ROUGH OPENING WIDTH EQUALS THE FINISHED WIDTH +2".