

Fiberglass Reinforced Polyester Door System (FRP) with aluminum frame



Ceco Door is proud to introduce the FRP Door System, a Fiberglass Reinforced Polyester (FRP) door and aluminum frame intended primarily for exterior openings such as restaurants and schools in high use areas, as well as anywhere a strong, light-weight opening is required to withstand abuse.

FRP Door Features:

- Fiberglass Reinforced Polyester (FRP) skins .120" thick
- Available with class "C" (exterior) or class "A" (interior) skins
- 6063-T6 aluminum alloy perimeter extrusions
- Water-blown Polyurethane core, foam in place
- 4'0" x 8'0" Singles and 8'0" x 8'0" Pairs
- 1-3/4" thick
- Bevels: square and 3 degree available
- Hinges: 4-1/2" butt, continuous and offset pivots
- Locks: cylindrical, mortise, deadbolt, flush pull, rim exit, and SVR, with or without ElectroLynx
- Factory installed flush pull and automatic door bottom option
- Aluminum windows kits available up to 1296 square inches for 1/4", 1/2" and 1" thick glass
- Factory installed aluminum louvers available in 12" x 12" and 24" x 24" sizes in clear finish
- Flush top cap standard. Optional closer reinforcement available
- Bottom-cap sweeps available
- Labels: Fire rated and hurricane resistant door options

Aluminum Frame Features:

- 3 sided frames
- 6063-T6 hardened aluminum alloy
- Jamb depths of 4-1/2", 5" and 6"
- Available in Dark Bronze, Black and Clear anodized
- Maximum size 8'0" x 8'0"
- Hinges: 4-1/2" butt, continuous and offset pivots
- 2-3/4" and 4-7/8" strikes with or without lip
- Label: Hurricane resistant option

Door Faces:

- Nine standard colors for pebble (textured) embossed faces

Available Door Face Colors:

- Black
- Dark Gray
- Light Gray
- Forest Green
- Brick Red
- Tan
- Colonial Blue
- White
- Dark Bronze

Frame, Door Edges and Window Kit Colors Available:

- Black
- Dark Bronze
- Clear

Features and Benefits:

- Modern materials and durable construction reduce lifecycle cost
- Durable finish reduces maintenance costs
- Door skin cleans easily
- Exceptional thermal performance (U-0.26 sealed in place, U-0.35 operable) helps reduce energy usage
- Lightweight doors extend the life of the entire entrance system
- Cycle slam tested at 15 cycles per minute to over 9 million cycles
- Fire rated up to 90 minutes singles and pairs with stainless steel edges and window kits
- Hurricane resistant up to +/- 70 PSF singles with cylindrical, mortise and exit hardware

Ceco Door
9159 Telecom Drive • Milan, TN 38358
Tel (888) 232-6366 • Fax (888) 232-6462
archhelp@cecodoor.com | www.cecodoor.com

ASSA ABLOY, the global leader
in door opening solutions

Copyright © 2016, ASSA ABLOY Door Group, LLC, an ASSA ABLOY Group company. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Door Group, LLC is prohibited.

