

SPECIFICATIONS

Synthetic Rubber Foam The Silencer Superior (SR) **Acoustical Underlayment**

The Silencer SR	(100 sf rolls, 3'x33.34')
The Silencer SR Commercia	al(6'x75')
1 Truckload (SR)	48 Skids (240,000 sf)
1 Skid (SR)	50 Rolls (5000 sf)

- · Moisture barrier, flap and tape strip locks out moisture
- Thickness of 0.085" offering similar acoustical properties to 1/4" cork
- · Eliminates hollow, clacking sounds 70IIC, 71STC - excellent sound absorption
- · Quick and easy installation Requires no additional seaming tape, cuts with a knife
- · Smoothes out minor subfloor irregularities
- Contains Ultra-Fresh[™] anti-microbial protection. which resists mold and mildew
- · Non-allergenic and odorless
- · Suitable for all floating laminate and engineered wood floors - Not for glue down installations
- Fire Rating: DOC-FF-1-70, passes N.B.S. smoke density ASTM E-622-95, 110 max, passes
- · The industry's best limited lifetime warranty
- 100% recyclable, environmentally friendly
- · Unmatched track record: Hundreds of millions of square feet installed. O claims

THE INDUSTRY'S BEST **PRODUCT & WARRANTY**

The Silencer's™ warranty not only covers our own product, but also extends to all brands of laminate and floating wood floors.

Should any manufacturer of these types of flooring neglect to take responsibility for their own floor's warranty because you choose to use The Silencer™, we will honor their original warranty.

Foam Products Corp. warrants that The Silencer™ will conform to the published product specifications, subject to manufacturing tolerances, will be merchantable for the ordinary purposes for which such goods are used and will be free of defects in material and workmanship at the time of shipment.

FPC further warrants that it will replace FPC's defective products and will reimburse purchaser the original purchase price of any excessively abraded wood flooring area under which FPC's product was originally installed for any excessive abrasion resulting solely from a defect in FPC's The Silencer™ that caused a substandard performance to any valid warranty of the wood flooring manufacturer.

This commercial warranty gives the purchaser specific legal rights and the purchaser may also have other rights, which vary from state to state.

This commercial warranty will be effective only if The **Silencer**™ underlayment is installed and maintained in full compliance with the wood flooring manufacturer's instructions, recommendations and specifications.

FPC does not assume any liability for faulty installation or lack of maintenance or improper maintenance. This warranty is non-transferable.



www.silencerunderlayment.com

MADE IN U.S.A.



THE SILENCER SUPERIOR

Acoustical Underlayment For Laminate and Floating Wood Floors with Moisture Barrier

Provides your floors with the **REAL** sound of hardwood

Reduces floor noise by providing excellent sound absorption







www.silencerunderlayment.com

THE SILENCER SUPERIOR

- Is quiet shhh!
- Contains *Ultra-Fresh*[™] anti-microbial which resists mold and mildew
- Provides cushioned comfort under laminate and floating wood floors
- 100% recyclable
- · Environmentally friendly
- · Has over 2 million satisfied customers
- Hundreds of millions of square feet installed with ZERO claims
- Moisture barrier with lip & tape to lock out moisture
- · Eliminates minor subfloor imperfections
- Suitable for use with radiant heat flooring systems

Install film side down against concrete/subfloor





The Silencer SR™

The **Silencer Superior** is an outstanding acoustical underlayment. Its moisture barrier and tape strip combine to lock out moisture and allow for quick and easy installation.

Designed for exceptional acoustical noise reduction, the **Silencer Superior** has high density and compression resistance properties that enable your floor to perform to its fullest potential and last a lifetime.

No floating floor should be without it.

The Silencer™ maintains the beauty of your floor for its lifetime like nothing else.







Ultra-Fresh™ is a registered trademark of Thomson Research Associates, Inc.

Sure it sounds great now, but how about next year?

Light-weight plastic underlayments perform adequately for the short term, but soon collapse with traffic and weight. Ultimately, this shortens the life span of the floor and invalidates fine acoustical performance with compression.

Only a Superior Underlayment Can Stand Up To Pressure.



The Silencer™ (left) even resists indentation from a car's weight, while a competing underlayment (right) may crush permanently, which can cause the floor to sag or buckle.