DYNATHANE

DYNATHANE

DOUBLE-STICK COMMERCIAL CARPET CUSHION

DOUBLE-STICK COMMERCIAL CARPET CUSHION

Product Description Dynathane 175 Dynathane 250 Dynathane 180* 100% High Density 100% High Density 100% High Density Frothed Polyurethane Frothed Polyurethane Frothed Polyurethane

6'
45'
45'
Yes
Yes
Yes
Yes
Extra Heavy Duty
Commercial/Hosoitality
Commercial/Hosoitality

.180 inches (3/16+*)

Non-Woven fabric

Commercial/Hospitality Commercial/Hospitality

Performance Data

Compression Resistance @ 25% 4.5 psi @ 25% 4.5 psi

Extra Heavy Duty

@ 65% 23 psi

10% max

@ 25% 4.5 psi @ 25% 6 psi @ 65% 23 psi @ 65% 38 psi 10% max. 10% max.

Tensile Strength, PSI Exceeds 100 lbs.

Flammability Tests

Passes, 110 max. Passes, 100 max. Passes, 100 max

 Pill Test
 Passes
 Passes

 ASTM E-648
 Radiant Panel
 N/A
 N/A

*Passes - Class 1 Meets Marine USCG Requirements

Passes



Recommended Use

ASTM-D3676

ASTM-D3676

ASTM E-662 Smoke Chamber

DOC FF 1-70

Compression Set @ 50%

- Environmentally Safe Exceeds EPA carpet VOC emissions requirements
- Non-Allergenic / Odorless
- Contains Zero (0) Formaldehyde, Stryene,
 BHT(Butylated Hydroxy Toluene), 4 PC (Phenylcyclohexene)
- Contributes to LEEDS™ project certification
- . Increases life of the carpet by up to 60%
- · Reduces noise levels and fatigue (stress on legs and back)
- . Insulation from cold floors
- · Suitable for use with radiant heat flooring systems
- . Use for double glue or standard stretch-in installations
- Warranted for the normal service life of the original carpet.

Foam Products Corp.

350 Beamer Road Calhoun, GA 30721 800.526.3626 www.foamproducts.com

Cushion DYNATHANE

Double-Stick Commercial

Carpet



High Density Polyurethane Commercial/Hospitality Carpet Cushion





By the makers of The **Silencer**Foam Products Corp
800.526.3626
www.foamproducts.com

DYNATHANE

100% Premium High Density Polyurethane Commercial/Hospitality Carpet Cushion

Use for Double Glue or stretch-in installations

- Environmentally safe Exceeds EPA carpet VOC emissions requirements
- Contains Zero (0) Formaldehyde, Stryene, BHT(Butylated Hydroxy Toluene), 4 PC (Phenylcyclohexene)
- Non Allergenic / Odorless
- . NEW FRESH® antimicrobial treatment resists mold, mildew, and bacteria
- · Contributes to LEEDS project certification
- · Reduces noise levels and fatique (stress on legs and back)
- · Insulation from cold floors
- · Suitable for use with radiant heat flooring systems
- Excellent resiliency, provides longer carpet life and appearance retention
- · Guaranteed performance

Installation & Adhesives

Consult the carpet manufacturer's installation specialists for specific instructions based on the carpet chosen. Pressure sensitive adhesives can be used between cushion and floor for easier removal. Use a notched trowel size of 1/16" width x 1/32" Depth x 1/32" spacing to insure evenness of the adhesive. Non pressure sensitive adhesives can be used: however, removal of cushion will be more difficult. A premium quality adhesive should be used between the carpet and cushion. Use a minimum notched trowel size of 1/8" width x 1/8" depth x 1/16" spacing. It is important to apply enough adhesive to fill the recesses in the carpet backing and create a 100% area bond between the carpet and cushion. Foam Products Corporation does not recommend any specific adhesive manufacturer. Consult the adhesive manufacturer of your choice for their warranties, installation instructions and recommended products for polyurethane carpet cushion

Warranty

Foam Products Corporation warrants that they will replace free of charge, any affected area should the DYNATHANE® cushion prove to be defective during the life of the carpet under which it was originally installed. Foam Products Corporation will not be responsible for replacement of the carpet nor will liability be assumed for any consequential damage, loss, or incidental expense. This commercial warranty gives you specific legal rights which vary from state to state. This commercial warranty will be effective only if DYNATHANE® cushion is installed wall to wall in accordance with the carpet manufacturers instructions and adhesives recommended by the adhesive manufacturer. Foam Products Corporation will not assume liability for faulty installation.

