

MODEL NUMBER	FLOOD COVERAGE	VENT SIZE	ROUGH OPENING
1540-520	200 sq. ft.	16"W x 8"H x 3"D	16 \frac{1}{4} in x 8 \frac{1}{4} in
1540-521	400 sq. ft.	16"W x 16"H x 3"D	$16\frac{1}{4}$ in x $16\frac{3}{8}$ in
1540-570	200 sq. ft.	$14\frac{1}{2}$ W x 8 $\frac{1}{2}$ H x 3 D	14 ½ in x 8 ¾ in

INSULATED SERIES

This series of vents are ideal for areas requiring flood venting protection but no natural air ventilation.

The flood door contains a 2" Styrofoam core that has an R-value of 8.34 and the vent frame is lined with felt weather stripping, helping to keep the enclosure as insulated to the elements as possible.

IDEAL FOR:

- Garages
- Full height enclosures (e.g. walkouts)
- Conditioned crawlspaces
- Storage facilities
- Metal buildings
- Foyers



2 Stacker 1540-521

Stacker Models are twice as efficient as a single unit and are a great solution for large amounts of square footage, and in situations where there is not enough wall space to fit in single units.

3 Wood Wall 1540-570

Wood Wall Models are designed to fit between studs spaced at 16" on center. Pre-drilled slots in the four corners on the vent flange make for an easy installation.

