

## CertaPRO® Board

### PRODUCT DESCRIPTION

**Basic Use:** CertaPro® Board is used to enhance thermal and acoustical performance where board stiffness properties are required and also functions as an exterior insulation when covered with a weather barrier. CertaPro Board is used in exterior curtain walls, interior walls and floor/ceiling assemblies, and as an exterior insulation on HVAC ducts and plenums or in constructions where framing is not present. It is also used as thermal insulation on tanks and vessels.



**Benefits:** CertaPro Board provides high sound absorption and excellent thermal performance. This product contains a minimum of 60% recycled content. The product is offered in a variety of stiffness properties from flexible to rigid and all can be easily cut, handled, fabricated and installed. The product resists mold and mildew and will not rot or deteriorate.

**Composition and Materials:** The product is composed of tan, uniformly textured, inorganic fibrous glass and formed with a formaldehyde-free binding agent.

**Limitations:** Insulation should be kept clean and dry at all times.

**Sizes:** See table on other side. Contact CertainTeed for other sizes and minimum order quantities.

### INSTALLATION

**Exterior Walls** – The faced side of the board should be installed toward the interior side of the structure, except in warm and humid areas where local code regulations may require a vapor retarder to face toward the exterior.

**Curtain Walls** – CertaPro Board is applied to spandrel and pre-cast concrete panels with approved adhesives or mechanical fasteners. Boards may also be installed using hat channels or Z studs. Where a vapor retarder is required, all joints, seams and penetrations must be sealed. Exterior applications require the insulation to be covered with appropriate weather barrier finish in addition to the factory-applied vapor retarder facing. Choice of finish depends on mechanical abuse, weather exposure and appearance requirements.

**HVAC/Mechanical** – All fabrication, application and installation steps should be in accordance with the requirements of the National Commercial and Industrial Installation Standards (current edition) published by the Midwest Insulation Contractors Association (MICA).

These installation recommendations are general in nature. Other methods are acceptable. Please consult your contractor for recommendations best suited to the application.

### AVAILABILITY AND COST

For availability and cost, contact your local contractor or distributor, or call CertainTeed Sales Support Group at 800-233-8990.

### WARRANTY

Refer to CertainTeed Limited Warranty for Commercial Insulation (30-25-034). Inasmuch as CertainTeed has no control over the installation design, installation workmanship, accessory materials or conditions of application, CertainTeed does not warrant the performance or results of any installation containing its products.

<b>Product Name</b>	CertaPro® Board
<b>Manufacturer</b>	CertainTeed Corporation
<b>Address</b>	P.O. Box 860 Valley Forge, PA 19482-0105
<b>Phone</b>	610-341-7000 • 800-233-8990
<b>Fax</b>	610-341-7571
<b>Website</b>	<a href="http://www.certainteed.com/insulation">www.certainteed.com/insulation</a>

### TECHNICAL DATA

#### Applicable Standards

- Model Building Codes:
  - ICC
  - California Quality Standards Reg. No. CA-T024 (PA)
  - City of Los Angeles, RR 8148
- Material Standards:
  - ASTM C553, CB 150, Type I, II & III
  - ASTM C612, CB 150 & CB 225, Type IA; CB 300 & CB 600, Types IA & IB
  - CAN/CGSB-51.10-92, CB 150 & CB 225, Type II, Class II; CB 300 & CB 600, Type I, Class II
- GREENGUARD® Children & Schools Certified

#### Fire Resistance

- Fire Hazard Classification:
  - ASTM E84, UL 723
  - CAN/ULC-S102-M88  
Max. Flame Spread Index: 25  
Max Smoke Developed Index: 50
- Limited Combustible:
  - NFPA 259 / ≤ 3,500 Btu/lb

#### Physical/Chemical Properties

- Thermal Performance:
  - ASTM C177 or ASTM C518 / See table on other side
- Acoustical Performance:
  - ASTM C423 / See table on other side
- Operating Limits (Temperature):
  - ASTM C411 / Max. 250°F (121°C) (Faced);  
Max. 450°F (232°C) (Unfaced)
- Water Vapor Permeance:
  - ASTM E96, Dessicant Method / Max. 0.02 perms  
(1.15 x 10<sup>-9</sup> g/Pa•s•m<sup>2</sup>) (ASJ and FSK Facing)  
Class I vapor retarder
- Water Vapor Sorption:
  - ASTM C1104 / ≤ 5% by weight
- Corrosiveness:
  - ASTM C665 / Pass
- Fungal Resistance:
  - ASTM C1338 / Pass
- Odor Emission:
  - ASTM C1304 / Pass

#### Quality Assurance

CertainTeed's commitment to quality and environmental management has ensured the registration of the Athens, Chowchilla and Kansas City plants to ISO 9001:2000 and ISO 14001:2004 standards.

**MAINTENANCE**

An inspection and preventative maintenance program for the insulation and vapor retarder system is recommended to ensure optimum performance.

**TECHNICAL SERVICES**

Technical assistance can be obtained either from the local CertainTeed sales representative, or by calling Sales Support Group at 800-233-8990.

**FILING SYSTEMS**

- CertainTeed Pub. No. 30-25-056
- Additional product information available upon request.

Type	AVAILABLE SIZES				THERMAL PERFORMANCE				ACOUSTICAL PERFORMANCE						NRC
	Thickness		Density		Thermal Resistance		Thermal Conductivity		Absorption Coefficients @ Octave Band Frequency (Hz)						
	in.	mm	Lb/ft <sup>3</sup>	Kg/m <sup>3</sup>	R	RSI	Btu•in (h•ft <sup>2</sup> •°F)	W (m <sup>2</sup> •°C)	125	250	500	1000	2000	4000	
CB 110	1 1/2	38	1.10	17.57	6.0	1.06	0.25	0.036	0.25	0.51	0.85	0.97	1.00	1.03	0.85
	3 1/2	89	1.10	17.57	14.0	2.47	0.25	0.036	0.55	1.15	1.29	1.18	1.14	1.18	1.20
	6	153	1.10	17.57	25.0	4.20	0.25	0.036	1.09	1.45	1.26	1.13	1.11	1.10	1.25
CB 150	1 1/2	38	1.50	24	6.0	1.06	0.25	0.036	0.19	0.51	0.82	0.86	0.95	0.97	0.80
	2	51	1.50	24	8.0	1.41	0.25	0.036	0.23	0.61	0.94	0.97	0.98	0.96	0.90
	2 1/2	64	1.50	24	10.0	1.76	0.25	0.036	0.41	0.78	0.96	0.94	0.93	0.97	0.90
	3	76	1.50	24	12.0	2.11	0.25	0.036	0.41	0.94	1.07	1.01	1.00	0.97	1.00
	3 1/2	89	1.50	24	14.0	2.47	0.25	0.036	0.60	1.08	1.09	1.02	1.04	1.06	1.05
	4	102	1.50	24	16.0	2.82	0.25	0.036	0.64	1.05	1.07	0.97	0.96	1.01	1.00
CB 225	1	25	2.25	36	4.2	0.73	0.24	0.035	0.06	0.30	0.68	0.85	0.91	0.94	0.70
	1 1/2	38	2.25	36	6.3	1.10	0.24	0.035	0.12	0.48	0.83	0.90	0.90	0.89	0.80
	2	51	2.25	36	8.3	1.47	0.24	0.035	0.22	0.63	1.04	1.00	1.00	0.97	0.90
	2 1/2	64	2.25	36	10.4	1.83	0.24	0.035	0.31*	0.81*	1.08*	1.02*	1.04*	1.03*	1.00*
	3	76	2.25	36	12.5	2.19	0.24	0.035	0.34	0.95	1.08	0.99	0.98	0.99	1.00
	3 1/2	89	2.25	36	14.6	2.56	0.24	0.035	0.54	1.11	1.12	1.01	1.02	1.00	1.05
CB 250	1	25	2.50	40	4.2	0.73	0.24	0.035	0.05	0.25	0.66	0.98	1.04	1.07	0.75
	2	51	2.50	40	8.3	1.47	0.24	0.035	0.21	0.79	1.21	1.14	1.09	1.07	1.05
	1	25	3.00	48	4.3	0.77	0.23	0.033	0.08	0.25	0.72	0.88	0.93	0.94	0.70
	1 1/2	38	3.00	48	6.5	1.15	0.23	0.033	0.10	0.51	0.89	0.95	0.92	0.93	0.80
	2	51	3.00	48	8.7	1.53	0.23	0.033	0.21	0.73	1.08	1.04	1.04	0.96	0.95
	2 1/2	64	3.00	48	10.9	1.92	0.23	0.033	0.31	0.81	1.08	1.02	1.04	1.03	1.00
CB 300	3	76	3.00	48	13.0	2.30	0.23	0.033	0.41	0.96	1.13	1.03	1.03	1.02	1.05
	3 1/2	89	3.00	48	15.2	2.68	0.23	0.033	0.72	1.14	1.11	1.00	1.02	1.00	1.05
	4	102	3.00	48	17.4	3.06	0.23	0.033	0.75	1.18	1.09	1.00	1.00	1.02	1.05
	1	25	4.50	72	4.5	0.80	0.22	0.032	0.09	0.33	0.79	1.06	1.07	1.06	0.80
	2	51	4.50	72	9.1	1.6	0.22	0.032	0.32	0.95	1.19	1.11	1.04	1.02	1.05
	1	25	6.00	96	4.5	0.80	0.22	0.032	0.05	0.27	0.78	0.97	0.97	0.91	0.75
CB 600	1 1/2	38	6.00	96	6.8	1.20	0.22	0.032	0.17	0.50	0.98	1.03	0.99	0.98	0.90
	2	51	6.00	96	9.1	1.60	0.22	0.032	0.31	0.89	1.07	0.99	1.02	0.98	1.00

All/Service/Jacket (ASJ facing) is not available in Type CB 150.  
CB 110, 150 and 600 are not available in FSK, WMP or ASJ facings.

\* Estimated sound absorption coefficients and NRC. Sound absorption tested in accordance with ASTM C423 using Type A mounting per ASTM E795.



**ASK ABOUT OUR OTHER CERTAINTEED PRODUCTS AND SYSTEMS:**

ROOFING • SIDING • TRIM • DECKING • RAILING • FENCE • FOUNDATIONS  
GYPSUM • CEILINGS • INSULATION • PIPE

CertainTeed Corporation  
P.O. Box 860  
Valley Forge, PA 19482

Professional: 800-233-8990  
Consumer: 800-782-8777  
[www.certainteed.com/insulation](http://www.certainteed.com/insulation)

