



PVA Standard Interior Primer Sealer 1090-1200N

Previously ICI Paints PREP & PRIME® PVA Standard
Commercial Latex Interior Primer

DESCRIPTION

Our professional commercial interior latex primer for use under latex or alkyd paints on properly prepared new or previously painted drywall, concrete block and brick. Easy application by brush or roller. Dries quickly to proper hardness for easy sanding. Ideal for use on new and existing commercial structures such as schools, offices, apartments, hotels and hospitals.

CERTIFICATIONS

AS OF 7/1/2009, COMPLIES WITH	
MPI#	N/A
LEED	Yes
CHPS	Yes
GREENGUARD	No
AIM	Yes
OTC/LADCO	Yes
CARB	Yes
SCAQMD	Yes

PERFORMANCE DATA

CHARACTERISTIC:	RESULTS:
Enamel Hold Out*	★★★★★☆☆☆☆☆
Adhesion to Substrate*	★★★★★☆☆☆☆☆
Dry Hide*	★★★★★★★★★★★★
Sag Resistance	12-16 mils wet
Air and Substrate Application Temperature	50° F (10° C) - 90° F (32° C)
Service Temperature Limits	200° F (93° C)
Storage Temperature	40° F (4° C) - 95° F (35° C)

*Performance ratings are based on product comparisons to other products in that sheen range, performed at 77° F (25° C) 50% RH. Rating scale is from 1-10, 10 being the highest rating.

COMPOSITION

- Vinyl-Acrylic Resin
- Titanium Dioxide and Extender Pigments
- Not manufactured with lead or mercury containing materials.

SPECIFICATION

Color:

White, (tintable, limit up to 4 oz/gal)

Clean-up Solvent:

Soap and water

Finish: Flat

Sheen: 2.5 - 6.5 @ 85°

Density:

10.91 lbs/gal (1.31 kg/L)

Solids:

Volume - 24% +/- 1%

Weight - 42% +/- 1%

VOC:

50 g/L (0.42 lbs/gal) maximum

Refer to MSDS for regulatory VOC content of complete product line

Theoretical Coverage @ 1 mil dry:

389 sq ft/gal (10 m²/L)

Practical Coverage:

Apply at 250-300 sq ft/gal (6-7 m²/L).

Actual coverage may vary depending on substrate and application method.

Recommended Film Thickness:

5.3 - 6.4 mils wet

1.3 - 1.5 mils dry

Airless Spray Application:

Pressure - 2000 psi

Tip - .015" - .019"

Dry Time 77°F (25°C) & 50% RH:

To touch – 30 minutes

To recoat – 2 hours

Flame Spread Rating:

Class A (0-25) on non-combustible surfaces

Flash Point:

None

Shelf Life:

1 year minimum - unopened



www.gliddenprofessional.com

9 FINISHES
PAINTING (09900)



SURFACE PREPARATION

GENERAL SURFACE PREPARATION:

All surfaces must be sound, dry, clean and free of oil, grease, rust, dirt, mildew, form release agents, curing compounds, loose and flaking paint and other foreign substances.

NEW SURFACES:

Drywall:

- Joint compound must dry for two days before priming
- Prime with this product

Concrete and Masonry:

- Cure at least 30 days before painting
- pH must be 10.0 or lower
- Roughen slick poured or precast concrete and remove sealers by chemical cleaning or abrasive method such as sandsweeping
- Rinse thoroughly with water and allow to dry
- Remove loose aggregate
- Prime with this product

Concrete Block, Plaster, Wood, Steel, Galvanized Metal and Aluminum Surfaces:

- Use the appropriate GLIDDEN PROFESSIONAL™ primer

PREVIOUSLY PAINTED SURFACES:

- Wash to remove contaminants
- Rinse thoroughly with water and allow to dry
- Dull glossy areas by light sanding
- Remove sanding dust
- Remove loose paint
- Prime bare areas with the appropriate GLIDDEN PROFESSIONAL primer
- Porous flat finishes must be sealed with this product.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear an NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

SHIPPING

FREIGHT CLASSIFICATION:

Paint, Freezable

PACKAGING:

5 gallons (18.925 L)

FLASH POINT:

None

DIRECTIONS FOR USE

TINTING:

May be tinted toward the finish coat color with up to four oz/gal of DRAMATONE™ colorants.

SPREADING RATE:

Apply at 250-300 sq ft/gal (6-7 m²/L). Actual coverage may vary depending on substrate and application method.

APPLICATION:

Mix thoroughly before use. May be applied by brush, roller or airless spray. No thinning required. For airless spray, use a .015"-.019" tip at 2000 psi, adjust pressure as needed. Do not apply when the surface or air temperature is below 50°F (10°C). Provide good ventilation and warmth for normal drying.

DRYING TIME:

At 77°F (25°C) and 50% R.H., dries to touch in 30 minutes and to recoat in two hours. Low temperature, high humidity, thick films or poor ventilation will increase these times.

CLEAN-UP:

Clean hands and tools immediately with warm, soapy water. Clean spills right away with a damp cloth.

PRECAUTIONS

WARNING! CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION. CONTAINS CRYSTALLINE SILICA WHICH CAN CAUSE LUNG CANCER AND OTHER LUNG DAMAGE IF INHALED. MAY BE HARMFUL IF SWALLOWED. WHEN TINTED, CONTAINS ETHYLENE GLYCOL WHICH CAN CAUSE SEVERE KIDNEY DAMAGE WHEN INGESTED AND HAS BEEN SHOWN TO CAUSE BIRTH DEFECTS IN LABORATORY ANIMALS. USE ONLY WITH ADEQUATE VENTILATION. KEEP OUT OF THE REACH OF CHILDREN. For emergency information call (800) 545-2643. **Note:** These warnings encompass the product series. Prior to use, read and follow product-specific MSDS and label information. If sanding, wear a dust mask to avoid breathing of sanding dust. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. Avoid contact with eyes and skin. If you experience eye watering, headaches, or dizziness, leave the area. If properly used, a respirator may offer additional protection. Obtain professional advice before using. Close container after each use. **FIRST AID:** For skin contact, wash thoroughly with soap and water. If any product remains, gently rub with petroleum jelly, vegetable or mineral/baby oil then wash again with soap and water. Repeat as needed. Remove contaminated clothing. For eye contact, flush immediately with plenty of water for at least 15 minutes. **Get medical attention.** If swallowed, **get medical attention immediately.** If inhalation causes discomfort, remove to fresh air. If discomfort persists or breathing difficulty occurs, get medical attention. **KEEP FROM FREEZING.** DS4-1105



Akzo Nobel Paints LLC, Strongsville, Ohio 44136



www.gliddenprofessional.com

LIMITATION OF LIABILITY To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance but are subject to change without prior notice. We guarantee our product to conform to the specifications contained herein. WE MAKE NO OTHER WARRANTY OR GUARANTEE OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE. Liability, if any, is limited to replacement of the product or refund of the purchase price. LABOR OR COST OF LABOR AND OTHER CONSEQUENTIAL DAMAGES ARE HEREBY EXCLUDED.