

Concrete Coatings Slip Resistant Additive 3001-XXXX

Previously ICI Paints GROUNDWORKS™ Slip Resistant Additive

DESCRIPTION

A finely ground polymer material to be added to paint, concrete stains or sealers to achieve a slip resistant surface on walkways, driveways, garage floors, patios, pool decks and other horizontal surfaces.

DIRECTIONS FOR USE

Designed to be incorporated into a suitable paint, concrete stain or sealer. Minimum inclusion ratio of 3001 Concrete Coatings Slip Resistant Additive is as follows: .18 lbs bottle to a gallon can or .88 lbs bottle to a five-gallon pail. More may be added depending on the desired texturing effect, but not to exceed .36 lbs (6oz) per gallon. While continually stirring, add 3001 Concrete Coatings Slip Resistant Additive to the container of paint, concrete stain or sealer. It may tend to float at first, but once wet it will mix in easily. Occasional stirring, during application, may be required in thinner products to keep the particles well suspended within the coating. Follow application instructions of the paint, concrete stain or sealer. Use of this additive in materials should be for additional slip resistance as a safety measure and should not be used in place of a nonskid finish.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear an NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead..

COMPOSITION

- Vinyl-Acrylic Resin
- Titanium Dioxide and Extender Pigments
- Not manufactured with lead or mercury containing materials.

SPECIFICATION

Color:

White powder, transparent in clear coatings

Mean Particle Size:

160-180 (microns) 50 (mesh)

PRECAUTIONS

WARNING! CAUSES EYE. SKIN AND RESPIRATORY TRACT IRRITATION. MAY BE HARMFUL IF SWALLOWED. USE ONLY WITH ADEQUATE VENTILATION. KEEP OUT OF THE REACH OF CHILDREN. Note: Should be treated as a nuisance dust while incorporating it into its intended vehicle. For emergency information call (800) 545-2643. For additional safety information, refer to the Material Safety Data Sheet for this product. If sanding, wear a dust mask to avoid breathing of sanding dust. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. Avoid contact with eyes and skin. If you experience eye watering, headaches, or dizziness, leave the area. If properly used, a respirator may offer additional protection. Obtain professional advice before using. Close container after each use. FIRST AID: For skin contact, wash thoroughly with soap and water. If any product remains, gently rub with petroleum jelly, vegetable or mineral/baby oil then wash again with soap and water. Repeat as needed. Remove contaminated clothing. For eye contact, flush immediately with plenty of water for at least 15 minutes. Get medical attention. If swallowed, get medical attention immediately. If inhalation causes discomfort, remove to fresh If discomfort persists or breathing difficulty occurs, get medical attention. **KEEP FROM FREEZING.** MPL43-0210

SHIPPING

FREIGHT CLASSIFICATION:

Paint related material- non hazardous

PACKAGING:

18 lbs. .88 lb.

FLASH POINT:

None





accurate at the date of issuance but are subject to change without prior notice. We guarantee our product to conform to the specifications contained herein. WE MAKE NO OTHER WARRANTY OR GUARANTEE OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE. Liability, if any, is limited to replacement of the product or refund of the purchase price. LABOR OR COST OF LABOR AND OTHER CONSEQUENTIAL DAMAGES ARE HEREBY EXCLUDED.

LIMITATION OF LIABILITY To the best of our knowledge, the technical data contained herein are true and

www.gliddenprofessional.com

3001 - 02/10