



Imagine your business tomorrow.™

DECRA-FLEX Paint

DECRA-FLEX elastomeric coatings encompass a smooth finish and a textured coating. These coatings are our premium quality, high-build waterborne elastomeric coatings that provide a long-lasting, weather-resistant finish on exterior, above-grade vertical masonry and stucco surfaces. They may also be used on non-masonry substrates, such as primed wood, primed metal, and properly prepared, previously painted surfaces.

Decra-Flex 300 paint resists water intrusion against wind-driven rain, yet breathes to resist blistering.* Its superb elongation properties allow the film to expand and contract over existing hairline cracks without recurrence of cracking through the film. An outstanding product for maintenance on architectural, commercial and industrial structures, including hotels, office buildings, apartments, condominiums and schools.

BENEFITS

- Maintains flexibility even at low temperatures and after extended weathering
- Provides a consistent, uniform finish, even over hairline cracks
- Provides a water and weather-resistant film
- Protects against mildew growth on paint film
- Brings fresh visual appeal to old masonry with long-lasting color
- Low odor
- Stays cleaner for longer
- Tintable to meet your design needs

CERTIFICATIONS

- MPI 40, 113, 132
- CARB
- AIM
- SCAQMD
- OTC/LADCO



*When applied as directed, DECRA-FLEX 300 coating provides a water resistant film, even against 98 mph wind-driven rain, yet breathes to allow entrapped moisture vapor to escape, to avoid blistering.

Samples of this product were independently evaluated by The Master Painter Institute, Inc. and meet MPI Green Performance™ Standards (GPS-1-08). Akzo Nobel Paints LLC certifies that this conforms to the specifications originally evaluated by The Master Painters Institute, Inc. for MPI Green Performance™ Standards (GPS-1-08)



Imagine your business tomorrow.™

DECRA-FLEX Paint

FEATURES

- Elastomeric formulation
- Bridges existing hairline cracks
- Resistance to 98 mph wind-driven rain (passes TT-C-555B)
- Mildew resistant
- Excellent color retention
- Low VOC
- Resists dirt pickup
- Decra-Flex 200 Dry Film Thickness 6.0-8.0 mils
- Decra-Flex 300 Dry Film Thickness 6.0-12.0 mils
- Decra-Flex 300 Water vapor transmission - 30 perms (ASTM D1653)



Glidden Professional has a wide portfolio of products to fit your every project need. From multi-purpose primers to problem-solving specialty primers, masonry coatings to elastomerics and roof coatings, we have what you need to complete your job, on time, and within budget. For more information about our complete line of products, go to www.gliddenprofessional.com.



For a clean, textured exterior finish on your masonry surface, prep first with 6001 Hydrosealer

About Glidden Professional Paint Centers

AkzoNobel's portfolio of Glidden Professional™ branded paints are sold through Glidden Professional Paint Centers and authorized independent dealers across the United States. We also offer our customers access to AkzoNobel's protective coatings brands, Devoe® High Performance Coatings and International® Paint, as well as our woodcare brand Flood®. In addition to paints and related products, Glidden Professional Paint Centers offer contractors expert advice to simplify the product selection and delivery of any residential, commercial or industrial project. To learn more, visit www.gliddenprofessional.com.

Akzo Nobel Paints LLC
15885 West Sprague Road
Strongsville, Ohio 44136
1-800-984-5444

www.gliddenprofessional.com

® and TM indicate trademarks of the AkzoNobel group of companies unless otherwise indicated.
MPI Green Performance is a trademark and MPI logo is a certification mark of Master Painters
Institute Inc. U.S. Green Building Council member logo is used with permission.
©2012 AkzoNobel. All Rights Reserved.

GP027B