

SPEED-WALL®

From the Makers of  Glidden Paint.

Interior Latex Matte Flat Paint 1251-XXXX

DESCRIPTION

A matte flat latex wall and ceiling paint formulated to meet the requirements of painters, building contractors and building managers. Delivers high production with excellent dry hide and excellent touch-up ability. Features easy application, quick drying and recoat when applied by brush, roller or spray. Ideal for use on interior walls and ceiling surfaces in new and maintenance applications.

FEATURES

- Good Hide
- Uniform Flat Finish
- Good Touch-Up Properties
- Easy Soap and Water Clean-up
- Low Odor/VOC
- Fast Drying

COMPOSITION

- Vinyl Acrylic Resin
- Titanium Dioxide and Extender Pigments
- Not manufactured with lead or mercury containing materials.

SPECIFICATION DATA

Color:
White & custom colors

Finish:
Flat, 2.5 units maximum @ 85°

Clean-up Solvent:
Soap & water

Density:
10.17 lbs/gal (1.22 kg/L)

VOC:
50 g/L (0.42 lbs/gal) maximum

Solids:
Volume - 16% ± 1%
Weight - 31% ± 1%

Practical Coverage:
Apply at 300-400 sq ft/gal (7-10 m²/L).
Actual coverage may vary depending on substrate and application method.

Recommended Film Thickness:
4.0 - 5.3 mils wet
0.6 - 0.9 mils dry

Flame Spread Rating:
Class A (0-25) over non-combustible surfaces

Flash Point:
None

Dry Time 77°F (25°C) & 50% RH:
To touch – 30 minutes
To recoat - 2 hours

Shelf Life:
1 year minimum - unopened

SPEED-WALL®

9 FINISHES
PAINTING (09900)

SURFACE PREPARATION

All surfaces must be sound, dry, clean and free of oil, grease, dirt, mildew, form release agents, curing compounds, loose and flaking paint and other foreign substances.

NEW SURFACES: Drywall - Prime with GRIPPER® multi-purpose primer sealer (3210 or GL3210) or latex primer (1030 or GL1050). Wood - Prime with GRIPPER multi-purpose primer sealer (3210 or GL3210), latex undercoater (1020) or STAIN JAMMER® solvent-based primer sealer (1110 or GL1110). Concrete, Plaster and Masonry - Cure at least 30 days before painting. pH must be 10.0 or lower. Roughen slick poured or precast concrete and remove sealers by chemical cleaning or abrasive method such as sandsweeping. Rinse thoroughly with water and allow to dry. Must be internally dry. Remove loose aggregate. Prime with GRIPPER multi-purpose primer sealer (3210 or GL3210). Fill concrete block with latex block filler (3010, GL3010 or 4000). Steel - Prime with waterborne metal primer (4020) or solventborne metal primer (4160). Galvanized Metal and Aluminum - Prime

with GRIPPER multi-purpose primer sealer (3210 or GL3210), waterborne metal primer (4020) or solventborne metal primer (4160).

PREVIOUSLY PAINTED SURFACES: Wash to remove contaminants. Rinse thoroughly with water and allow to dry. Dull glossy areas by light sanding. Remove sanding dust. Remove loose paint. Prime bare areas with primer specified under NEW SURFACES.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear an NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

DIRECTIONS FOR USE

TINTING: Tint the appropriate base with universal colorants.

SPREADING RATE: Apply at 300-400 sq ft/gal (7-10 m²/L). Actual coverage may vary depending on substrate and application method. For best hiding, tint primers towards finish coat color. Certain shades of yellow, orange, pink and red may require multiple coats.

APPLICATION: Mix thoroughly before use. May be applied by brush, roller or spray. No thinning required. For spray

application, use a .015"-.017" tip. Adjust pressure as needed. Do not apply when the surface or air temperature is below 50°F (10°C). Provide good ventilation and warmth for normal drying.

DRYING TIME: At 77°F (25°C) and 50% R.H., dries to touch in 30 minutes and to recoat in two hours. Low temperature, high humidity, thick films or poor ventilation will increase these times.

CLEAN-UP: Clean immediately with warm, soapy water.

PRECAUTIONS

WARNING! CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION. MAY BE HARMFUL IF SWALLOWED. WHEN TINTED, CONTAINS ETHYLENE GLYCOL AND DIETHYLENE GLYCOL. ETHYLENE GLYCOL CAN CAUSE SEVERE KIDNEY DAMAGE WHEN INGESTED AND HAS BEEN SHOWN TO CAUSE BIRTH DEFECTS IN LABORATORY ANIMALS. DIETHYLENE GLYCOL MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS AND LIVER, KIDNEY DAMAGE. USE ONLY WITH ADEQUATE VENTILATION! KEEP OUT OF THE REACH OF CHILDREN. For emergency information call (800) 545-2643. **Note: These warnings encompass the product series. Prior to use, read and follow product-specific MSDS and label information.** For additional safety information, refer to the Material Safety Data Sheet for this product. If sanding, wear a dust mask to avoid breathing of sanding dust. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. Avoid contact with eyes and skin. If you experience eye watering, headaches, or dizziness, leave the area. If properly used, a respirator may offer additional protection. Obtain professional advice before using. Close container after each use. **FIRST AID:** For skin contact, wash thoroughly with soap and water. If any product remains, gently rub with petroleum jelly, vegetable or mineral/baby oil then wash again with soap and water. Repeat as needed. Remove contaminated clothing. For eye contact, flush immediately with plenty of water for at least 15 minutes. **Get medical attention.** If swallowed, **get medical attention immediately.** If inhalation causes discomfort, remove to fresh air. If discomfort persists or breathing difficulty occurs, get medical attention. **KEEP FROM FREEZING.**

DS396-1205

SHIPPING

FREIGHT CLASSIFICATION:
Paint, Freezable

PACKAGING:
1 gallon (3.785)
5 gallons (18.925 L)

FLASH POINT:
None

