

INDUSTRIAL SECURITY



The Alpha gate fuses top industrial design with reliable, functional quality.

This mix of aesthetic appeal and function can turn your entrance both stylish and secure. The Alpha gate answers the needs of the enterprise end user and local installers with straight forward sizing and options. Quick delivery time, minimized shipping costs and virtually zero down time allow businesses to operate profitably while meeting current safety and security requirements.





IMMOVABLE • WITHSTAND • UNBREACHABL

INDUSTRIAL SECURITY



Clean, aesthetically pleasing design



Anti-climb top rai



Post and guide rollers



Post mounted kinetic gate operator

TECHNICAL DATA	UNIT	ALPHA
Voltage	VAC	110 - 240V
Frequency	HZ	50 - 60
Current	Α	15
Duty Cycle	%	100
Max. Clear Drive Thru Width	Feet (m)	40' (12)
Max. Gate Panel Height	Feet (m)	8'+1' (2.7)
Gate Infill	Panel Infill	9 gage chain link
Finish	Coating	Galvanized and/or Powder-Coated
Operating Temp Range	°F (°C)	-40 to +120 (-40 to +49)

TECHNICAL SPECIFICATIONS

- Patented aluminum beam construction providing a strong rigid gate without unnecessary weight
- Internal tensioning rods for unequalled structural integrity
- Concealed nylon composite rollers and lockable metal gate operator cover offers a tamperresistant gate
- Post mounted gate operator ensures continual drive gear alignment
- · Anti-climb toprail for added security and increased threat delay
- Rack & Pinion drive offers a cleaner, quieter, more secure operation than traditional chain driven systems
- Variable speed drive maximizes gate and hardware life
- Thru-Beam Photo Cell
- Uninterruptable power supply
- ASTM, UL, C.S.A. Approved
- Anti-Tailgate Logic

STANDARD FINISH

- Aluminum beam and toprail
- Galvanized pickets and portals (posts)
- Custom powder-coated colors available on request

OPTIONS

- Traffic Lights (bidirectional)
- Strobe Light
- Vehicle Detectors
- Extreme Cold-Weather Kit
- Solar Kit
- 1 or 2 foot per second travel





Not all height and width combinations are available.

1' High (3 rows) of barbed wire is available on most height and width combinations.