








CROSS REFERENCE ACCESS DOOR

ACCESS DOORS (GP, UAD, BASIC, AL, GP LV, GP VIS, RP)

WB Product Number	Description	Acudor #	Babcock #	Cendrex #	Elm #	Karp #	J.L. Ind #	Larson #	Mifab #	Milcor #	Nystrom #	
 <p>BEST! Fully concealed offset hinges up to 24 x 24</p> <p>WB GP 100 Series</p>	<p>Visit www.wbdoors.com to download submittals and CAD drawings.</p>	<p>No other access door compares to the WB Premium 100 Series</p>										
		NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	
<p>The Premium Door in the Building Industry. General Purpose Premium, 14 ga. door, fully concealed offset hinge up to and including 24 x 24. Laser cut. Radius corners. Cam latch opens w/screwdriver. Gasketing on 4 sides. Meets all architectural specifications.</p>												
 <p>BETTER! Semi-concealed hinge</p> <p>WB UAD 200 Series</p>	<p>Visit www.wbdoors.com to download submittals and CAD drawings.</p>	UF-5000	NA	NA	NA	NA	TM	NA	NA	NA	NA	
<p>Utility, Meets most architectural specifications. 16 ga. steel. Trim 1-1/2" wide, Full length semi-concealed piano hinge. Laser cut. Cam latch opens with screwdriver. Gasketing on 3 sides.</p>												
 <p>GOOD! Pin Lug hinge</p> <p>WB BASIC 300 Series</p>	<p>Visit www.wbdoors.com to download submittals and CAD drawings.</p>	NA	NA	AHD	NA	NA	NA	NA	NA	NA	NA	
<p>The Contractor's Door. Our most Economical Door. 18 ga. steel (up to & including 16" x 16") and 16 ga. steel (18" x 18" - 24" x 24") Pin Lug hinge. Cam latch opens with screwdriver. Gasketing not available.</p>												
 <p>WB AL 1500 Aluminum Series</p>	<p>Lightweight, insulated. Concealed continuous piano type hinge, insulated with 1" TUFF-R polyisocyanurate. All aluminum.</p>	LT 4000	NA	PAL	NA	NA	NA	NA	NA	NA	NA	
 <p>WB GP LV 100 Series</p>	<p>SPECIAL - with louvers. 14 ga. Steel door. Trim is 1-1/2" wide, Fully-concealed hinge up to and including 24 x 24. Laser cut. Available in WB UAD.</p>	NA	NA	AHD LOUVER	NA	NA	NA	NA	NA	NA	NA	
 <p>WB GP VIS 100 Series</p>	<p>SPECIAL - Full glass in 14 ga. door, Fully-concealed hinge up to and including 24 x 24. Laser cut</p>	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	
 <p>WB RP 110 Series</p>	<p>Removable Panel. Same quality features as the WB Premium door. For use in confined areas. Door is 14 ga. steel. Trim 1-1/2" wide. Laser cut. Cam latches opens with screwdriver.</p>	PA-3000	NA	NA	NA	WSR SERIES	NA	NA	NA	NA	NA	










WILLIAMS BROTHERS CORPORATION OF AMERICA

Corporate Office 1330 Progress Drive, Front Royal, VA 22630 Western Distribution Center 4058 S. McCarran Blvd., Bldg.A, Reno, NV 89502
Phone: 1-800-255-5515 • Fax: 1-800-822-5001 • Website: www.wbdoors.com

For country of manufacture of all Williams Brothers products please call us or visit our website at www.wbdoors.com

CROSS REFERENCE ACCESS DOOR

ACCESS DOORS (SMP, DW, RDW, PL, AP, AT)

WB Product Number	Description	Acudor #	Babcock #	Cendrex #	Elm #	Karp #	J.L. Ind #	Larson #	Mifab #	Milcor #	Nystrom #
 WB SMP 120 Series	Surface Mounted. 14 ga. steel. Trim 1-1/2" wide. Full length piano hinge allows door to open to 180°	SF-2000	NA	SFM	SF	DSC-214SM	NA	NA	MI-SF	NA	NA
 WB DW 400 Series	Drywall Bead. 14 ga. Steel, Frame is 16 ga. Steel, 1" wide perforated flange of 24 ga. galvanized steel for mounting purposes	DW-5040	AHD GYP	B-NP	DWB	KDW	WB	L-DWB	MDW	3023 (DW)	NM
 WB RDW 410 Series	Recessed-Drywall Bead. 14 ga. steel, 1" recessed depth accommodates drywall. Frame is 16 ga. Steel, 1" wide perforated flange of 24 ga. galvanized steel for mounting purposes.	DW-5015	B-NW	AHA GYP	NA	RDW	NA	L-DWR	CAD-DW	NA	RW
 WB RDW 410-2 Series	Recessed-Drywall Bead. with 5/8" gypsum board preinstalled. 14 ga. steel, 5/8" recessed depth accommodates drywall. Frame is 16 ga. Steel, 1" wide perforated flange of 24 ga. galvanized steel for mounting purposes.	DW-5015	B-NW	AHA GYP	NA	RDW	NA	L-DWR	CAD-DW	NA	RW
 WB PL 500 Series	Plaster Bead. 14 ga. Steel, Frame is 16 ga. Steel, 3" wide expanded flange 24 ga. galvanized material, space from the expanded flange to 1/4" safety edge will accommodate 1 3/4" of plaster	PS-5030	B-NP	AHD PLY	ML	DSC-214PL	PW	L-PSW	CAD-FL-PL	3200 K	NA
 WB AP 510 Series	Recessed Plaster Bead. 14 ga. steel. Door is recessed 1" and lined with expanded metal lath. Frame is 16 ga. steel w/ 24 ga. galvanized casing bead and expanded metal lath surrounding door	AP-5010	B-RP	AHA-PLY	AP	DSC-210PL	CP	L-APC	CAD-PL	3206 (AP)	RP
 WB AT 600 Series	Accoustical Tile (not available in drywall) 14. ga. steel. Door is recessed to accommodate up to 1" thick acoustical tile, Frame is 16 ga. Steel, Continuous piano hinge opens 180°	AT-5020	B-RA	AHA	AT	DSC-210	CT	L-CPA	CAD	3205 (AT)	RA






WILLIAMS BROTHERS CORPORATION OF AMERICA

Corporate Office 1330 Progress Drive, Front Royal, VA 22630 Western Distribution Center 4058 S. McCarran Blvd., Bldg.A, Reno, NV 89502
 Phone: 1-800-255-5515 • Fax: 1-800-822-5001 • Website: www.wbdoors.com

For country of manufacture of all Williams Brothers products please call us or visit our website at www.wbdoors.com

CROSS REFERENCE ACCESS DOOR

ACCESS DOORS (AT, ATR)

WB Product Number	Description	Acudor #	Babcock #	Cendrex #	Elm #	Karp #	J.L. Ind #	Larson #	Mifab #	Milcor #	Nystrom #
 WB AT 600-2 Series	Accoustical Tile with 5/8" gypsum board preinstalled. (not available in drywall) 14. ga. steel. Door is recessed to accommodate up to 1" thick acoustical tile, Frame is 16 ga. Steel, Continuous piano hinge opens 180°	AT-5020	B-RA	AHA	AT	DSC-210	CT	L-CPA	CAD	3205 (AT)	RA
 WB ATR 610 Series	Fire-Resistive Ceiling for Accoustical Tile (not available in drywall) 16 ga. steel recessed 1-1/2", Frame is 16 ga. steel, hat channel type shape Continuous piano hinge allowing 180°	NA	NA	NA	CFR	KATR	NA	L-CPB	CAD-FR	3204 (ATR)	NA
 WB ATR 610-2 Series	Fire-Resistive Ceiling for Accoustical Tile with 5/8" gypsum board preinstalled. (not available in drywall) 16 ga. steel recessed 1-1/2", Frame is 16 ga. steel, hat channel type shape Continuous piano hinge allowing 180°	NA	NA	NA	CFR	KATR	NA	L-CPB	CAD-FR	3204 (ATR)	NA






WILLIAMS BROTHERS CORPORATION OF AMERICA

Corporate Office 1330 Progress Drive, Front Royal, VA 22630 Western Distribution Center 4058 S. McCarran Blvd., Bldg.A, Reno, NV 89502
 Phone: 1-800-255-5515 • Fax: 1-800-822-5001 • Website: www.wbdoors.com

For country of manufacture of all Williams Brothers products please call us or visit our website at www.wbdoors.com

CROSS REFERENCE ACCESS DOOR

ACCESS DOORS (FR PRE, FR, FRU, FR DW, FR PL, FRB)

WB Product Number	Description	Acudor #	Babcock #	Cendrex #	Elm #	Karp #	J.L. Ind #	Larson #	Mifab #	Milcor #	Nystrom #
 <p>WB FR PRE 700 Series</p>	<p>Premium Heavy Duty. Fire-Rated/Walls Only 14 ga. steel. Inside door has rolled safety edges for protection, Frame is 16 ga. steel, 2 1/2" deep, Insulation is 2" thick mineral wool (ThermaFiber®), between two pieces of 22 ga. steel, Continuous piano hinge allows opening to 180°</p>	NA	B-ST	NA	NA	NA	HGFD	NA	NA	NA	FST
 <p>WB FR 800 Series</p>	<p>Standard. Fire-Rated/Walls & Ceilings 18 ga. Steel, Frame is 16 ga. steel, 2 1/2" deep, Insulation is 2" thick mineral wool (ThermaFiber®), in between two pieces of 22 ga. steel</p>	FW-5050	B-IT	PFI	FRC	KRP-150FR	FD	L-FRAP	MPFR	NA	IT
 <p>WB FRU 810 Series</p>	<p>Standard Ultra. Fire-Rated/Walls & Ceilings 18 ga. Steel, Frame is 16 ga. steel, 2 1/2" deep, Insulation is 2" thick mineral wool (ThermaFiber®), in between two pieces of 22 ga. Steel, Fully concealed, pivot rod type hinge. Allows opening to 140°</p>	NA	NA	NA	NA	NA	NA	NA	NA	3218 (UFR)	NA
 <p>WB FR DW 820 Series</p>	<p>Fire-Rated/Walls & Ceilings Drywall Bead. 18 ga. steel, IFrame is 16 ga. steel, 1" wide perforated flange of 24 ga galvanized material for mounting purposes, 2 1/2" deep, Insulation is 2" thick mineral wool (ThermaFiber®), between two pieces of 22 ga. steel</p>	NA	B-IW	PFI GYP	FRC-GB	KRP-350FR	FDWB	NA	MPFR-DW	NA	IW
 <p>WB FR PL 830 Series</p>	<p>Fire-Rated/Walls & Ceilings Plaster Bead. 18 ga. steel, Frame is 16 ga. steel, 3" wide perforated flange of 24 ga. galvanized material for mounting, space from expanded flange to 1/4" safety edge of door accommodates 1" plaster, 2 1/2" deep, Insulation: 2" thick mineral wool (ThermaFiber®), contained within door cavity</p>	NA	B-IP	NA	NA	NA	FDPW	NA	NA	NA	IP
 <p>WB FRB 900 Series</p>	<p>Fire-Rated/Walls Only Uninsulated 14 ga. steel. Frame is 16 ga. steel, 2 1/2" deep, Hinge is Continuous piano hinge. Allows opening to 180°. Latches are Self-latching direct action latch accepts both key and knurled knob"</p>	FB-5060	B-UT	PFN	FR	KRP-250FR	NA	NA	MFRU	NA	UT
 <p>WB FR 850 Series</p>	<p>Upward Swinging - Fire-Rated Ceiling 16 ga. steel flush to frame, with reinforced edges. Door filled with 2" thick fire insulation. 16 gauge mounting frame with 1" trim. Concealed hinge w/coil spring for dampening. L Latch, operable from both sides.</p>	NA	NA	NA	NA	NA	NA	NA	NA	3210 (CFRAD)	NA










WILLIAMS BROTHERS CORPORATION OF AMERICA







Corporate Office 1330 Progress Drive, Front Royal, VA 22630 Western Distribution Center 4058 S. McCarran Blvd., Bldg.A, Reno, NV 89502
 Phone: 1-800-255-5515 • Fax: 1-800-822-5001 • Website: www.wbdoors.com

For country of manufacture of all Williams Brothers products please call us or visit our website at www.wbdoors.com

ACCESS DOORS (MD SEC, HG SEC, GY, TB, MAP, DUCT, EXT)

WB Product Number	Description	Acudor #	Babcock #	Cendrex #	Elm #	Karp #	J.L. Ind #	Larson #	Mifab #	Milcor #	Nystrom #
 <p>WB MD SEC 1000 Series</p>	<p>Medium Security Access Door 12 ga. steel door, 16 ga. steel frame, semi-concealed piano hinge. Counter sunk tamperproof screws, snake eye screwdriver is required. (not included)</p>	MS-7000	B-MT	PSM	SLK	DSB-123	SP	L-DPM	MI-SAD	3211-200	MT
 <p>WB HG SEC 1100 Series</p>	<p>High Security Access Door 10 ga. door, 2" x 2" x 3 1/16" angle frame, heavy duty butt hinges. Prepped for detention lock with paracentric key. (not included)</p>	SD-6000	B-HS	PSH	SLA	DSB-123-SD	HSP	L-DPH	MI-SADH	3211	HS
 <p>WB GY 3000 Series</p>	<p>Lightweight Gypsum Ceiling Panel Exceeds all required specifications that the market expects. 5/8" lightweight Gypsum drop-in-door.</p>	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
 <p>WB GY 3100 Series</p>	<p>Lightweight Gypsum Ceiling Panel with Hinge Exceeds all required specifications that the market expects. 5/8" lightweight Gypsum drop-in-door.</p>	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
 <p>WB MAP Plastic</p>	<p>Reversible Access Door High impact ABS plastic. Door locked to return frame with snap friction catch, removable panel, tile-able.</p>	NA	B-PL	NA	NA	HA	NA	NA	PA	NA	PL
 <p>WB ADC/ADH 1400 Series</p>	<p>True Fit Duct Access Door 22 ga steel flanged frame, 22 ga steel door. ADH-D - continuous hinge, ADC-D - no hinge.</p>	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
 <p>WB EXT 1300 Series</p>	<p>Visit www.wbdoors.com to download submittals and CAD drawings.</p>	<p style="text-align: center;">No other access door compares to the WB EXT 1300 Series</p> <p style="text-align: center;">NA NA NA NA NA NA NA NA NA NA NA</p> <p style="text-align: center;">Uncomparable Exterior Access Door. 16 ga. steel door, trim 1-1/2" wide, 16 ga. steel frame, 2-3/8" depth Insulation: Double layer of 1" GreenGuard® Extruded Polystyrene insulation board, with R-Value @ 75°F Mean 5.0 x 2, FM approved.</p>									

ACCESS DOORS (WIN, AL, ADWT)

WB Product Number	Description	Acudor #	Babcock #	Cendrex #	Elm #	Karp #	J.L. Ind #	Larson #	Mifab #	Milcor #	Nystrom #
 <p>WB WIN 1700 Series</p>	<p>Insulated Walk-In Duct Door 20 ga. galvanized steel door, 16 ga galvanized steel frame. 1" 3lb density insulation. 2 exterior latches with interior handles. 1/2" neoprene closed cell door to frame gasketing.</p>	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
 <p>WB AL 1500 Series</p>	<p>Premium Lightweight All Aluminum Door Non-Extruded Aluminum .063 door and surround trim, flush to edge of frame which is 1 5/16" mitered aluminum extrusion flange with 1-1/2" deep mounting frame. 4 sides closed cell neoprene gasketing.</p>	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
 <p>WB AL 4000 Series</p>	<p>Lightweight All Aluminum Door Extruded Aluminum .063 door and surround trim, flush to edge of frame which is 1 5/16" mitered aluminum extrusion flange with 1-1/2" deep mounting frame. 4 sides closed cell neoprene gasketing.</p>	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
 <p>WB ADWT Series</p>	<p>Airtight/Watertight Door 16 ga. stainless steel or steel door, 16 ga mounting frame. Flush to frame, reinforced edges, continuous exposed piano hinge. Air infiltration less than 0.01 cfm/sq foot-ASTM E 283</p>	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
 <p>WB TB 1200 Series</p>	<p>Drop-In Ceiling Access Door 16 ga. steel, continuous piano hinge, flush, stainless steel cam latch. Drops into the T-Bar ceiling grid. White baked enamel coat. Comes with mounting screws.</p>	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
 <p>WB BP-II 450 Access Door</p>	<p>Virtually Invisible Access Designed for Drywall. Strong concealed aluminium frame and steel hardware, concealed mechanical touch-latch, lift-out doors with safety cables, moisture resistant GWB inlay, perimeter gasket virtually air & smoke tight.</p>	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA