





| | | | | | |
|---|---|-------|--------|---|--|
| SEALER 10 GRAY VOC: < 650 g/l | Fast drying universal primer for automotive, fleet and industrial painting. For Professional Use Only** | 21041 | GALLON | 2 |  |
|---|---|-------|--------|---|--|



ARCHITECTURAL AND INDUSTRIAL MAINTENANCE

ADDITIVES

| PRODUCT | DESCRIPTION AND APPLICATION | PART # | SIZE | PACK | |
|---------------------------|---|-----------------|-----------------|--------|--|
| X-TENDER™ | Slow evaporating additive to retard the drying of fast-dry alkyd and solvent based primers/paints including XIM 400W NT 100. Add 1-2 ounces per gallon. Improves brush & roll applications. Eliminates “dry-spraying”. Does not amber with age. | 1103R2 11031 | QUART GALLON | 4 2 |  |
| LATEX X-TENDER™ | “Open Time”, Flow and Leveling additive for fast drying latex and water based primers/paints including epoxies and elastomers. Does not haze clear varnishes when added. Use with confidence to improve application and drying. | 11072 11071 | QUART GALLON | 4 2 |  |
| BLEED CONTROL 100™ | Additive for water based paints, primers and stains. Helps to control the extractive bleeding and discoloration associated with redwood, red cedar, T111 siding, etc. Add 4 ounces per gallon. | 11427 | 4 OZ | 6 |  |








ARCHITECTURAL AND INDUSTRIAL MAINTENANCE

8/2013



“BONDERS” (SOLVENT BASED)

(BONDING PRIMERS/SEALERS)

| PRODUCT | DESCRIPTION AND APPLICATION | PART # | SIZE | PACK | |
|--|---|------------------------------------|---|------------------|---|
| FLASH BOND® 400 CLEAR VOC: < 650 g/l | Quick Dry, Clear Bonding Primer/Sealer. Interior or Exterior. Alkyd Topcoats. For Tough-To-Paint surfaces: Glass, Tile, Formica®, Metals, Many Plastics, Wood and other construction materials. | 11015 1101R2 11011 1101R6 | AEROSOL QUART GALLON 5 GALLON PAIL | 6 4 2 1 |  |
| FLASH BOND® 400C NT Clear, Deep Tintable VOC: < 100 g/l | 100 g/l Alternative to 400 Clear. For Tough-To-Paint surfaces: Glass, Tile, Formica®, Metals, Many Plastics, Wood and other construction materials. Tintable with up to 4 oz. colorant. | 11611 1161R6 | GALLON 5 GALLON PAIL | 2 1 |  |
| 400 WHITE VOC: < 450 g/l | Quick Dry, White Bonding Primer/Sealer. Interior or Exterior. Alkyd or Latex Topcoats. For Tough-To-Paint surfaces: Glass, Tile, Formica®, Metals, Many Plastics, | 1102A5 11022 11021 11026 | AEROSOL QUART GALLON 5 GALLON PAIL | 6 4 2 1 |  |
| 400W NT 100 Replaces 400W NT and 400W ES VOC: < 100 g/l | 100 g/l Alternative to 400 White Quick Dry, White Bonding Primer/Sealer. All topcoats-for Tough-To-Paint surfaces: Interior/Exterior Glass, Tile, Formica®, Metals, Many Plastics, Wood and other construction materials. Including: Kynar® and Silicone Polyester pre-coated siding. | 11625 11622 11621 11626 | AEROSOL QUART GALLON 5 GALLON PAIL | 6 4 2 1 |  |
| PLASTIC & VINYL NT BONDER VOC: < 100 g/l | 100 g/l Alternative to Plastic & Vinyl Bonder Quick Dry, White, High Solids Bonding Sealer. Interior or Exterior. All topcoats (except lacquers). For plastic surfaces including Polypropylene, PVC, Acrylic and many other Plastic construction materials. | 11435 11432 11431 | AEROSOL QUART GALLON | 6 4 2 |  |

“BONDERS” (WATER BASED)

(BONDING PRIMER / SEALERS)

| PRODUCT | DESCRIPTION AND APPLICATION | PART # | SIZE | PACK | |
|---|---|----------------------------------|---|------------------|---|
| Advanced Technology UMA® WHITE VOC: < 100 g/l | Quick Dry, White Bonding Primer/Sealer. Interior or Exterior. All topcoats. For Tough-To-Paint surfaces: Glass, Tile Formica®, Metals, Many Plastics, Wood and other construction materials including Kynar® and Silicone Polyester pre-coated siding. | 11055 11052 11051 11056 | AEROSOL QUART GALLON 5 GALLON PAIL | 6 4 2 1 |  |
| Advanced Technology UMA® TINTABLE BASE VOC: < 100 g/l | Quick Dry, Tintable Base version of UMA Bonding Primer/Sealer. Interior or Exterior. Can be used as a deep tone tint base Bonder. All topcoats. For Tough-To-Paint surfaces: Glass, Tile, Formica®, Metals, Many Plastics, Wood and other construction materials. Up to 4 oz Tint. | 11062 11061 11066 | QUART GALLON 5 GALLON PAIL | 4 2 1 |  |





ARCHITECTURAL AND INDUSTRIAL MAINTENANCE

SEALERS

| PRODUCT | DESCRIPTION AND APPLICATION | PART # | SIZE | PACK | |
|---|--|----------------|-------------------------|--------|--|
| 900 CLEAR COAT VOC: < 630 g/l | Clear, acrylic alkyd protective sealer for decorative metals . Fast drying. For doors, windows, Brass, Copper, Aluminum, etc. Interior or Exterior. (Not for use on Exterior Wood or Steel) "NOT FOR SALE IN CALIFORNIA" | 21305 | AEROSOL | 6 | |
| | | 21302 | QUART | 4 | |
| | | 21301 | GALLON | 2 | |
| REPAIRZ™ WALL SEALER Previously RESTORZ II VOC: <100 G/L | Fast drying, water based penetrating primer and penetrating sealer/wall repair for interior walls and surfaces. Helps block moisture while remaining breathable. Eliminates bubbles. Wallpaper Strippable. Seals: Drywall Mud, Adhesive and Paste Residue. No drip formula dries hazy clear. | 11641 11646 | GALLON 5 GALLON PAIL | 2 1 | |

PRIMERS (SOLVENT BASED)

| PRODUCT | DESCRIPTION AND APPLICATION | PART # | SIZE | PACK | |
|---|--|--------|--------|------|--|
| 360 NT GRAY PRIMER Replaces 360 Gray Primer VOC: < 100 g/l | 100 g/l Alternative to 360 PRIMER Quick Dry Solvent Based Rust Inhibiting Primer for Iron, Steel and Ferrous Metals. Latex or alkyd topcoats Interior or Exterior. | 21711 | GALLON | 2 | |

PRIMERS (WATER BASED)

| PRODUCT | DESCRIPTION AND APPLICATION | PART # | SIZE | PACK | |
|--|---|--------|---------------|------|--|
| PEEL BOND™ VOC: < 100 g/l | Clear, High Build, Water Based Bonding Primer Sealer and Filler. Remains flexible. Interior or Exterior. Acrylic Latex and Elastomeric paints. Bonds to Old Paint, Wood, Plywood, T111, PVC, Aluminum, Galvanized Metal, Brick, Stucco. | 11462 | QUART | 4 | |
| | | 11461 | GALLON | 2 | |
| | | 11466 | 5 GALLON PAIL | 1 | |
| TRIM MAGIC™ VOC: < 100 g/l | Clear, Very High Build, Water Based Bonding Primer Sealer and Filler. Remains flexible. Interior or Exterior. Acrylic Latex and Elastomeric paints. Bonds to Old Paint, Wood, Plywood, T111, PVC, Aluminum, Galvanized Metal, Brick, Stucco. | 11542 | QUART | 4 | |
| | | 11541 | GALLON | 2 | |

PRIMER SEALERS (SOLVENT BASED)

| PRODUCT | DESCRIPTION AND APPLICATION | PART # | SIZE | PACK | |
|---------------------------------------|--|--------|---------------|------|--|
| RESTORZ™ VOC: < 350 g/l | Quick Dry, White, High Solids. Shellac Alternative Sealer ; Fire Restoration, Stain Blocker and Odor Sealer. For Interior use-spot exterior. Seals knots, pet and nicotine odors along with smoke damage/odors in fire restoration work. | 11395 | AEROSOL | 6 | |
| | | 11391 | GALLON | 2 | |
| | | 11396 | 5 GALLON PAIL | 1 | |
| X-SEAL™ VOC: < 350 g/l | Solvent Based Specialty Primer, Sealer and Stain Blocker for Interior or Exterior use. Use with Alkyd or Latex topcoats. Brush, Roll or Spray. Wood, Drywall, etc. New or Old Construction. | 11305 | AEROSOL | 6 | |
| | | 11302 | QUART | 4 | |
| | | 11301 | GALLON | 2 | |
| | | 11306 | 5 GALLON PAIL | 1 | |



ARCHITECTURAL AND INDUSTRIAL MAINTENANCE

PRIMER SEALERS (WATER BASED)

| PRODUCT | DESCRIPTION AND APPLICATION | PART # | SIZE | PACK | |
|---|--|--------|---------------|------|--|
| PRIME START® VOC: < 100 g/l | Fast Dry, White Acrylic Primer, Sealer and Stain Blocker. Interior or Exterior use. Use with Alkyd or Latex topcoats. Brush, Roll or Spray. Wood, Drywall, etc. New or Old Construction. 'MPI /Green Certified' | 11252 | QUART | 4 | |
| | | 11251 | GALLON | 2 | |
| | | 11256 | 5 GALLON PAIL | 1 | |

SPECIALTY COATINGS & PREP

| PRODUCT | DESCRIPTION AND APPLICATION | PART # | SIZE | PACK | |
|--|---|--------|-----------------|------|--|
| TILE DOC™ EPOXY ACRYLIC COATING VOC: < 380 g/l | An Acrylic modified Epoxy for refinishing tubs, sinks, and shower areas that's made to hold up to HOT , Soapy Water. Use on ceramic, Porcelain, Fiberglass, and Acrylic surfaces. Mix equal parts of Part A & B. Bright White; Tintable to pastel tones. KIT CONTAINS 1 EACH OF Part A & Part B. KITS: Tile DOC Pint Kit: 1 Pint A & 1 Pint B Tile DOC Quart Kit: 1 Qrt A & 1 Qrt B Tile DOC Gallon Kit: 1 Gal A & 1 Gal B | 4205A5 | AEROSOL | 6 | |
| | | 42012 | QUART (Part A) | 4 | |
| | | 42022 | QUART (Part B) | 4 | |
| | | 42011 | GALLON (Part A) | 2 | |
| | | 4202R1 | GALLON (Part B) | 2 | |
| | | 54020K | 2 PINT KIT | 6 | |
| | | 54022K | 2 QUART KIT | 1 | |
| 54021K | 2 GALLON KIT | 1 | | | |
| ETCH-I-M™ | Water Based Etching Cream that "dulls" ceramic and glazed porcelain surfaces in 10 minutes. Prepares surfaces for Tile DOC®. | 44082 | QUART | 4 | |
| | | 44081 | GALLON | 2 | |
| | | 44086 | 5 GALLON PAIL | 1 | |

SPECIALTY PRODUCTS

| PRODUCT | DESCRIPTION AND APPLICATION | PART # | SIZE | PACK | |
|--|--|--------|--------|------|--|
| GON™ Prep Cleaner | Pre-Paint cleaner and surface Prep. Removes difficult deposits of dirt, grease, wax, tar, silicones and adhesives. Solvent Based. For Professional Use Only** | 44011 | GALLON | 2 | |
| FLASH BOND™ 300 VOC: < 750 g/l | Adhesion promoter and fortifier for synthetic and acrylic automotive enamels. Fleet use. For Professional Use Only** | 21011 | GALLON | 2 | |