

aptiQ™

## MT20

Multi-technology enrollment reader with ENGAGE™ technology



### Overview

The aptiQ™ MT20 USB and Bluetooth Low Energy (BLE) multi-technology enrollment reader with ENGAGE™ technology is designed to simplify your enrollment process. The MT20 simplifies the enrollment of proximity, smart or mobile credentials in an access control system by using a computer's USB connection or the ENGAGE mobile app with BLE connection. The MT20 does not require software to operate when using a USB connection and will function on any operating system. When using a BLE connection, only the ENGAGE mobile app is required.

The USB connection emulates a keyboard and will keystroke the facility code and badge ID from the credential to the cursor's location on the screen. With the BLE connection and ENGAGE mobile app, the reader will pass credential information directly to the app.

The MT20 is compatible with aptiQ smart credentials (MIFARE® Classic and MIFARE DESFire™ EV1), aptiQmobile™ credentials, PIV credentials, and most proximity credentials.

### Features and benefits

- Use your computer or the ENGAGE mobile app to easily enroll credentials in your access control system or NDE locks
- Recognizes aptiQ smart credentials (MIFARE® Classic and MIFARE DESFire™ EV1), aptiQmobile credentials, PIV credentials, and most proximity credentials
- Limited Lifetime Warranty



Model	MT20
Reader type	USB and Bluetooth Low Energy
Software and operating system requirements	N/A - USB ENGAGE app - BLE
Bit formats recognized	26A, 32X, 34N, 34S, 35C, 37X, 37H, 40X
Technologies supported	Schlage Proximity XceedID™ Proximity HID® Proximity GE/CASI ProxLite® AWID® Proximity LenelProx®  Schlage MIFARE® Secure Sector XceedID™ MIFARE® Secure Sector aptiQ™ Smart Cards using MIFARE DESFire™ EV1 with PACSA DESFire® CSN HID iClass® CSN Inside Contactless PicoTag® CSN ST Microelectronics® CSN Texas Instruments Tag-It® Serial Number Phillips I-Code® CSN
Physical dimensions (l x w x h)	5.56" x 2.00" x .695"
Operating temperatures	0 to 40 C
Weight	4.1 oz
Power supply	Connect to powered USB port or via USB power supply
Interface	USB and Bluetooth Low Energy
Current requirement	160 mA

Allegion, the Allegion logo, Schlage, aptiQ, the aptiQ logo, aptiQmobile and XceedID, are trademarks of Allegion plc, its subsidiaries and/or affiliates in the United States and other countries. All other trademarks are the property of their respective owners.

## About Allegion

Allegion (NYSE: ALLE) creates peace of mind by pioneering safety and security. As a \$2 billion provider of security solutions for homes and businesses, Allegion employs more than 7,800 people and sells products in more than 120 countries across the world. Allegion comprises more than 25 global brands, including strategic brands CISA®, Interflex®, LCN®, Schlage® and Von Duprin®. For more, visit [www.allegion.com](http://www.allegion.com).

aptiQ ■ LCN ■  ■ STEELCRAFT ■ VON DUPRIN



© 2014 Allegion  
010523, Rev. 10/14  
[www.allegion.com/us](http://www.allegion.com/us)