Motorization Overview

parasol° cellular shades

Hardwired Systems

Somfy Sonesse® 30 RTS

- Available with standard rectangular window application (operate from bottom up)
- Headrail is 2.5" high and 2.5" deep. Headrail color: White
- Includes a 24V DC Transformer with a 15 ft cord
- Motor can be located left or right side of shade
- Motor will include 7 1/2" wire
- Size Standards:
 - Minimum width 22",
 - if two motors are used, minimum is 44".
 - Maximum width 120".
 - Maximum height: 120".
 - Minimum height: 20".
- Additional Options:
 - Sonesse 30 DCT
 - Sonesse 30 RS485
 - Power: 24V DC Power and Distributuion Panel (Large Applications)
- Controls: Single and multi-channel Remotes; Wall Switches; Sun Sensor: Home Automation, MyLink app
- Exclusions:
 - Top-Down/Bottom-Up
 - Top-Down
 - Duo-Lucent

Battery Operated Systems

Auto-Tilt

- Available with standard Bottom-Up, Top-Down, Top-Down/Bottom-Up, 2-On-1 Headrail and Duo-Lucent™ rectangular window shade applications.
- Motor can be left or right side
- Size Standards:
- Refer to the Parasol Cellular Shades Retail Sales Guide.
- Additional Options:
 - Power
 - Battery (High mount or Low mount) DC Transformer
 - Satellite Battery Wand
- Controls
- Hand-Held remote
- Wireless Wall Switch
- Exclusions:
 - 2-On-1 Headrail as end mount (EB).
 - 2-On-1 Headrail w/ hold-down brackets.
 - 2-On-1 Headrail w/ Top-Down/Bottom-Up or Duo-Lucent

For further motorization information contact the Lafayette Customer Service Motorization Department.



