



Innovative Tile and Stone  
Installation Systems

# Product Selection Catalog

## North America



Underlayments

Crack Suppression

Shower Pans • Seats • Niches

**interior**

Shower Drains

**exterior**

Waterproofing

**commercial**

Sound Control

**residential**

Floor Warming

**industrial**

Adhesives

Mortars

Grouts

Caulk




Snap for more  
information.



Glass Mosaic Chandelier, Georgia Health Sciences University's College of Dental Medicine, Augusta, GA



Cahn Pool, Beverly Hills, CA



The W Hotel Boston and Residences, Boston, MA

LATICRETE International, Inc. is a worldwide manufacturer of tile and stone installation systems. The company was founded in 1956 by Dr. Henry M. Rothberg and Lillian R. Rothberg. With a tile setting background and a chemical engineering degree, Dr. Rothberg was determined to bring improvements to centuries old portland cement based tile and stone installation products. Dr. Rothberg's work in this area is the basis for all modern tile and stone adhesives.

Throughout its existence, LATICRETE has enjoyed the freedom of action and dedication to purpose brought by being a privately owned enterprise. Being able to ignore the short term, often unrealistic, demands of the stock markets or equity speculators, allows us to provide industry leading levels of product innovation, customer satisfaction and corporate citizenship. By

heavily reinvesting our earnings into superior research, customer support, and manufacturing capabilities, we continue to build long term value despite fluctuations in construction activity and evolving market needs. The commitment of our owners to provide robust client service is unwavering and reflected throughout our organization, in addition to developing products which support GREEN efforts. LATICRETE offers a wide array of certified low VOC (volatile organic compounds) installation materials, independently tested and certified by the GREENGUARD Environmental Institute, contributing to LEED certification.

With approximately 650 associates worldwide, LATICRETE operates 7 plants in the United States, as well as facilities in UAE, China, India, Singapore, Australia, Norway, Italy, and Costa Rica to name a few.

	PAGE
Installation Systems.....	4
Warranties.....	5
Technical Training and Seminars.....	7
Marketing Tools, Certifications and Memberships.....	8
<b>Vapor Reduction</b>	
LATAPOXY® 312 Vapor Reduction Membrane.....	9
<b>Plaza &amp; Deck System</b>	
LATICRETE® Tile and Drain Mat.....	9
<b>Underlayments</b>	
LATICRETE 86 LatiLevel™.....	10
LATICRETE 84 LatiLevel.....	10
LATICRETE Admix & Primer.....	11
LATICRETE 816 LatiPatch™.....	11
<b>Preformed Shower System/Shower Drains</b>	
<b>NEW!</b> LATICRETE Hydro Ban® Pre-Sloped Shower Pan.....	12
<b>NEW!</b> LATICRETE Hydro Ban Preformed Seats.....	13
<b>NEW!</b> LATICRETE Hydro Ban Preformed Niche.....	13
<b>NEW!</b> LATICRETE Hydro Ban Linear Drain.....	14
<b>NEW!</b> LATICRETE Hydro Ban Bonding Flange Drain.....	15
<b>Waterproofing</b>	
LATICRETE Hydro Ban.....	16
LATICRETE 9235 Waterproofing Membrane.....	17
LATICRETE Hydro Barrier™.....	17
LATAPOXY Waterproof Flashing Mortar.....	18
<b>Sound Control/Anti-Fracture</b>	
LATICRETE 170 Sound & Crack Isolation Mat.....	18
LATICRETE Blue 92 Anti-Fracture Membrane.....	18
LATICRETE Crack Suppression Kit.....	18
LATICRETE 125 Sound & Crack Adhesive^.....	19
<b>Floor Warming</b>	
LATICRETE Floor HEAT Mat and Accessories.....	20 – 21
<b>Epoxy Adhesives</b>	
LATAPOXY 310 Stone Adhesive.....	22
LATAPOXY 310 Cordless Mixer.....	22
LATAPOXY 300 Adhesive.....	23
LATAPOXY 210 Adhesive.....	23
<b>Polymer Fortified Thin-Set Mortars</b>	
LATICRETE 254 Platinum.....	24
LATICRETE 254R Platinum Rapid.....	24
LATICRETE Sure Set™.....	25
LATICRETE Glass Tile Adhesive Mortar.....	25
LATICRETE 253 Gold.....	26
LATICRETE 253R Gold Rapid.....	26
LATICRETE 252 Silver.....	27

	PAGE
<b>Non-Modified Thin-Set Mortars</b>	
LATICRETE 272 Mortar.....	27
LATICRETE 317.....	28
LATICRETE 8500 Glass Block Mortar.....	28
<b>Latex Fortified Thin-Set Mortars and Latex Thin-Set Additives</b>	
LATICRETE 4237 Latex Additive.....	29
LATICRETE 211 Powder.....	29
LATICRETE 333 Super Flexible Additive.....	29
LATICRETE 101 Rapid Latex Admix.....	29
<b>Mastic</b>	
LATICRETE 15 Premium Mastic.....	30
<b>Medium Bed Mortars</b>	
LATICRETE 4-XLT.....	30
<b>NEW!</b> LATICRETE 4-XLT Rapid.....	31
<b>NEW &amp; IMPROVED!</b> LATICRETE 255 MultiMax™.....	31
LATICRETE 220 Marble & Granite Mortar.....	32
<b>Premium Latex Mortar Beds</b>	
LATICRETE 3701 Fortified Mortar Bed.....	32
LATICRETE 3701 Mortar Admix.....	33
LATICRETE 226 Thick Bed Mortar.....	33
LATICRETE 209 Floor Mud.....	33
<b>Cementitious Grouts</b>	
LATICRETE PermaColor™ Grout^.....	34
LATICRETE 1500 Sanded Grout.....	34
LATICRETE 1600 Unsanded Grout.....	35
<b>Grout Additive</b>	
LATICRETE 1776 Grout Enhancer.....	35
<b>Epoxy Grouts</b>	
LATICRETE SpectraLOCK PRO Premium Grout†.....	36
LATICRETE SpectraLOCK Grout Dazzle Part D Component.....	36
LATICRETE SpectraLOCK PRO Grout Part AB Liquids.....	37
LATICRETE SpectraLOCK Grout Part C Powders.....	37
LATICRETE SpectraLOCK 2000 IG.....	38
<b>Caulk</b>	
LATICRETE Premium Acrylic Caulk.....	39
LATICRETE Latasil™.....	39
LATICRETE Latasil 9118 Primer.....	39
Grout and sealant color chart.....	40
Grout coverage charts.....	41
Product selection guide and substrate guide.....	42 – 43

Consult our website at [www.laticrete.com](http://www.laticrete.com) for the most current versions of product data sheets, warranties and MSDS sheets.

Content of this brochure is for informational purposes only. Refer to individual product data sheets and warranties for complete information.

^United States Patent No.: 6,784,229 B2 (and other Patents).


†United States Patent No.: 6,881,768 (and other Patents).

# LATICRETE Offers a COMPLETE SYSTEM SOLUTION for Virtually EVERY Application

LATICRETE has successfully provided the technology for innovative, permanent installations of tile and stone finishes. Architecturally specified and preferred by professional installers, LATICRETE provides solutions for virtually every application.


- LATICRETE® products are industry accepted, code approved and backed by 100% labor and materials system warranties, thereby assuring a successful installation each and every time
- LATICRETE membranes, adhesives, grouts, and sealants are weather resistant and freeze/thaw stable

## SOUND CONTROL AND ANTI-FRACTURE




LATICRETE SpectraLOCK® PRO Premium Grout\* or LATICRETE PermaColor™ Grout\*

## COMMERCIAL AND INDUSTRIAL FLOORS




LATICRETE SpectraLOCK 2000 IG | LATICRETE Lotasil™

## PREFORMED SHOWER




LATICRETE Hydro Ban Curb | LATICRETE Hydro Ban Bonding Drain Grate | LATICRETE Hydro Ban Pre-Sloped Shower Pan

## WET AREAS AND CONTINUOUS UNDERWATER SUBMERSION




LATICRETE 254 Platinum | LATICRETE Lotasil™

## WALLS AND FACADES



Properly prepared concrete, backer board or masonry substrates (if substrate requires leveling, use LATICRETE 3701 Mortar Admix with LATICRETE 226 Thick Bed Mortar)

## PLAZA & DECK



LATICRETE 9235 Waterproofing Membrane or LATICRETE Hydro Ban for secondary waterproofing and crack suppression | LATICRETE PermaColor Grout | LATICRETE 254 Platinum | LATICRETE Tile Drain Mat | LATICRETE 3701 Mortar Admix and LATICRETE 226 Thick Bed Mortar, or LATICRETE 3701 Fortified Mortar Bed with wire-reinforcing | Structural concrete deck, properly pitches

For over half a century Architects, Engineers and Developers have trusted LATICRETE with their tile and stone installation needs. Let our experience, product quality and technical support assist you on your next project – no matter what the application is.

# LATICRETE offers the best warranties IN THE INDUSTRY



With a LATICRETE® System Warranty\* you can enjoy peace of mind with high-quality, world renowned LATICRETE products.

When selecting the installation system for your project, consider the value and peace of mind that a LATICRETE warranty can bring.

LATICRETE provides comprehensive warranties covering commercial, residential, and industrial projects around the world. However, our best guarantee is over 56 years of experience with industrial, commercial and residential installations in every imaginable climate around the world.

All LATICRETE materials are covered by a limited one-year warranty when properly installed according to our written instructions (see Data Sheet 230.13). By using the combinations of products shown to form a complete single source system, both the term and the scope of the warranty\* are dramatically increased.

LATICRETE 5 Year System Warranty See Data Sheet 230.05APD for complete warranty information.	
APPLICATION	PRODUCTS
<b>Underlayment</b>	LATICRETE® 84 Latilevel™ LATICRETE Admix & Primer
<b>Vapor Reduction</b>	LATAPOXY® 312 Vapor Reduction Membrane
<b>Waterproofing</b>	LATICRETE Hydro Ban® LATICRETE Hydro Barrier™ LATICRETE 9235 Waterproofing Membrane LATAPOXY Waterproof Flashing Mortar * LATICRETE 302 Waterproofing * LATICRETE 9237 Waterproofing Membrane
<b>Sound Control</b>	LATICRETE 170 Sound & Crack Isolation Mat
<b>Anti-Fracture</b>	LATICRETE Blue 92 Anti-Fracture Membrane
<b>Thick Bed Method</b>	LATICRETE 3701 Mortar Admix mixed with LATICRETE 226 Thick Bed Mortar LATICRETE 3701 Fortified Mortar Bed * LATICRETE 3642 Latex mixed with LATICRETE 226 Thick Bed Mortar
<b>Slurry Bond Coat</b>	LATICRETE 254 Platinum * LATICRETE 73 Crete Admix mixed with LATICRETE 211 Powder * LATICRETE 335 Super Flex
<b>Thin Bed Method</b>	LATICRETE 253 Gold (regular or rapid version) LATICRETE Sure Set™ LATICRETE 333 Super Flexible Additive mixed with LATICRETE 317 (exterior use limited to residential/light commercial applications; do not use in areas subject to water immersion) * LATICRETE 335 Super Flex * LATICRETE 73 Crete Admix mixed with either of the following ■ LATICRETE 211 Powder; or ■ LATICRETE 317; or ■ LATICRETE 290
<b>Grouting</b>	LATICRETE 1776 Grout Enhancer mixed with either of the following ■ LATICRETE 1500 Sanded Grout; or ■ LATICRETE 1600 Unsanded Grout; or ■ * LATICRETE 500 Sanded Grout; or ■ * LATICRETE 600 Unsanded Grout
<b>Sealant†</b>	LATICRETE Latasil™ LATICRETE Latasil 9118 Primer

▲ See Data Sheets 230.05APD, 025.OAPD and 230.99 for complete warranty information.  
 \* Available in markets outside of the United States of America and Canada.  
 † Use of suitable flexible sealant is required per Tile Council of America Detail EJ171 for use in expansion joints, coves, corners, changes in plane and other joints wherever tile or stone abuts dissimilar materials or restraining surfaces.  
 ^ LATICRETE® Floor Warming Thermostat sold by LATICRETE International, Inc., warrants parts and materials for one (1) year from the date of purchase. The sole remedy for the LATICRETE Floor Warming Thermostats is product replacement (see DS 230.13 for full details on the LATICRETE Product Warranty).

LATICRETE 25 Year System Warranty See Data Sheet 025.OAPD for complete warranty information.	
APPLICATION	PRODUCTS
<b>Underlayment</b>	LATICRETE 86 Latilevel LATICRETE Admix & Primer
<b>Floor Warming</b>	LATICRETE Floor HEAT Mat (only)
<b>Waterproofing/Anti-Fracture</b>	LATICRETE 9235 Waterproofing Membrane LATICRETE Hydro Ban LATAPOXY Waterproof Flashing Mortar LATICRETE Hydro Ban Pre-Sloped Shower Pan (and applicable accessories) LATICRETE Hydro Ban Linear Drain LATICRETE Hydro Ban Bonding Flange Drain
<b>Sound Control/Anti-Fracture</b>	LATICRETE 125 Sound & Crack Adhesive United States Invention Patent No.: 6,784,229 B2 (and other Patents) LATICRETE 170 Sound & Crack Isolation Mat * LATICRETE QT Sound Control Underlayment Patent No.: 6,920,723
<b>Plaza &amp; Deck</b>	LATICRETE Plaza and Deck System
<b>Thick Bed Method</b>	LATICRETE 3701 Fortified Mortar Bed LATICRETE 3701 Mortar Admix mixed with LATICRETE 226 Thick Bed Mortar
<b>Slurry Bond Coat</b>	LATICRETE 254 Platinum * LATICRETE 4237 Latex Additive mixed with either of the following ■ LATICRETE 211 Powder; or ■ LATICRETE 317; or ■ LATICRETE 272 Mortar
<b>Thin Bed Method</b>	LATICRETE 254 Platinum (regular or rapid version) LATICRETE 255 MultiMax™ United States Invention Patent No.: 6,784,229 B2 (and other Patents) LATAPOXY 300 Adhesive LATICRETE Sure Set™ LATICRETE Glass Tile Adhesive Mortar LATICRETE 4-XLT (regular or rapid version) * LATICRETE 4237 Latex Additive mixed with any of the following ■ LATICRETE 211 Powder; or ■ LATICRETE 317; or ■ LATICRETE 272 Mortar; or ■ LATICRETE PermaColor™ Grout United States Invention Patent No.: 6,784,229 B2 (and other Patents) (for installation of paper face mounted glass mosaics only) LATICRETE 3701 Mortar Admix mixed with any of the following ■ LATICRETE 272 Mortar; or ■ LATICRETE 317; or ■ LATICRETE 220 Marble & Granite Mortar * LATICRETE 325 Premium Tile Adhesive mixed with LATICRETE 333 Super Flexible Additive
<b>Spot Bonding</b>	LATAPOXY 310 Stone Adhesive — Standard and Rapid Grade
<b>Masonry Veneer Installation System</b>	LATICRETE 3701 Fortified Mortar Bed LATICRETE Hydro Ban LATICRETE Masonry Veneer Mortar LATICRETE Masonry Pointing Mortar
<b>Grouting</b>	LATICRETE SpectraLOCK PRO® Premium Grout (non-industrial applications) United States Invention Patent No.: 6881768 (and other Patents) LATICRETE SpectraLOCK PRO Grout (non-industrial applications) LATAPOXY 2000 Industrial Grout LATICRETE SpectraLOCK 2000 IG LATICRETE PermaColor Grout * LATAPOXY SP-100
<b>Sealant†</b>	LATICRETE Latasil™ LATICRETE Latasil 9118 Primer

LATICRETE Lifetime System Warranty See Data Sheet 230.99 for complete warranty information.	
APPLICATION	PRODUCTS
<b>Underlayment</b>	LATICRETE 86 Latilevel LATICRETE Admix & Primer
<b>Floor Warming^</b>	LATICRETE Floor HEAT Mat
<b>Waterproofing/Anti-Fracture</b>	LATICRETE Hydro Ban LATICRETE 9235 Waterproofing Membrane LATICRETE Hydro Ban Pre-Sloped Shower Pan (and applicable accessories) LATICRETE Hydro Ban Linear Drain LATICRETE Hydro Ban Bonding Flange Drain
<b>Thick Bed Mortar</b>	LATICRETE 3701 Fortified Mortar Bed
<b>Slurry Bond Coat</b>	LATICRETE 254 Platinum LATICRETE 4237 Latex Additive mixed with LATICRETE 211 Powder
<b>Thin Bed Method</b>	LATICRETE 254 Platinum (regular or rapid version) LATICRETE 255 MultiMax LATICRETE 4237 Latex Additive mixed with either of the following: ■ LATICRETE 211 Powder; or ■ LATICRETE 317; or ■ LATICRETE 272 Mortar LATICRETE 3701 Mortar Admix mixed with any of the following: ■ LATICRETE 272 Mortar; or ■ LATICRETE 317; or ■ LATICRETE 220 Marble & Granite Mortar
<b>Grout</b>	LATICRETE SpectraLOCK PRO Premium Grout LATICRETE SpectraLOCK PRO Grout LATICRETE PermaColor Grout
<b>Sealant†</b>	LATICRETE Latasil LATICRETE Latasil 9118 Primer

# The LEED-ER IN GREEN



LATICRETE offers resource tools to help design and specification professionals save time when specifying tile and stone installation systems.

First, the web-based LATICRETE® Architectural Guidebook empowers design and specification professionals to create custom specifications based on industry standards for over 100 types of installations with just a few clicks of a mouse.

Second, LATICRETE offers BIM-Compliant, Revit format details and objects which provide visual, specification and material references for design and construction teams. You can now generate specifications even faster, and with greater clarity and ease. Our integrated 2D and 3D model-based details allow you to quickly and easily reference, manipulate, and visualize detail components electronically, and in an automated format.

## CERTIFIED PRODUCTS, CONTRIBUTING TO LEED PROJECTS

LATICRETE provides tile and stone installation materials certified by the GREENGUARD Environmental Institute (GEI). Based on criteria used by the U.S. Green Building Council's LEED-CI program, the GREENGUARD certification provides you the proof and assurance that the specified LATICRETE Systems meet appropriate indoor air quality standards for volatile organic compounds (VOCs), including formaldehyde.

## ONLINE LEED PROJECT CERTIFICATION ASSISTANT

Specifying tile and stone installation materials for projects seeking LEED certification is now faster and easier than ever before. The web-based LATICRETE LEED Project Certification Assistant automatically generates all of the information required for LATICRETE products on a specific LEED project, eliminating manual collection of data.

- Quickly produces an Adobe Acrobat file for each LATICRETE product selected stating its VOC content, recycled content, manufacturing location, raw material sources, GREENGUARD for Children & Schools certification (if available), supporting technical information, and a map showing the location of your project with a 500-mile radius circle depicting its relation to LATICRETE manufacturing facilities.
- Eliminates the time consuming challenge of obtaining and quantifying the necessary data for LEED-compliant installation materials; Detailed, accurate information in just a few moments

Visit [www.laticrete.com](http://www.laticrete.com) today.



## CERTIFICATION IN PROCESS

LATICRETE offers intensive training programs which were specifically developed for tile and stone industry distributors, dealers and other industry professionals.

## BENEFITS

- Increase understanding of the tile and stone installation industry
- Expand knowledge of how to select and recommend the most suitable installation materials
- Increase knowledge of LATICRETE® products
- Learn trade definitions, performance requirements and industry standards
- Learn how to solve and avoid job problems
- Participate in hands-on product demonstrations

## SEMINAR LOCATION

The LATICRETE Technical Training Center is located on our 44-acre Corporate Headquarters campus in rural Bethany, Connecticut.

While attending the LATICRETE seminar you will be our guest at the LATICRETE Visitor Center. Arrival and check-in is Wednesday after 7:00 p.m., check-out and departure is Friday after 7:00 p.m. or Saturday before 3:00 p.m.

## DAILY SCHEDULE

The LATICRETE seminars run Thursdays and Fridays from 9:00 a.m. – 5:00 p.m. Experienced instructors utilize both classroom instruction and hands-on product demonstrations. You will also be able to meet with key LATICRETE personnel. Time is allocated for questions and discussion at the end of each day's presentation. Optional social activities and sightseeing excursions are also planned.

## Program Includes

- All transportation between the airport and the LATICRETE Visitor Center
- Lodging at the LATICRETE Visitor Center
- All meals
- All books, technical binders and product catalogs
- Daily transportation to and from the visitor center to the LATICRETE Technical Training Center and return
- Graduation diploma and unique promotional items



## LATICRETE “PROFIT THROUGH KNOWLEDGE” TECHNICAL SEMINARS

### Seminar Content

- Selecting the proper installation systems
- Industry standards
- Substrates (preparation/requirements)
- Types of tile and stone
- Waterproofing membranes
- Latex portland cement mortars
- Epoxy and cement grouts
- Epoxy adhesives
- Sales and marketing techniques
- Hands-on product demonstrations

## SEGMENTED “PROFIT THROUGH KNOWLEDGE” DISTRIBUTOR TRAINING PROGRAMS

### Seminar Content

- New construction methods
- Concrete construction
- Plaza and deck installation
- Forensic examination
- Surface preparation
- Facades
- Hands-on product demonstrations
- Moisture in concrete
- Swimming pool installations

## NORTH AMERICA “ON THE ROAD” SEMINARS

These sessions run for two days at LATICRETE manufacturing plants around the country. Seminars begin at 8:00 a.m. and go to 5:00 p.m. A question and discussion period is held at the end of the day's presentation.

### Seminar Content

- Selecting the proper installation systems
- Industry standards
- Substrates (preparation/requirements)
- Types of tile and stone
- Waterproofing membranes
- Latex portland cement mortars
- Epoxy and cement grouts
- Epoxy adhesives
- Sales and marketing techniques
- Hands-on product demonstrations

### Program Includes

- Presentations by various LATICRETE corporate staff and field technical representatives
- Continental breakfast, lunch, refreshment breaks
- Technical binders, product catalogs, handouts
- Graduation diploma and unique promotional items

For further information, log onto [www.laticrete.com/seminars](http://www.laticrete.com/seminars), or contact LATICRETE at +1.203.393.0010, ext. 235; Fax: +1.203.393.1948; or [seminars@laticrete.com](mailto:seminars@laticrete.com)

# Marketing Tools, Certifications and Memberships



LATICRETE provides you with online access to the latest in sales and marketing tools.

SIMPLY VISIT  
**www.laticrete.com**

to download the latest  
LATICRETE marketing support tools or  
request a hard copy  
at [www.laticrete.com/tools](http://www.laticrete.com/tools)




Log onto **www.laticrete.com**  
today to download our latest  
LATICRETE® Technical Design Manuals.

## PRODUCT AND PROCESS



## CONTRACTORS



## DISTRIBUTORS



## INDUSTRY



## DESIGNERS



## CHARITABLE



## GREEN





## LATAPOXY® 312 Vapor Reduction Membrane

LATAPOXY® 312 Vapor Reduction Membrane is a three component system made of special epoxies and fillers to ensure adhesion and strength. It reduces the moisture vapor emission rate (MVER) from concrete to protect your floor installation:

- Ideal for slab on grade construction
- Allows the installation of vinyl, wood, epoxy, tile, stone and other floor coverings
- Reduces moisture vapor emission rate from 12 lbs/1000 ft<sup>2</sup> in 24 hours (678 µg/s•m<sup>2</sup>) to below 3 lbs/1000 ft<sup>2</sup> in 24 hours (170 µg/s•m<sup>2</sup>)

### PACKAGING

3.5 gallon (13.2 l) bucket (used for mixing).

2 LATAPOXY 312 Vapor Reduction Membrane Part A at 2.0 lb (0.9 kg).

1 LATAPOXY 312 Vapor Reduction Membrane Part B at 2.6 lb (1.2 kg).

7 lb (3.2 kg) LATAPOXY 312 Vapor Reduction Membrane Part C powder.

13.6 lb (6.2 kg) per unit; 48 units per pallet.

### Approximate Coverage

180 – 220 ft<sup>2</sup> (16.7 – 20.4 m<sup>2</sup>) per unit




**Warranty: 5 Year**  
Refer to Data Sheet 312.0




## LATICRETE® Tile Drain Mat

As a component of the LATICRETE® Plaza & Deck System, the patented and lightweight LATICRETE Tile Drain Mat provides three times the drainage rate of a conventional 2" (50 mm) crushed gravel bed. The LATICRETE Drain Mat provides integral subsurface drainage for infiltrated water, and reduces the potential for efflorescence.

- Part of the LATICRETE Plaza & Deck System
- "Extra Heavy" service rating per ASTM C627 (TCNA)



**Warranty: 25 Year**  
Refer to Data Sheet 290.0





**Performance Level: BEST**  
**Warranty: Lifetime**  
 Refer to Data Sheet 238.9



## LATICRETE® 86 LatilLevel™

Free-flowing, pumpable cementitious mortar for rapid leveling of interior subfloors. Can be poured from feather edge to 1-1/2" (38 mm) thickness in one pour. LATICRETE® 86 LatilLevel™ will produce a smooth and flat surface with excellent durability, which is ready for tile in less than 4 hours.

### PACKAGING

55 lb (25 kg) bag; 54 bags per pallet.

**REQUIRED** LATICRETE Admix & Primer

Approximate Coverage Per 55 lb (25 kg) bag	
Thickness	Coverage
1/8" (3 mm)	52 ft <sup>2</sup> (4.8 m <sup>2</sup> )
1/4" (6 mm)	26 ft <sup>2</sup> (2.4 m <sup>2</sup> )
1/2" (12 mm)	13 ft <sup>2</sup> (1.2 m <sup>2</sup> )
3/4" (18 mm)	8.6 ft <sup>2</sup> (0.8 m <sup>2</sup> )
1" (25 mm)	6.7 ft <sup>2</sup> (0.6 m <sup>2</sup> )
1-1/2" (38 mm)	5 ft <sup>2</sup> (0.45 m <sup>2</sup> )



**Performance Level: BETTER**  
**Warranty: 5 Year**  
 Refer to Data Sheet 084.0



## LATICRETE 84 LatilLevel

A cementitious powder that is mixed with water to produce a free flowing, self leveling underlayment mortar for interior sub floors. LATICRETE 84 LatilLevel can be poured from feather-edge to 1" (25 mm) in one pour producing a smooth and flat surface with excellent durability.

### PACKAGING

50 lb (22.7 kg) bag; 56 bags per pallet.

**REQUIRED** LATICRETE Admix & Primer

Approximate Coverage Per 50 lb (25 kg) bag	
Thickness	Coverage
1/8" (3 mm)	45 ft <sup>2</sup> (4.2 m <sup>2</sup> )
1/4" (6 mm)	22.5 ft <sup>2</sup> (2.1 m <sup>2</sup> )
1/2" (12 mm)	11.3 ft <sup>2</sup> (1.1 m <sup>2</sup> )
3/4" (18 mm)	7.5 ft <sup>2</sup> (0.7 m <sup>2</sup> )
1" (25 mm)	5.6 ft <sup>2</sup> (0.5 m <sup>2</sup> )

## LATICRETE Admix & Primer

A latex primer that increases bond strength to substrates and is required when using LATICRETE 86 LatiLevel and LATICRETE 84 LatiLevel self leveling underlayments. Use as an admix with LATICRETE 816 LatiPatch™ to increase strength of adhesion over difficult to bond to substrates such as cutback adhesive and vinyl tile.

### PACKAGING

5 quart (4.8 ℓ) jug; 4 jugs per carton; 28 cartons per pallet.

#### Approximate Coverage

Dilute 1:1 by volume with clean potable water to yield approximately 500 ft<sup>2</sup> (46.3 m<sup>2</sup>) per jug, or, for extremely dry, porous substrates, may be applied full strength yielding 250 ft<sup>2</sup> (23.2 m<sup>2</sup>) per jug.

When used as an admix with LATICRETE 816 LatiPatch, coverage will depend upon the thickness desired. See Data Sheet 662.0 or information below for LATICRETE 816 LatiPatch for further details on approximate coverage.



**Warranty: Lifetime**  
Refer to Data Sheet 662.0

## LATICRETE 816 LatiPatch™

Rapid cementitious patching compound that can be applied over concrete and exterior glue plywood. LATICRETE 816 LatiPatch is ideal for use over difficult substrates such as non water soluble cutback adhesive, vinyl tile, dry porous concrete and unglazed ceramic tile and its sand-free formula provides a smooth finish. Easily mixes with water to allow tiling in just 1 – 2 hours.

### PACKAGING

25 lb (11.3 kg) bag; 100 bags per pallet.

8 lb (3.6 kg) carton; 4 per carton; 44 cartons per pallet.

**REQUIRED** LATICRETE Admix & Primer (see above)

### MIXING

As an admix; approximately 5 quarts (4.7 ℓ) per 25 lb (11.3 kg) bag of LATICRETE 816 LatiPatch.

#### Approximate Coverage Per 25 lb (11.3 kg) bag

Thickness	Coverage
1/8" (3 mm)	29.2 ft <sup>2</sup> (2.7 m <sup>2</sup> )
1/4" (6 mm)	14.6 ft <sup>2</sup> (1.4 m <sup>2</sup> )
1/2" (12 mm)	7.3 ft <sup>2</sup> (0.7 m <sup>2</sup> )



Refer to Data Sheet 674.0

## A COMPLETE Shower Installation System from the SUBSTRATE UP!



LATICRETE Hydro Ban Pre-Sloped Pans, Preformed Seats and Preformed Niches are designed for use with LATICRETE installation materials.

- Compatible with LATICRETE Hydro Ban® waterproof membrane – allows for fast and simple waterproofing of walls and accessories.
- Single source supply – allows for convenient ordering and shipping



**Warranty: 25 Year, Lifetime**  
Referring to Data Sheet 031.0

### LATICRETE® Hydro Ban Pre-Sloped Shower Pan

LATICRETE® Hydro Ban Pre-Sloped Shower Pan is a lightweight high-density polystyrene base pan with a code approved reinforced waterproof coating that is ready-to-tile. Equipped with a factory installed drain assembly the base pan can easily be modified on site to adjust for any measurement variations. Lightweight, durable and plumbing code approved, the LATICRETE Hydro Ban Pre-Sloped Shower Pan also offers an exclusive comprehensive system warranty – providing your peace of mind and insurance on your installation.

- Lightweight high-density expanded polystyrene
- Installs easily in minutes
- One piece, pre-sloped to drain – eliminates need for a mud bed or pan liner
- Site sizeable – dimensions can easily be adjusted on site
- Ready-to-tile waterproof surface, waterproofing meets ANSI A118.10
- Factory installed drain body – no assembly needed
- Code approved per ASME A112.18-2/CSA B125.2.05 (US and CN)
- Equipped with a heavy gauge stainless steel drain, curb and sealant

#### AVAILABLE SIZES

- 36" x 60" (91 cm x 152 cm) PVC or ABS center drain
- 36" x 48" (91 cm x 122 cm) PVC or ABS center drain
- 48" x 60" (122 cm x 152 cm) PVC or ABS center drain
- 48" x 48" (122 cm x 122 cm) PVC or ABS center drain
- 38" x 66" (96 cm x 168 cm) PVC or ABS off center drain
- Custom sizes available

# Preformed Shower System/Shower Drains

## LATICRETE Hydro Ban Preformed Seats

LATICRETE Preformed Seats compliment the shower installation allowing for fast and easy installations — saving you time and money. LATICRETE Hydro Ban Preformed Seats can be installed directly over the LATICRETE Hydro Ban Pre-Sloped Shower Pan, providing added beauty and functionality.

- Lightweight, high strength expanded polystyrene
- Simple and easy to install
- Ready-to-tile, waterproof surface

### AVAILABLE SIZES

- 16" x 16" (41 cm x 41 cm) triangle
- 23" x 23" (58 cm x 58 cm) triangle
- 16" x 16" (41 cm x 41 cm) convex



**Warranty: 25 Year, Lifetime**  
Referring to Data Sheet 032.0



## LATICRETE Hydro Ban Preformed Niches

LATICRETE Preformed Niches provide an easy and decorative option for shower or kitchen tile wall inserts — allowing for fast and easy installations as they are preformed and ready for tile installation.

- Lightweight, high strength expanded polystyrene
- Simple and easy to install
- Ready-to-tile, waterproof surface
- Ideal for bathrooms, kitchens

### AVAILABLE SIZES


- 12" x 12" (30 cm x 30 cm) square
- 12" x 12" (30 cm x 30 cm) and 12" x 6" (30 cm x 15 cm) wide combo
- 8" x 12" (20 cm x 30 cm) and 8" x 6" (20 cm x 15 cm) narrow combo
- 12" x 20" (15 cm x 51 cm) mega
- 8" x 8" (20 cm x 20 cm) soap niche



**Warranty: 25 Year, Lifetime**  
Referring to Data Sheet 033.0

# Preformed Shower System/Shower Drains

**NEW!**



**Warranty: 25 Year, Lifetime**  
Referring to Data Sheet 034.0

## LATICRETE® Hydro Ban Linear Drain

LATICRETE® Hydro Ban Linear Drains are constructed of 16 gauge 304 Stainless Steel and Made in the USA. Available in both a tile-in version providing a seamless continuous tiled floor appearance — virtually making the drain disappear and an attractive brushed finish offset oval design. Ideal for large format tile or stone installations for shower floors installed along the wall or at medial locations.

- Low profile design is ideal for large format tile and stone
- Allows for placement along walls or intermediate locations
- Adjustable grate height allows for range of tile or stone thicknesses
- Made in the USA
- Code approved per ASME A112.18-2:2005/CSA B125.2.05 (US and CN)
- Easy to install, only two components
- Compatible with LATICRETE installation materials for a complete waterproof assembly






## LATICRETE Hydro Ban Bonding Flange Drain

LATICRETE Hydro Ban Bonding Flange Drain consists of a PVC or ABS Flange body, adjusting ring and a stainless steel drain assembly. Offered in a traditional squared center drain placement in either an exclusive tile-in version to provide enhanced design options or in a polished or brushed finish grate design. Each 5" x 5" (127 mm x 127 mm) square drain integrates with the LATICRETE Bonding flange assembly, allowing for easy connection to 2" (48 mm), 3" (72 mm) or 4" (96 mm) outlets with no adaptors needed.



**Warranty: 25 Year, Lifetime**  
Referring to Data Sheet 035.0

- Exclusive tile-in grate option provides for a seamless appearance, making the drain seem to disappear!
- Polished and brushed drain grates constructed of heavy duty 304 stainless steel to resist wear and scratching
- Bonding flange body available in PVC or ABS
- Adjusts both vertically and laterally for easy installation
- Suitable for tile thicknesses of 1/4" up to 1-1/2" (6 mm – 38 mm)
- Code approved per ASME A112.18-2-2005/CSA B125.2.05 (US and CN)
- Compatible with LATICRETE Mortar Bed and LATICRETE Hydro Ban waterproofing membrane providing a complete waterproof assembly and easy installation




Brushed stainless steel grate



Polished stainless steel grate



Tile-in grate





**Performance Level: BEST**

**Warranty: Lifetime**

Refer to Data Sheet 663.0 and 663.5

## LATICRETE® Hydro Ban®

LATICRETE® Hydro Ban® is a thin waterproofing/anti-fracture membrane that combines optimum performance and unmatched productivity. LATICRETE Hydro Ban allows for flood testing in just 2 hours\* after final cure for faster flood testing in cold temperatures and over mortar beds. Backed by a LATICRETE Lifetime System Warranty, LATICRETE Hydro Ban does not require the use of fabric\* in the field, coves or corners and it bonds directly to metal, PVC or ABS plumbing fixtures. Save yourself money, time and complete your installations faster with greater ease.

- Flood test in 2 hours\*
- Improved flood testing over fresh mortar beds and at cooler temperatures
- No fabric required in coves or corners\*
- IAPMO and ICC approved
- Anti-fracture protection up to 1/8" (3 mm)
- Easy to clean with water

### PACKAGING

**Commercial Unit:** 5 gallon (19 l) pail liquid; 36 units per pallet.

**Mini Unit:** 4 x 1 gallon (3.8 l) pails of liquid packed in a carton; 30 cartons per pallet.

#### Approximate Coverage

Per Commercial Unit	250 ft <sup>2</sup> (23.2 m <sup>2</sup> )
Per Mini Unit	50 ft <sup>2</sup> (4.7 m <sup>2</sup> )



In addition to the conventional means of applying LATICRETE Hydro Ban, the airless spraying technique can be used as an alternate means of application. LATICRETE Hydro Ban can be effectively sprayed to increase productivity up to 3x or 4x on large projects. Any airless sprayer can be used which will deliver up to 3300 PSI (22.8 MPa) using a maximum tip size of 0.031" (0.79 mm). See TDS 410 for further information on the application of LATICRETE Hydro Ban with an airless sprayer.

\* See Data Sheet 663.0 for complete product information. LATICRETE® Hydro Ban® can be flood tested in 2 hours when cured at 70°F (21°C) or above 50% R.H. It can be flood tested in 24 hours when cured at 50 – 69°F (10 – 20.6°C) and up to 70% R.H. The time to flood testing starts when the second coat has completely cured from a light sage green to a darker olive green color.



## LATICRETE 9235 Waterproofing Membrane

LATICRETE 9235 Waterproofing Membrane is “The Industry Standard” for wet areas and continuous water submersion applications. Applies with a paint roller or brush, cures in just hours and provides a permanent waterproofing base for tile, glass mosaic and stone in pools, showers and spas. LATICRETE 9235 Waterproofing Membrane is accepted by IAPMO and ICC for shower pans, meets ANSI A118.10 and ANSI A118.12, is non-hazardous and meets all VOC requirements. When anti-fracture treatment is required in wet areas, LATICRETE 9235 Waterproofing Membrane provides the complete package. You only need one product to protect your floor from water damage and substrate cracks. Inhibits the growth of stain-causing mold and mildew in membranes with Microban® antimicrobial product protection. “Extra Heavy” service rating per ASTM C627.

### PACKAGING

**Full Unit:** 6 gallon (23 l) pail of liquid, 1 carton LATICRETE Waterproofing/Anti-Fracture Fabric, packed separately; 36 units per pallet.

**Mini Unit:** 2 gallon (7.6 l) jug of liquid and LATICRETE Waterproofing/Anti-Fracture Fabric, packed together in one pail; 48 pails per pallet.

Approximate Coverage	
Per Full Unit	300 ft <sup>2</sup> (27.8 m <sup>2</sup> )
Per Mini Unit	75 ft <sup>2</sup> (7 m <sup>2</sup> )



**Performance Level: BEST**

**Warranty: Lifetime**

Refer to Data Sheets 236.0 and WPAF.5



## LATICRETE Hydro Barrier™

LATICRETE Hydro Barrier™ is a thin, load bearing, self curing liquid rubber polymer which can be easily applied to form a flexible seamless waterproofing/anti-fracture membrane. LATICRETE Hydro Barrier can be used on interior and exterior, horizontal or vertical surfaces and is approved by IAPMO for use as shower pan liner. LATICRETE Hydro Barrier requires the use of fabric in the coves and corners or change of plane for waterproofing applications only.

- Interior and exterior
- Swimming pools, fountains, water features, shower pans, stalls, and tub surrounds
- Industrial, commercial and residential

### PACKAGING

**Full Unit:** 3.5 gal (13.3 l) pail liquid; 48 full units per pallet.

**Mini Unit:** 4x1 gal (3.8 l) pail liquid; 30 cartons per pallet.

LATICRETE Waterproofing/Anti-Fracture Membrane Fabric sold separately. Item# S-09235-NF-19

Approximate Coverage	
Per Full Unit	175 ft <sup>2</sup> (16.3 m <sup>2</sup> )
Per Mini Unit	50 ft <sup>2</sup> (4.6 m <sup>2</sup> )



**Performance Level: BETTER**

**Warranty: 5 Year**

Refer to Data Sheet 105.0





**Performance Level: BEST**  
**Warranty: 25 Year**  
 Refer to Data Sheet 070.0

## LATAPOXY® Waterproof Flashing Mortar

LATAPOXY® Waterproof Flashing Mortar is an epoxy based 3 component, trowel applied, waterproofing and vapor barrier membrane. It can be used to waterproof seams, gaps or joints between a variety of substrates and metal and PVC pipe penetrations or flashing. It is specifically designed to be used under ceramic tile, stone or brick for rapid installations which require a fast curing waterproof flashing. LATAPOXY Waterproof Flashing Mortar is flexible, easy to apply and will allow for rapid installations.


- Easy to apply using a trowel
- Adheres to metal and PVC pipes, drains and flashing
- Waterproof seam between flashing and façade

### PACKAGING

3.5 gallon pail with 2 LATAPOXY Waterproof Flashing Mortar Part A 1.4 lbs (0.65 kg), 2 LATAPOXY Waterproof Flashing Mortar Part B 1.15 lbs (0.5 kg), and 2 LATAPOXY Waterproof Flashing Mortar Part C 5.5 lbs (2.5 kg); 48 units per pallet.

#### Approximate Coverage

45 ft<sup>2</sup>/unit (4.2 m<sup>2</sup>) at 1/8" (3 mm) thick, depending on application



**Performance Level: BETTER**  
**Warranty: 25 Year**  
 Refer to Data Sheet 170.0

## LATICRETE® 170 Sound & Crack Isolation Mat

LATICRETE® 170 Sound & Crack Isolation Mat is a high performance 1/8" (3 mm) thick underlayment membrane that provides exceptional sound reduction while simultaneously providing anti-fracture protection for tile or stone installations. Ideal for schools, hotel, condominium and other applications requiring sound control, LATICRETE 170 Sound & Crack Isolation Mat is specifically designed to be used in conjunction with LATICRETE installation materials.

- ΔIIC rating — 20 per ASTM E2179
- Isolates cracks up to 1/8" (3 mm)
- "LIGHT RATING" per ASTM C627 (TCNA)
- Contains 89% post consumer recycled content

### PACKAGING

13.9 m<sup>2</sup> roll, 20 rolls per pallet.

#### Approximate Coverage Per roll

150 ft<sup>2</sup> (13.9 m<sup>2</sup>)



**Performance Level: BETTER**  
**Warranty: 5 Year**  
 Refer to Data Sheets 647.0, 648.0 and WPAF.5

## LATICRETE Blue 92 Anti-Fracture Membrane and LATICRETE Crack Suppression Kit

A 2-part system that forms a highly flexible, full coverage membrane that reduces crack transmission from the substrate to floor finishes. Adds no appreciable thickness to floor construction, and is ready to receive floor finish in just a few hours. Easy to install, no odor and cleans up with water. LATICRETE Blue 92 Anti-Fracture Membrane inhibits the growth of stain-causing mold and mildew in substrates with Microban antimicrobial product protection. "Extra Heavy" service rating per ASTM C627 (TCNA). Meets ANSI A118.12.

### PACKAGING

**Kit:** 2 gallon (7.6 l) jug of liquid; 1 each 15" (37.5 cm) wide roll of LATICRETE Waterproofing/Anti-Fracture Fabric packed together in one carton; 36 cartons per pallet.

**Full Unit:** 5 gallon (19 l) pail liquid; 1 carton LATICRETE Waterproofing/Anti-Fracture Fabric, packed separately, 36 units per pallet.

#### Approximate Coverage

75 linear feet (23 m) at 15" (37.5 cm) wide.

300 ft<sup>2</sup> (28 m<sup>2</sup>) per full unit.



## LATICRETE 125 Sound & Crack Adhesive<sup>^</sup>

LATICRETE has proudly led the tile industry for over fifty years with innovative technologies that allow for faster, more economical methods of installing tile or stone. LATICRETE 125 Sound & Crack Adhesive<sup>^</sup> is a single component product to which you just add water. LATICRETE 125 Sound & Crack Adhesive is fortified with special polymers, select rubber fillers and reinforcing fibers for strength. This gives LATICRETE 125 Sound & Crack Adhesive the ability to do what the others can't do — provide tremendous anti-fracture protection and sound deadening performance. There isn't a faster, easier way to get sound and anti-fracture performance and act as a flexible tile or stone adhesive over a variety of substrates. Eliminate the labor cost and time associated with peel and stick mats, rubber sheets or liquid and fabric systems; just mix, spread and begin setting tile. The performance is proven and the product is backed by the LATICRETE 25 Year system warranty. Meets ISO 13007-1 C1ES2 classification.

- Passes ANSI A118.12 anti-fracture performance up to 1/8" (3 mm)
- Incredible sound control ΔIIC of 15 as tested to ASTM E2179
- "EXTRA HEAVY" Floor Rating per ASTM C627 (TCNA)
- 30% post consumer recycled content
- Exceptional ease of use; virtually no drag on the substrate — the smoothest mortar you'll ever use

### PACKAGING

56 bags per pallet.

#### Approximate Coverage

When back buttering tile for sound control applications, there will be a significant decrease in coverage.

80–95 ft<sup>2</sup>/25 lb bag (7.4–8.8 m<sup>2</sup>/11.3 kg bag) with 1/4" x 1/4" (6 mm x 6 mm) notched trowel.

60–70 ft<sup>2</sup>/25 lb bag (5.6–6.5 m<sup>2</sup>/11.3 kg bag) with 1/4" x 3/8" (6 mm x 9 mm) notched trowel.

40–50 ft<sup>2</sup>/25 lb bag (3.7–4.7 m<sup>2</sup>/11.3 kg bag) with 1/2" x 1/2" (12 mm x 12 mm) notched trowel.

For all installations requiring sound protection, use a 1/4" x 3/8" (6 mm x 9 mm) or a 1/2" x 1/2" (12 mm x 12 mm) notched trowel along with back buttering tiles.

For installations only requiring anti-fracture protection, a 1/4" x 1/4" (6 mm x 6 mm) or 1/4" x 3/8" (6 mm x 9 mm) may be used for maximum coverage

<sup>^</sup> United States Patent No.: 6,784,229 B2 (and other Patents).



**Performance Level: BEST**

**Warranty: 25 Year**

Refer to Data Sheet 024.0





**Warranty: Lifetime**  
Refer to Data Sheet 605.0

## LATICRETE® Floor HEAT Mat

A versatile floor warming mat for installation underneath tile and stone. Equipped with self-adhesive backing, LATICRETE® Floor HEAT Mat is simple to install and comes with a low profile wire so it is undetectable beneath tile and stone floors. The LATICRETE Floor HEAT Mat is designed for optimal performance when used in conjunction with LATICRETE 254 Platinum, LATICRETE 86 LatilLevel™ and LATICRETE SpectraLOCK® PRO Premium Grout† or LATICRETE SpectraLOCK PRO Grout .

### PACKAGING

120 VAC Standard Mat Specifications		
Product (W x L)	Sq Ft	Model Number
1' x 10'	10'	0800-1210-2
1' x 12'	12'	0800-1212-2
1' x 15'	15'	0800-1215-2
1' x 20'	20'	0800-1220-2
1' x 23'	23'	0800-1223-2
1' x 25'	25'	0800-1225-2
1' x 30'	30'	0800-1230-2
1' x 35'	35'	0800-1235-2
1' x 40'	40'	0800-1240-2
1' x 45'	45'	0800-1245-2
1' x 50'	50'	0800-1250-2
1.5' x 37'	55.5'	0800-1837-2
1.5' x 40'	60'	0800-1840-2
1.5' x 44'	66'	0800-1844-2
1.5' x 47'	70.5'	0800-1847-2
1.5' x 50'	75'	0800-1850-2
1.5' x 54'	81'	0800-1854-2
3' x 2'	6'	0800-3602-2
3' x 5'	15'	0800-3605-2
3' x 7'	21'	0800-3607-2
3' x 30'	90'	0800-3630-2

240 VAC Standard Mat Specifications		
Product (W x L)	Sq Ft	Model Number
1.5' x 13'	19.5'	0800-1813-4
1.5' x 20'	30'	0800-1820-4
1.5' x 27'	40.5'	0800-1827-4
1.5' x 33'	49.5'	0800-1833-4
1.5' x 40'	60'	0800-1840-4
1.5' x 47'	70.5'	0800-1847-4
1.5' x 53'	79.5'	0800-1853-4
3' x 30'	90'	0800-3630-4
3' x 35'	105'	0800-3635-4
3' x 40'	120'	0800-3640-4
3' x 45'	135'	0800-3645-4
3' x 50'	150'	0800-3650-4



**Warranty: Lifetime**  
Refer to Data Sheet 606.2

## LATICRETE Floor Warming Thermostat

LATICRETE offers a new dual voltage 120V/240V simple to use programmable thermostat designed to be used with LATICRETE Floor HEAT products. Features include a built-in GFCI, a 15' floor warming temperature sensor, and digital programming.

### PACKAGING

LATICRETE® Floor warming Thermostat 10 per box.	
Product	Model Number
120V/240V 5mA GFCI	0800-0003-2

LATICRETE Floor warming Thermostat (Single)	
Product	Model Number
120V/240V 5mA GFCI	0800-0003-2S
Individual FW Therm. Sensor	0800-0001-2



Refer to Data Sheet 604.0

## LATICRETE Wire Eye™

LATICRETE Wire Eye™ is an electric wire fault indicator designed specifically to be used during the installation of LATICRETE Floor HEAT products. LATICRETE Floor HEAT lead wires are attached to LATICRETE Wire Eye allowing for continuity monitoring during the installation process. If continuity is lost, the LATICRETE Wire Eye emits an alarm to alert the installer of a potential problem.

### PACKAGING

LATICRETE Wire Eye™ 20 per box.	
Product	Model Number
	0800-0002-2

LATICRETE Wire Eye (Single)	
Product	Model Number
	0800-0002-2S

\*United States Patent No.: 6,881,768 (and other Patents).

## LATICRETE Floor HEAT Kit

A complete floor warming kit, the contents include a LATICRETE Floor HEAT Mat, LATICRETE Floor Warming Thermostat, and LATICRETE Wire Eye. Kits are available in the (5) most popular mat sizes. Equipped with self-adhesive backing, LATICRETE Floor HEAT is simple to install and comes with a low profile wire so it is virtually undetectable beneath tile and stone floors. The LATICRETE Floor HEAT mat is designed for optimal performance when used in conjunction with LATICRETE 254 Platinum, LATICRETE 86 LatiLevel and LATICRETE SpectraLOCK PRO Grout.

### PACKAGING


#### 120 VAC Standard Mat Specifications

Product (W x L)	Sq Ft	Model Number
1' x 10'	10'	0800-1210-3
1' x 20'	20'	0800-1220-3
1' x 30'	30'	0800-1230-3
3' x 2'	6'	0800-3602-3
3' x 5'	15'	0800-3605-3



**Warranty: Lifetime**

Refer to Data Sheets 604.0, 605.0 and 606.0



## LATICRETE Floor HEAT Merchandiser

A retail and distributor friendly display, LATICRETE Merchandiser requires very little floor space while highlighting all of the LATICRETE Floor HEAT kits. Includes (9) packages offering (5) different mat sizes. Merchandiser ships complete and requires minimal effort to assemble.

### PACKAGING

#### 120 VAC Standard Mat Specifications

Product (W x L)	Sq Ft	Model Number	Qty Per Merchandiser
1' x 10'	10'	0800-1210-3	2
1' x 20'	20'	0800-1220-3	2
1' x 30'	30'	0800-1230-3	1
3' x 2'	6'	0800-3602-3	2
3' x 5'	15'	0800-3605-3	2



## LATAPOXY® 310 Stone Adhesive

A two-component, high strength construction epoxy adhesive for spot bonding large format tile and stone on vertical surfaces, for interior or approved exterior applications. Offers major advantages in terms of speed and productivity over mechanical anchoring, plaster and wire, and the thin-set method of veneer installation. Comes in both standard and rapid version for faster curing. Easier to work with when compared to traditional methods — no drilling, cutting of kerfs or setting of pins — LATAPOXY® 310 Stone Adhesive allows for quick, easy plumb adjustment while stone is in place to compensate for uneven walls and stone thickness variations. LATAPOXY 310 Stone Adhesive is permanent; it will not fail or deteriorate over time and is ICC and IBC approved. Meets ISO 13007-1 R2 classification.

### PACKAGING

**Kit:** 2.6 gallon (10 ℓ): All components packed in one carton; 40 cartons per pallet. Available in standard and rapid versions.  
2 gallon (8 ℓ): 1.06 quart (8 x ℓ) units packed in one carton; 40 cartons per pallet. Available in standard and rapid versions.

**Cartridges:** 2.3 gallon (9 ℓ) Cartridge Pack (for use in LATAPOXY 310 Cordless Mixer): 15 x 0.16 gallon (0.6 ℓ) cartridges per carton, 27 cartons per pallet. Available in standard and rapid versions.

### MIXING

Combine equal volumes of LATAPOXY 310 Stone Adhesive Part A and LATAPOXY 310 Stone Adhesive Part B (1:1). Do not mix more than approximately 0.13 gallons (0.5 ℓ) of LATAPOXY 310 Rapid Stone Adhesive at a time.

Inches (or millimeters) out of plumb	Approximate Coverage	
	LATAPOXY® 310 Stone Adhesive Thickness	10 Liter Units
Plumb Wall (3 mm)	1/8" Thick (3 mm)	300 – 325 ft <sup>2</sup> (27 – 30 m <sup>2</sup> )
1/4" (6 mm)	1/4" Thick (6 mm)	150 – 170 ft <sup>2</sup> (14 – 16 m <sup>2</sup> )
1/2" (12 mm)	1/2" Thick (12 mm)	75 – 80 ft <sup>2</sup> (7 – 7.5 m <sup>2</sup> )



**Performance Level: BEST**

**Warranty: 25 Year**

Refer to Data Sheets  
679.0 and 679.3



Refer to Data Sheets 683.0

## LATAPOXY 310 Cordless Mixer

Triple your productivity of vertical stone and tile installations and dramatically reduce labor costs with the exclusive dual component LATAPOXY 310 Cordless Mixer. Quickly and easily dispenses LATAPOXY 310 Stone Adhesive onto tile, porcelain and stone veneers. Hundreds of square feet can be installed per day with less effort and greater success with this system. Patented design and gear system allow speed and dosing control for accurate applications every time. No mixing, just insert the dual component cartridge, screw on mixing nozzle and pull the trigger!

### PACKAGING

One LATAPOXY 310 Cordless Mixer per carton; 24 cartons per pallet.



## LATAPOXY 300 Adhesive

A high-strength, three-part 100% solids epoxy adhesive formulated for chemical resistant installations of quarry tile, brick and packing house tile. Prevents curling of moisture-sensitive marbles and agglomerates. Recommended for mesh mount glass mosaics and resin backed tiles and stones. Will not stain white or light colored marbles. "Extra Heavy" service rating per ASTM C627 (TCNA). Meets ANSI A118.3 and ISO 13007-1 R2 classification.

### PACKAGING

All components packed in one pail; 36 pails per pallet. Makes 1.8 gallons (6.8 l) of mortar.

Approximate Coverage Per #2 unit	
Notch Trowel	Coverage
1/16" (1.5 mm) V-notch	180 – 200 ft <sup>2</sup> (16.7 – 18.6 m <sup>2</sup> )
1/8" x 1/8" (3 mm x 3 mm) Square	90 – 110 ft <sup>2</sup> (8.4 – 10.2 m <sup>2</sup> )
3/16" (4 mm) V-notch	70 – 80 ft <sup>2</sup> (6.5 – 7.4 m <sup>2</sup> )
1/4" x 1/4" (6 mm x 6 mm) Square	30 – 35 ft <sup>2</sup> (2.8 – 3.3 m <sup>2</sup> )



**Performance Level: BEST**  
**Warranty: 25 Year, Lifetime**  
 Refer to Data Sheet 633.0



Community College of Southern Nevada, Cheyenne Campus, North Las Vegas, NV

## LATAPOXY 210 Adhesive

An economical, modified epoxy portland cement adhesive designed for tile and stone installations that are resistant to diluted chemicals, salts, and cleaning agents. Safe, odorless, and easy to use. "Extra Heavy" service rating per ASTM C627 (TCNA). Meets ANSI A118.8.

### PACKAGING

**Single Unit Pail:** All components packed into one pail; 48 pails per pallet; White. Makes 2.5 gallons (9.5 l) of mortar.

**Double Unit Carton:** All components packed into one carton; 27 cartons per pallet; Grey. Makes 5 gallons (19 l) of mortar.

Approximate Coverage Per single unit	
Notch Trowel	Coverage
1/8" x 1/8" (3 mm x 3 mm)	80 – 90 ft <sup>2</sup> (7.4 – 8.3 m <sup>2</sup> )
1/4" x 1/4" (6 mm x 6 mm)	40 – 50 ft <sup>2</sup> (3.7 – 4.6 m <sup>2</sup> )
1/4" x 3/8" (6 mm x 9 mm)	30 – 40 ft <sup>2</sup> (2.7 – 3.7 m <sup>2</sup> )



**Performance Level: GOOD**  
 Refer to Data Sheet 630.0

# Polymer Fortified Thin-Set Mortars



**Performance Level: BEST**  
**Warranty: Lifetime**  
 Refer to Data Sheet 677.0



## LATICRETE® 254 Platinum

The ultimate one-step, polymer-fortified thin-set that provides unsurpassed strength, far exceeding all ANSI A118.4 and ANSI A118.11 strength requirements. Meets ISO 13007-1 C2TES1P1 classification. Ideal for interior, exterior, and submerged applications on virtually all substrates and applications. Increases your productivity with long open time, allowing flexibility on the job site that results in fast, accurate installations. Easy to trowel mortar assures proper coverage on both the substrate and the veneer as well as less fatigue for the installer. The exceptional bond strength and easy workability of LATICRETE® 254 Platinum makes this multipurpose the ultimate adhesive for difficult to bond porcelain tiles as well as glass mosaics and large format glass. Inhibits the growth of stain-causing mold and mildew in substrates with Microban® antimicrobial protection.

### PACKAGING

50 lb (22.7 kg) bag; 56 bags per pallet; Grey and White.

### MIXING

Approximately 5 – 5.5 quarts/50 lbs (4.7 – 5.2 l) 22.7 kgs) of water per bag.

Approximate Coverage Per 50 lb (22.7 kg) bag	
Notch Trowel	Coverage
1/4" x 1/4" (6 mm x 6 mm)	80 – 95 ft <sup>2</sup> (7.4 – 8.8 m <sup>2</sup> )
1/4" x 3/8" (6 mm x 9 mm)	60 – 70 ft <sup>2</sup> (5.6 – 6.5 m <sup>2</sup> )
1/2" x 1/2" (12 mm x 12 mm)	40 – 45 ft <sup>2</sup> (3.7 – 4.2 m <sup>2</sup> )



**Performance Level: BEST**  
**Warranty: Lifetime**  
 Refer to Data Sheet 729.0

## LATICRETE 254R Platinum Rapid

Excellent for exterior applications which require rapid setting, LATICRETE 254R Platinum Rapid has unsurpassed adhesion and workability to exterior glue plywood, as well as concrete and porcelain tiles. This one-step, polymer fortified, thin-set mortar is designed to mix with water only. Inhibits the growth of stain-causing mold and mildew in the substrate with Microban antimicrobial protection.

### PACKAGING

25 lb (11.3 kg) bag; 104 bags per pallet; Grey and White.

### MIXING

Approximately 2.8 – 3.2 quarts/25 lbs (2.6 – 3.1 l/11.3 kg) of water per bag.

Approximate Coverage Per 25 lb (11.3 kg) bag	
Notch Trowel	Coverage
1/4" x 1/4" (6 mm x 6 mm)	40 – 47 ft <sup>2</sup> (3.7 – 4.4 m <sup>2</sup> )
1/4" x 3/8" (6 mm x 9 mm)	30 – 35 ft <sup>2</sup> (2.8 – 3.3 m <sup>2</sup> )
1/2" x 1/2" (12 mm x 12 mm)	20 – 23 ft <sup>2</sup> (1.9 – 2.1 m <sup>2</sup> )



## LATICRETE Sure Set™

LATICRETE Sure Set™ is a superior polymer fortified cementitious thin-set which eliminates the need for back buttering large format tile and stone in both thin bed or medium bed applications in wet and dry areas. LATICRETE Sure Set is mixed with water and has unique wetting characteristics which yields maximum coverage on larger tile and stone. This also allows the installer to quickly and easily install tile in a drop, adjust and go method.

### PACKAGING

50 lb (22.7 kg) bag; 56 bags per pallet; Grey and White.

### MIXING

Approximate water required per 50 lb (22.7 kg) bag: 5 qts (4.7 ℓ)

Approximate Coverage Per 50 lb (22.7 kg) bag	
Notch Trowel	Coverage
1/4" x 1/4" (6 mm x 6 mm)	80 – 95 ft <sup>2</sup> (7.4 – 8.8 m <sup>2</sup> )
1/4" x 3/8" (6 mm x 9 mm)	55 – 70 ft <sup>2</sup> (5.1 – 6.5 m <sup>2</sup> )
1/2" x 1/2" (12 mm x 12 mm)	40 – 55 ft <sup>2</sup> (3.7 – 5.1 m <sup>2</sup> )



**Performance Level: BEST**  
**Warranty: 25 Year**  
 Refer to Data Sheet 261.0



## LATICRETE Glass Tile Adhesive Mortar

LATICRETE Glass Tile Adhesive Mortar is a one-step, non-sag, polymer fortified adhesive mortar that is specifically formulated for use in glass tile applications. LATICRETE Glass Tile Adhesive Mortar has great workability and produces an ultra white finish that helps enhance the look of glass mosaics, glass tile, and most translucent tile or stone. In addition to containing Microban® antimicrobial protection, LATICRETE Glass Tile Adhesive Mortar is GREENGUARD certified for low VOC. LATICRETE Glass Tile Adhesive Mortar can also be used with porcelain or ceramic tile. Exceeds ANSI A118.4 and ANSI A118.11 bond strength requirements.

### MIXING

Approximately 2.5 qts (2.4 ℓ) of water for 25 lb bag

Approximate Coverage Per 25 lb (11.3 kg) bag	
Notch Trowel	Coverage
1/4" x 1/4" (6 mm x 6 mm)	35 ft <sup>2</sup> (3.2 m <sup>2</sup> )
1/4" x 3/8" (6 mm x 9 mm)	26 ft <sup>2</sup> (2.4 m <sup>2</sup> )
1/8" x 3/16" (3 mm x 4.5 mm)	52 ft <sup>2</sup> (4.8 m <sup>2</sup> )

Approximate Coverage Per 10 lb (4.5 kg) bag	
Notch Trowel	Coverage
1/4" x 1/4" (6 mm x 6 mm)	14 ft <sup>2</sup> (1.2 m <sup>2</sup> )
1/4" x 3/8" (6 mm x 9 mm)	10 ft <sup>2</sup> (0.9 m <sup>2</sup> )
1/8" x 3/16" (3 mm x 4.5 mm)	21 ft <sup>2</sup> (2.0 m <sup>2</sup> )



**Performance Level: BETTER**  
**Warranty: 25 Year**  
 Refer to Data Sheet 252.0



# Polymer Fortified Thin-Set Mortars



**Performance Level: BETTER**  
**Warranty: 5 Year**  
 Refer to Data Sheet 296.0



## LATICRETE® 253 Gold

LATICRETE® 253 Gold is a superior polymer fortified bagged cementitious thin-set powder to be mixed with water to install ceramic tile and stone using the thin-set method of installation. LATICRETE 253 Gold is designed for use in interior and exterior floor and wall installations of all types of ceramic tiles, porcelain tile and stone over concrete, exterior glue plywood\* and a variety of substrates.

\*Interior only

### PACKAGING

25 lb (11.3 kg) bag; 104 bags per pallet; White.  
 50 lb (22.7 kg) bag; 56 bags per pallet; Grey and White.

### MIXING

Approximately 5 – 5.5 quarts/50 lbs (4.7 – 5.2 *ℓ*/22.7 kg) of water per bag.

Approximate Coverage Per 50 lb (22.7 kg) bag	
Notch Trowel	Coverage
1/4" x 1/4" (6 mm x 6 mm)	80 – 95 ft <sup>2</sup> (7.4 – 8.8 m <sup>2</sup> )
1/4" x 3/8" (6 mm x 9 mm)	60 – 70 ft <sup>2</sup> (5.6 – 6.5 m <sup>2</sup> )



**Performance Level: BETTER**  
**Warranty: 5 Year**  
 Refer to Data Sheet 296.3

## LATICRETE 253R Gold Rapid

LATICRETE 253R Gold Rapid is an excellent solution for both interior and exterior applications that require a mortar with rapid setting characteristics. LATICRETE 253R Gold Rapid is a bagged cementitious powder to be mixed only with water to install ceramic tile, porcelain tile and stone using the thin-set method of installation. Designed for interior and exterior floor and wall installations of all types of ceramic tiles and stone over concrete, exterior glue plywood\* and a variety of other substrates and is ready for grouting in 2 to 4 hours.

\*Interior only

### PACKAGING

25 lb (11.3 kg) bag; 104 bags per pallet; Grey and White.  
 50 lb (22.7 kg) bag; 56 bags per pallet; Grey and White.

### MIXING

Approximately 2.8 – 3.2 quarts/25 lbs (2.6 – 3.1 *ℓ*/11.3 kg) or 5.6 – 6.4 qts/50 lb (5.2 – 6.1 *ℓ*/22.7 kg) of water per bag.

Approximate Coverage Per 25 lb (11.3 kg) bag	
Notch Trowel	Coverage
1/4" x 1/4" (6 mm x 6 mm)	40 – 47 ft <sup>2</sup> (3.7 – 4.4 m <sup>2</sup> )
1/4" x 3/8" (6 mm x 9 mm)	30 – 35 ft <sup>2</sup> (2.8 – 3.3 m <sup>2</sup> )

# Polymer Fortified Thin-Set Mortars/Non-Modified Thin-Set Mortars

## LATICRETE 252 Silver

For economical interior and exterior installations. Designed to be mixed with water for a strong bond. Meets ANSI A118.4 and ANSI A118.11 bond strength requirements.

### PACKAGING

50 lb (22.7 kg) bag; 56 bags per pallet; Grey and White.

### MIXING

Approximately 5 – 5.5 quarts/50 lbs (4.7 – 5.2 l/22.7 kg) of water per bag.

Approximate Coverage Per 50 lb (22.7 kg) bag	
Notch Trowel	Coverage
1/4" x 1/4" (6 mm x 6 mm)	80 – 95 ft <sup>2</sup> (7.4 – 8.8 m <sup>2</sup> )
1/4" x 3/8" (6 mm x 9 mm)	60 – 70 ft <sup>2</sup> (5.6 – 6.5 m <sup>2</sup> )



**Performance Level: GOOD**  
Refer to Data Sheet 676.0



## LATICRETE 272 Mortar

LATICRETE 272 Mortar is a high performance bagged cementitious powder for ceramic tile and stone installations. LATICRETE 272 Mortar can be mixed with either water or LATICRETE 101 Rapid Latex Admix to achieve an optimal bond strength for the desired application. For increased performance and flexibility, mix with LATICRETE 333 Super Flexible Additive. Meets ANSI A118.1 strength requirements.

\*Interior only

### PACKAGING

50 lb (22.7 kg) bag; 56 bags per pallet; Grey and White.

### MIXING

Per 50 lb (22.7 kg) bag; 2 gallons (7.6 l) of LATICRETE 333 Super Flexible Additive, 1.7 gallons (6.5 l) of LATICRETE 3701 Mortar Admix or water.

Approximate Coverage Per 50 lb (22.7 kg) bag	
Notch Trowel	Coverage
1/4" x 1/4" (6 mm x 6 mm)	75 – 90 ft <sup>2</sup> (7.0 – 8.4 m <sup>2</sup> )
1/4" x 3/8" (6 mm x 9 mm)	55 – 65 ft <sup>2</sup> (5.1 – 6 m <sup>2</sup> )



**Performance Level: GOOD**  
**\*Warranty: 5 Year, 25 Year, Lifetime**  
Refer to Data Sheets 259.0

\* When mixed with LATICRETE® 3701 Mortar Admix or LATICRETE 333 Super Flexible Additive.



# Non-Modified Thin-Set Mortars



**\*Warranty: 5 Year, 25 Year, Lifetime**

Refer to Data Sheet 317.0

\* When mixed with LATICRETE® 3701 Mortar Admix or LATICRETE 333 Super Flexible Additive.



## LATICRETE® 317

This smooth and creamy, sanded thin-set mortar can be used for interior and exterior applications on floors and walls over masonry, concrete, cement backer board, mortar beds and gypsum wallboard\*. Meets ANSI A118.1 strength requirements. For increased performance and flexibility, mix with LATICRETE® 333 Super Flexible additive. For use in exterior applications, mix with LATICRETE 3701 Mortar Admix.

\*Interior only

### PACKAGING

50 lb (22.7 kg) bag; 56 bags per pallet; Grey and White.

### MIXING

Per 50 lb (22.7 kg) bag; 2 gallons (7.6 l) of LATICRETE 333 Super Flexible Additive or LATICRETE 101 Rapid Latex Admix; 1.7 gallons (6.5 l) of LATICRETE 3701 Mortar Admix.

Approximate Coverage Per 50 lb (22.7 kg) bag	
Notch Trowel	Coverage
1/4" x 1/4" (6 mm x 6 mm)	75 – 90 ft <sup>2</sup> (7.0 – 8.4 m <sup>2</sup> )
1/4" x 3/8" (6 mm x 9 mm)	55 – 65 ft <sup>2</sup> (5.1 – 6 m <sup>2</sup> )



Refer to Data Sheet 291.0

## LATICRETE 8500 Glass Block Mortar

LATICRETE 8500 Glass Block Mortar is a high-strength, factory-prepared mortar for installing glass block. Economical and easy to use, LATICRETE 8500 Glass Block Mortar is recommended for interior and exterior use. It eliminates job site blending and provides a factory controlled mix for high performance.

### PACKAGING

50 lb (22.7 kg) bag; 54 bags per pallet; White.

### MIXING

Approximately 4 qts (3.8 l) of liquid mixes with 50 lbs (22.7 kg) of powder.

Approximate Coverage Per 100'² (9 m²) for 3-7/8" (10 cm) wide nominal block	
Glass Block	Number of bags
6" (15 cm)	14
8" (20 cm)	10.5
12" (30 cm)	7

# Latex Fortified Thin-Set Mortars and Latex Thin-Set Additives

## LATICRETE 4237 Latex Additive and LATICRETE 211 Powder

LATICRETE 4237 Latex Additive produces a high strength adhesive that is frost, weather and shock resistant. Designed for use with LATICRETE 211 Powder, LATICRETE 4237 Latex Additive is ideal for installing ceramic tiles, porcelain tiles, adhered masonry veneer brick and stone on concrete, brick, block, and masonry surfaces. "Extra Heavy" service rating per ASTM C627 (TCNA) and exceeds ANSI A118.4.

### PACKAGING

LATICRETE 4237 Latex Additive; 5 gallon (19 ℓ) pail; 36 pails per pallet.  
LATICRETE 211 Powder; 50 lb (22.7 kg) bag; 56 bags per pallet; Grey and White.

### MIXING

#### As a Thin-Set

Approximately 1.5 gallons (5.7 ℓ) of LATICRETE 4237 Latex Additive is required per 50 lb (22.7 kg) bag of LATICRETE 211 Powder.

**Approximate Coverage** Per 50 lb (22.7 kg) bag of LATICRETE® 211 Powder

Notch Trowel

Coverage

1/4" x 1/4" (6 mm x 6 mm)

80 – 95 ft<sup>2</sup> (7.4 – 8.8 m<sup>2</sup>)

1/4" x 3/8" (6 mm x 9 mm)

60 – 70 ft<sup>2</sup> (5.6 – 6.5 m<sup>2</sup>)



**Performance Level: BEST**  
**Warranty: 25 Year, Lifetime**

LATICRETE 4237 Latex Additive,  
Refer to Data Sheet 230.1

LATICRETE 211 Powder,  
Refer to Data Sheet 239.0



## LATICRETE 333 Super Flexible Additive

Create highly flexible thin-set mortars with superior bond strength with this incredible liquid additive. Mixes with all LATICRETE pre-bagged, non-fortified thin-set mortars for installation over concrete, brick, block, portland cement backer board, existing ceramic tile, cement terrazzo, exterior glue plywood\*, gypsum wallboard\*, vinyl tile\*, linoleum\*, plastic laminates\*, and non-water soluble cut back adhesives\*. Ideal for remodeling projects. "Extra Heavy" service rating per ASTM C627 (TCNA).

\*Interior only.

### PACKAGING

2 gallon (7.6 ℓ) jug; 3 jugs per carton; 40 cartons per pallet.  
5 gallon (19 ℓ) pail; 36 pails per pallet.

### MIXING

2 gallons (7.6 ℓ) mixes with approximately 50 lbs (22.7 kg) of LATICRETE thin-set mortars.



**Performance Level: BEST**  
**Warranty: 25 Year**

Refer to Data Sheet 266.0

## LATICRETE 101 Rapid Latex Admix

Offers high strength, rapid-setting properties when mixed with LATICRETE thin-set mortars, as well as other portland cement-based materials. Allows for grouting within 2 – 4 hours. May also be used for fast-setting wall or floor patches. Meets ANSI A118.4 and ANSI A118.11 bond strength requirements.

### PACKAGING

5 gallon (19 ℓ) pail; 36 pails per pallet.

### MIXING

2 gallons (7.6 ℓ) mixes with approximately 50 lbs (22.7 kg) of LATICRETE thin-set mortars.



**Performance Level: BEST**  
Refer to Data Sheet 264.0



**Performance Level: BEST**  
Refer to Data Sheet 286.0

## LATICRETE® 15 Premium Mastic

A white, non-flammable, pre-mixed, latex adhesive designed for interior installations of ceramic tile and stone on both floors and walls. Creamy and smooth, this water-resistant adhesive is ideal for installations over cement backer board, gypsum wallboard and exterior glue plywood. Exceeds ANSI A136.1 Type 1 and Type 2 requirements.

### PACKAGING

1 quart (0.9 ℓ) tub; 6 tubs per carton; 80 cartons per pallet.  
1 gallon (3.8 ℓ) pail; 4 pails per carton; 30 cartons per pallet.  
3.5 gallon (13.2 ℓ) pail; 48 pails per pallet.

Approximate Coverage Per gallon (3.8 ℓ) pail	
Notch Trowel	Coverage
1/8" (3 mm) V-notch	50 – 60 ft <sup>2</sup> (4.6 – 5.6 m <sup>2</sup> )
3/16" (5 mm) V-notch	30 ft <sup>2</sup> (2.8 m <sup>2</sup> )
1/4" x 1/4" (6 mm x 6 mm)	20 ft <sup>2</sup> (1.9 m <sup>2</sup> )



**Performance Level: BETTER**  
**Warranty: 25 Year**  
Refer to Data Sheet 080.0

## LATICRETE 4-XLT

LATICRETE® 4-XLT is a multi-use, polymer fortified adhesive mortar offering tremendous utility including non-sag wall installations, medium bed build up to 3/4" (19 mm) and thin-set applications on floors. LATICRETE 4-XLT is built on the LATICRETE Water Dispersion Technology™ (WDT) platform which provides for the complete dispersion of water within the mix allowing users to achieve the desired application consistency. LATICRETE 4-XLT also incorporates LATICRETE DUST LOCK™ Technology. This unique way of manufacturing our adhesives incorporated with LATICRETE plastic packaging dramatically reduces mess both during transportation of the product as well as during mixing. Exceeds both ANSI A118.4 and A118.11.

### PACKAGING

50 lb (22.7 kg) bag; 56 bags per pallet; Grey and White.

### MIXING

Approximately 5.25 – 6 quarts/50 lbs (5 – 5.7 ℓ/22.7 kg) of water per bag.

Application	Water
Wall and Medium Bed	5.25 qts (5 ℓ)
Thin-Set	6 qts (5.7 ℓ)

Approximate Coverage Per 50 lb (22.7 kg) bag	
Notch Trowel	Coverage
1/4" x 1/4" (6 mm x 6 mm)	80 – 95 ft <sup>2</sup> (7.4 – 8.8 m <sup>2</sup> )
1/4" x 3/8" (6 mm x 9 mm)	60 – 70 ft <sup>2</sup> (5.6 – 6.5 m <sup>2</sup> )
1/2" x 1/2" (12 mm x 12 mm)	40 – 47 ft <sup>2</sup> (3.7 – 4.4 m <sup>2</sup> )

WATER  
DISPERSION  
TECHNOLOGY™

DUST  
LOCK™

## LATICRETE 4-XLT Rapid

LATICRETE 4-XLT Rapid is a fast setting, multi-use, polymer fortified adhesive mortar for large format tile installations. LATICRETE 4-XLT Rapid offers tremendous utility for non-sag wall installations, medium bed build up and thin-set applications on floors. LATICRETE 4-XLT Rapid is built on LATICRETE Water Dispersion Technology™ (WDT) platform. WDT provides for the complete dispersion of water within the mix allowing users to achieve the desired application consistency. LATICRETE 4-XLT Rapid also features LATICRETE DUST LOCK™ Technology, dramatically reducing on-site mess both during transportation of the product as well as while mixing.

### PACKAGING

50 lb (22.7 kg) bag; 56 bags per pallet; Grey and White.

### MIXING

Approximate water required per 50 lb (22.7 kg) bag:

Application	Water
Wall and Medium Bed	5.25 – 5.5 qts (4.9 – 5.2 ℓ)
Thin-Set	5.5 – 6 qts (5.2 – 5.7 ℓ)

### Approximate Coverage Per 50 lb (22.7 kg) bag

Notch Trowel	Coverage
1/4" x 1/4" (6 mm x 6 mm)	80 – 95 ft <sup>2</sup> (7.4 – 8.8 m <sup>2</sup> )
1/4" x 3/8" (6 mm x 9 mm)	60 – 70 ft <sup>2</sup> (5.6 – 6.5 m <sup>2</sup> )
1/2" x 1/2" (12 mm x 12 mm)	40 – 47 ft <sup>2</sup> (3.7 – 4.4 m <sup>2</sup> )

## LATICRETE 255 MultiMax™

Carry only one product onto the job site for virtually all applications with this versatile lightweight mortar that replaces mastic, thin bed, and medium bed mortar. LATICRETE 255 MultiMax™ is reinforced with Kevlar® for unmatched non-sag performance and adjustability of large format tile and stone on walls. Build up to 3/4" (19 mm) without shrinkage on floors, without any slump, sag or lippage. Incredibly lightweight consistency allows for easy troweling onto the substrate with minimal effort. A 40 lb (18.2 kg) bag of LATICRETE 255 MultiMax provides the same coverage as a 50 lb (22.7 kg) bag of standard thin-set mortar. Mixes with water for maximum strength and performance. Inhibits the growth of stain-causing mold and mildew in substrates with Microban antimicrobial product protection.

### PACKAGING

40 lb (18.2 kg) bag; 56 bags per pallet; Grey and White.

### MIXING

Approximate water required per 40 lb (18.2 kg) bag:

Application	Water
Wall and Medium Bed	5.9 qts (5.6 ℓ)
Thin-Set	6.7 qts (6.4 ℓ)

### Approximate Coverage Per 40 lb (18.2 kg) bag

Application	Notch Trowel	Coverage
Wall	1/4" x 1/4" (6 mm x 6 mm)	72 – 88 ft <sup>2</sup> (6.7 – 8.2 m <sup>2</sup> )
	1/4" x 3/8" (6 mm x 9 mm)	48 – 58 ft <sup>2</sup> (4.4 – 5.4 m <sup>2</sup> )
Medium Bed	1/2" x 1/2" (12 mm x 12 mm)	36 – 44 ft <sup>2</sup> (3.3 – 4.1 m <sup>2</sup> )
Thin-Set	1/4" x 1/4" (6 mm x 6 mm)	80 – 98 ft <sup>2</sup> (7.4 – 9.1 m <sup>2</sup> )
	1/4" x 3/8" (6 mm x 9 mm)	54 – 66 ft <sup>2</sup> (5.0 – 6.1 m <sup>2</sup> )



**Performance Level: BETTER**  
**Warranty: 25 Year**  
 Refer to Data Sheet 080.0



**Performance Level: BEST**  
**Warranty: Lifetime**  
 Refer to Data Sheet 255.0



# Medium Bed Mortars/Premium Latex Mortar Beds



Refer to Data Sheet 297.0



## LATICRETE® 220 Marble & Granite Mortar

A fortified dry-set mortar specifically formulated to provide a one-step installation for large format ceramic tile, marble and stone, including ungauged tiles or installing tiles on a rough surface. LATICRETE® 220 Marble & Granite Mortar is mixed with water and can be built up to 3/4" (19 mm). Supports heavy tiles and stone, reducing lippage problems. For increased performance over hard to bond surfaces, mix with LATICRETE 333 Super Flexible Additive. For exterior use, mix with LATICRETE 3701 Mortar Admix.

### PACKAGING

50 lb (22.7 kg) bag; 56 bags per pallet; Grey and White.

### MIXING

Per 50 lb (22.7 kg) bag; 1.9 gallons (7.2 l) of LATICRETE 333 Super Flexible Additive or LATICRETE 101 Rapid Latex Amix; 1.25 gallons (4.7 l) of LATICRETE 3701 Mortar Admix or water.

Approximate Coverage Per 50 lb (22.7 kg) bag	
Notch Trowel	Coverage
3/4" (19 mm) Half Loop	25 – 35 ft <sup>2</sup> (2.3 – 3.2 m <sup>2</sup> )
1/2" x 1/2" (12 mm x 12 mm)	25 – 35 ft <sup>2</sup> (2.3 – 3.2 m <sup>2</sup> )



**Performance Level: BEST**

**Warranty: Lifetime**

Refer to Data Sheet 100.0



## LATICRETE 3701 Fortified Mortar Bed

LATICRETE 3701 Fortified Mortar Bed is a one-step polymer fortified blend of carefully selected raw materials, portland cement and graded aggregates. LATICRETE 3701 Fortified Mortar Bed does not require the use of latex admix; you only need to add water to produce a thick bed mortar or render with exceptional strength. Save time and money by eliminating the need for job site measuring and mixing of sand and cement to the proper ratio. A suitable alternative to LATICRETE 3701 Mortar Admix combined with LATICRETE 226 Thick Bed.

### PACKAGING

60 lb (27.3 kg) bag; 56 bags per pallet.

Approximate Coverage
12 ft <sup>2</sup> at 1/2" (1.1 m <sup>2</sup> at 12 mm)
6 ft <sup>2</sup> at 1" thickness (0.56 m <sup>2</sup> at 25 mm)
3 ft <sup>2</sup> at 2" (0.3 m <sup>2</sup> at 50 mm)



## LATICRETE 3701 Mortar Admix and LATICRETE 226 Thick Bed Mortar

When mixed together, LATICRETE 226 Thick Bed Mortar and LATICRETE 3701 Mortar Admix is a thick-bed mortar that is exceptionally strong and resistant to weather, frost, thermal, and physical shock. Can be used to build high strength concrete patches, stucco, and plaster mortars.

### PACKAGING

LATICRETE 3701 Mortar Admix; 5 gallon (19 ℓ) pail; 36 pails per pallet.  
LATICRETE 226 Thick Bed Mortar; 60 lb (27.3 kg) bag; 56 bags per pallet.

### MIXING

**As Thick Bed Mortar:** Approximately 5 gallons (19 ℓ) of admix is required per 7 x 60 lb (27.3 kg) bags of mortar.

#### Approximate Coverage As thick bed mortar

45 ft<sup>2</sup> (4 m<sup>2</sup>) at 1" (25 mm) thick per 1 x 5 gallon (19 ℓ) pail of admix and 7 x 60 lb (27.3 kg) bags of mortar.



**Performance Level: BEST**

**Warranty: 25 Year**

LATICRETE® 3701 Mortar Admix,  
Refer to Data Sheet 231.0

LATICRETE 226 Thick Bed Mortar,  
Refer to Data Sheet 239.1



## LATICRETE 209 Floor Mud

Pre-mixed, economical alternative to LATICRETE 226 Thick Bed Mortar, LATICRETE 209 Floor Mud mixes with LATICRETE 3701 Mortar Admix to provide a conventional floor mortar bed. Suitable for interior applications such as shower pan fills in bathrooms.

### PACKAGING

60 lb (27.3 kg) bag; 56 bags per pallet.

### MIXING

LATICRETE® 3701 Mortar Admix or Water	LATICRETE 209 Floor Mud
0.7 gal (2.7 ℓ)	60 lbs (27.3 kg)
1.0 gal (3.8 ℓ)	85 lbs (38.6 kg)
5.0 gal (19 ℓ)	420 lbs (190.9 kg)

#### Approximate Coverage

6 ft<sup>2</sup> (0.56 m<sup>2</sup>) at 1" (25 mm) thickness per 60 lb (27 kg) bag.



**Performance Level: GOOD**

Refer to Data Sheet 209.0



**Performance Level: BETTER**  
**Warranty: Lifetime**  
 Refer to Data Sheet 250.0



## LATICRETE® PermaColor™ Grout<sup>^</sup>

The maximum performance available in a cement-based grout. Provides consistent color, Microban® to resist stain-causing mold and mildew, and Kevlar®<sup>^</sup> for strength and durability. LATICRETE® PermaColor™ Grout<sup>^</sup> is easy to install and is just mixed with water (no additive required). Ideal for both floors and walls, joint widths of 1/16" (1.5 mm) to 1/2" (12 mm). For both interior and exterior applications.

### COLORS

See Grout and Sealant Color Chart on page 40 for a list of available colors.

### PACKAGING

25 lb (11.3 kg) bag; 104 bags per pallet.  
 8 lb (3.6 kg) box, 4 per carton, 44 cartons per pallet.

### Approximate Coverage

Refer to Grout Coverage Chart on page 41.

<sup>^</sup> United States Patent No.: 6,784,229 B2 (and other Patents).



**Performance Level: GOOD**  
**Warranty: 5 Year\***  
 Refer to Data Sheet 256.0

\*When mixed with LATICRETE® 1776 Grout Enhancer.



## LATICRETE 1500 Sanded Grout

For dense, durable grout joints between 1/16" (1.5 mm) and 3/8" (9 mm). Designed for use with LATICRETE 1776 Grout Enhancer or water. When LATICRETE 1500 Sanded Grout is mixed with LATICRETE 1776 Grout Enhancer, it eliminates shading and blotching caused by minerals and organic particles commonly found in domestic water, and inhibits the growth of stain-causing mold and mildew in grout joint with Microban® antimicrobial product protection. Meets ANSI A118.7.

### COLORS

See Grout and Sealant Color Chart on page 40 for a list of available colors.

### PACKAGING

10 lb (4.5 kg) box; 4 per carton; 44 cartons per pallet.  
 25 lb (11.3 kg) bag; 104 bags per pallet.

### Approximate Coverage

Refer to Grout Coverage Chart on page 41.

## LATICRETE 1600 Unsanded Grout

For dense, durable grout joints 1/8" (3 mm) wide or less. Designed for use with LATICRETE 1776 Grout Enhancer or water. When LATICRETE 1600 Unsanded Grout is mixed with LATICRETE 1776 Grout Enhancer, it eliminates shading and blotching caused by minerals and organic particles commonly found in domestic water, and inhibits the growth of stain-causing mold and mildew in grout joints with Microban antimicrobial product protection.

### COLORS

See Grout and Sealant Color Chart on page 40 for a list of available colors.

### PACKAGING

1 lb (0.45 kg) box; 8 per carton; 176 cartons per pallet; White only.

8 lb (3.6 kg) box; 4 per carton; 44 cartons per pallet.

25 lb (11.3 kg) bag; 104 bags per pallet (see color card for available colors).

### Approximate Coverage

Refer to Grout Coverage Chart on page 41.



**Performance Level: GOOD**

**Warranty: 5 Year\***

Refer to Data Sheet 258.0

\*When mixed with LATICRETE 1776 Grout Enhancer.



## LATICRETE 1776 Grout Enhancer

Designed for use with LATICRETE 1500 Sanded Grout or LATICRETE 1600 Unsanded Grout. LATICRETE 1776 Grout Enhancer, when used in place of water, eliminates shading and blotching caused by minerals and organic particles commonly found in domestic water. Inhibits the growth of stain-causing mold and mildew in the grout joints with Microban® antimicrobial product protection. "Extra Heavy" service rating per ASTM C627 (TCNA).

### PACKAGING

26 oz (0.75 ℓ) bottle; 12 per carton; 40 cartons per pallet.

47 oz (1.42 ℓ) bottle; 6 per carton; 48 cartons per pallet.

64 oz (1.85 ℓ) bottle; 6 per carton; 48 cartons per pallet.

5 gal (19 ℓ) pail; 36 pails per pallet.

### MIXING

#### LATICRETE® 1500 Sanded Grout

Package Size	LATICRETE 1776 Grout Enhancer
10 lb (4.5 kg) box	1 x 26 oz (0.8 ℓ) bottle
25 lb (11.3 kg) bag	1 x 64 oz (1.8 ℓ) bottle
50 lb (22.7 kg) bag	2 x 64 oz (1.8 ℓ) bottle

#### LATICRETE 1600 Unsanded Grout

Package Size	LATICRETE 1776 Grout Enhancer
8 lb (3.6 kg) box	1 x 47 oz (1.4 ℓ) bottle
25 lb (11.3 kg) bag	3 x 47 oz (1.4 ℓ) bottle



**Performance Level: BETTER**

**Warranty: 5 Year**

Refer to Data Sheet 265.0





**Performance Level: BEST**  
**Warranty: 25 Year, Lifetime**  
 Refer to Data Sheet 681.0



## LATICRETE® SpectraLOCK® PRO Premium Grout†

New and improved LATICRETE® SpectraLOCK® PRO Premium Grout† has all the great features of LATICRETE SpectraLOCK PRO Grout — color uniformity, durability and ease of installation — with enhanced performance. LATICRETE SpectraLOCK PRO Premium Grout is StainProof<sup>▲</sup>, so it's even easier to maintain. The improved “non-sag” formula is even easier to install while providing attractive, full grout joints.

- StainProof<sup>▲</sup>
- Improved non-sag formula
- Exceeds ANSI A118.3
- Easy to install; never needs sealing
- Inhibits the growth of stain-causing mold and mildew with Microban<sup>®</sup>
- Can be used on floors and walls
- Working time of 80 minutes

### PACKAGING (LIQUIDS ONLY KITS)

**Mini Unit:** Liquid components, gloves, sponge, and cleaning packets packed in one pail; 4 units per carton; 45 cartons per pallet.

**Full Unit:** Equals four LATICRETE SpectraLOCK PRO Premium Grout Mini Units. Liquid components, gloves, sponge, and cleaning packets packed in one pail; 80 pails per pallet.

**Commercial Unit:** Equals four LATICRETE SpectraLOCK PRO Premium Grout Full Units. Liquid components, gloves, sponge, and cleaning packets packed in one carton; 44 cartons per pallet.

**NOTE: LATICRETE® SpectraLOCK® Grout† Part C filler powder required and sold separately.**

### Approximate Coverage

Refer to Grout Coverage Chart on page 41.

<sup>▲</sup>Stainproof (residential installation only) to common household cleaners, liquids and other goods. Clean all spills immediately.

<sup>†</sup> United States Patent No.: 6881768 (and other Patents).



**Performance Level: BEST**  
**Warranty: Lifetime**  
 Refer to Data Sheet 685.0

## LATICRETE SpectraLOCK Grout Dazzle Part D Component

A unique design component, LATICRETE SpectraLOCK Grout Dazzle Part D Component adds metallic and “glow-in-the-dark” enhancements to LATICRETE SpectraLOCK PRO Premium Grout and LATICRETE SpectraLOCK PRO Grout. These high-end design elements offer limitless imaginative applications. Use LATICRETE SpectraLOCK Dazzle on walls and floors. Add a metallic look to plain tile and stone. Accentuate metallic tiles, glass tiles, mosaics, stone and listellos with dazzling color combinations. Use LATICRETE SpectraLOCK Grout Dazzle Part D Component in your pools and spas; and use LATICRETE SpectraLOCK Grout Dazzle Glow in your bathrooms, hallways and entry ways. For use in interior and exterior applications on floors and walls.

Colors		Packaging
1295 Gold	1296 Silver	1 x jar Dazzle; 2 per carton
1297 Copper	1298 Mother-of-Pearl	
1299 Glow-in-the-Dark		
Mixing		
LATICRETE® SpectraLOCK® PRO Grout† Liquids	Amount of LATICRETE SpectraLOCK Dazzle Required	
Mini Unit	1 x jar Dazzle	
Full Unit	4 x jar Dazzle	
Commercial Unit	16 x jar Dazzle	

## LATICRETE SpectraLOCK PRO Grout Part AB Liquids

LATICRETE SpectraLOCK PRO Grout offers high performance, color uniformity, durability, and stain resistance with extraordinary ease of use.

- Stain resistant
- Meets ANSI A118.3
- Easy to install
- Never needs sealing
- Working time of 80 minutes
- Can be used on floors and walls

### PACKAGING (LIQUIDS ONLY KITS)

**Mini Unit:** Liquid components, gloves, sponge, and cleaning packets packed in one pail; 4 units per carton; 45 cartons per pallet.

**Full Unit:** Equals four LATICRETE SpectraLOCK PRO Grout Mini Units. Liquid components, gloves, sponge, and cleaning packets packed in one pail; 80 pails per pallet.

**Commercial Unit:** Equals four LATICRETE SpectraLOCK PRO Grout Full Units. Liquid components, gloves, sponge, and cleaning packets packed in one carton; 44 cartons per pallet.

**NOTE:** LATICRETE SpectraLOCK Grout Part C filler powder required and sold separately.

### Approximate Coverage

Refer to Grout Coverage Chart on page 41.



**Performance Level: BEST**

**Warranty: Lifetime**

Refer to Data Sheet 685.0



## LATICRETE SpectraLOCK Grout Part C Powders

Available in 40 colors and designed to be used with LATICRETE SpectraLOCK PRO Premium Grout AB liquids, LATICRETE SpectraLOCK PRO Grout Part AB liquids and LATICRETE SpectraLOCK 2000 IG Part AB Liquids.

### COLORS

See Grout and Sealant Color Chart on page 40 for a list of available colors.

### PACKAGING

**Mini Unit:** 2 lb (0.9 kg) container; 4 containers per carton; 126 cartons per pallet.

**Full Unit:** 9 lb (4.1 kg) container; 4 containers per carton; 44 cartons per pallet.

**NOTE:** LATICRETE SpectraLOCK PRO Premium Grout Part AB Liquids, LATICRETE SpectraLOCK PRO Grout Part AB Liquids and LATICRETE SpectraLOCK 2000 IG Part AB Liquids required and sold separately.

### Approximate Coverage

Refer to Grout Coverage Chart on page 41.



**Performance Level: BEST**

**Warranty: Lifetime**

Refer to Data Sheet 685.0





**Performance Level: BEST**  
**Warranty: 25 Year**  
 Refer to Data Sheet 030.0



## LATICRETE® SpectraLOCK® 2000 IG

New three-part, 100% solids epoxy grout specifically formulated for maximum chemical, stain, and temperature resistance. New non-sag formula is easy to install and clean. Recommended for industrial and commercial food processing applications as well as dairies, breweries, meat packing plants, clean-in-place rooms, veterinary hospitals, kennels and commercial kitchens. LATICRETE® SpectraLOCK® 2000 IG is unaffected by many acids, corrosives, and solvents. Easy to clean and fast curing, LATICRETE SpectraLOCK 2000 IG is ideal for same day installations and ready for traffic in as little as 12 hours. Exceeds ANSI A118.3 and ANSI A118.5 requirements.

- Easy to install and clean
- Non-sag formula
- 80 minute working time
- Improved chemical resistance
- 20% more coverage than LATAPOXY® 2000 Industrial Grout
- Available in all LATICRETE grout colors except #44 Bright White — use LATICRETE SpectraLOCK Grout Part C Powders

### PACKAGING

**#2 Unit Pail Kit (Complete Unit):** Unit net weight 28.5 lb (12.9 kg); 48 pails per pallet.

**#2 Unit Pail (Liquid Only):** Unit net weight 10.5 lb (4.8 kg); 48 pails per pallet.

**#4 Unit Carton (Liquid Only):** Unit net weight 16 lb (7.3 kg); 56 cartons per pallet.

### Approximate Coverage

Refer to Grout Coverage Chart on page 41.



\* United States Patent No.: 6881768 (and other Patents).

## LATICRETE Premium Acrylic Caulk

LATICRETE Premium Acrylic Caulk is a high performance siliconized acrylic latex sealant designed for interior applications for ceramic tile and stone. It is ideal for a variety of caulking applications in bathrooms, kitchens and floors. LATICRETE Premium Acrylic Caulk also resists staining, mold, and mildew. LATICRETE Premium Acrylic Caulk cleans up easily with water and matches all 40 LATICRETE grout colors in sanded and unsanded varieties.

### COLORS

See Grout and Sealant Color Chart on page 40 for a list of available colors.

### PACKAGING

10.5 oz (310 ml) cartridges; 6 cartridges per carton; 240 cartons per pallet.

Approximate Coverage <small>Per cartridge</small>	
Thickness	Coverage
1/4" x 1/4" (6 mm x 6 mm)	25 linear feet (7.62 m)



**Performance Level: GOOD**

Refer to Data Sheet 6257.0

## LATICRETE Latasil™

High performance, 100% silicone sealant designed for use in coves, corners, changes in plane and expansion joints in exterior and interior applications of tile and stone. Can be used in swimming pools and other wet area applications. LATICRETE Latasil™ conforms to ASTM C920 and ASTM C794 adhesion properties and inhibits the growth of stain-causing mold and mildew in sealant joints with Microban® antimicrobial product protection.

### COLORS

See Grout and Sealant Color Chart on page 40 for a list of available colors.

### PACKAGING

10.3 oz (305 ml) cartridges; 6 cartridges per carton; 240 cartons per pallet.

Approximate Coverage <small>Per cartridge</small>	
Thickness	Coverage
1/4" x 1/4" (6 mm x 6 mm)	25 linear feet (7.62 m)
3/8" x 3/8" (9 mm x 9 mm)	11 linear feet (3.35 m)



**Performance Level: BEST**

**Warranty: Lifetime**

Refer to Data Sheets 6200.1



## LATICRETE Latasil™ 9118 Primer

Increases adhesion for porous stone, submerged, and permanent wet area applications.

### PACKAGING

8 oz (240 ml) bottle; 5 bottles per carton; 50 cartons per pallet.

Approximate Coverage <small>Per cartridge</small>	
Thickness	Coverage
1/4" x 1/4" (6 mm x 6 mm)	350 linear feet (106 m)
3/8" x 3/8" (9 mm x 9 mm)	175 linear feet (53 m)



Refer to Data Sheet 6528.1

# Grout and Sealant Color Chart

## LATICRETE® and LATAPOXY® Grouts and Sealants

This chart shows available colors for the following grouts and sealants:

LATICRETE® SpectraLOCK® PRO Premium Grout†

LATICRETE SpectraLOCK PRO Grout

LATICRETE PermaColor™ Grout‡

LATICRETE 1500 Sanded Grout

LATICRETE 1600 Unsanded Grout

LATICRETE SpectraLOCK® 2000 IG

LATICRETE Latasil™

LATICRETE Premium Acrylic Caulk

LATICRETE® SpectraLOCK® PRO Premium Grout†, LATICRETE SpectraLOCK PRO Grout, LATICRETE PermaColor™ Grout‡, and LATICRETE Premium Acrylic Caulk are available in all 40 colors. Use Grout Selection Key for all other products. LATICRETE SpectraLOCK Dazzle (Gold, Silver, Copper and Mother-of-Pearl) can be mixed with all 40 colors of LATICRETE SpectraLOCK PRO Premium Grout or LATICRETE SpectraLOCK PRO Grout.

## GROUT AND SEALANT SELECTION KEY

Available in All 40 Colors:

LATICRETE® SpectraLOCK® PRO Premium Grout†

LATICRETE SpectraLOCK PRO Grout

LATICRETE PermaColor™ Grout‡

LATICRETE Premium Acrylic Caulk (Sanded and Unsanded)

I, II and III Pricing Group

Available in Selected Colors:









































▲ LATICRETE Latasil™

■ LATICRETE SpectraLOCK Dazzle Glow

★ LATICRETE 1500 Sanded Grout and LATICRETE 1600 Unsanded Grout

# LATICRETE 1600 Unsanded Grout colors available in 25 lb (11.3 kg) bags

✓ LATICRETE SpectraLOCK 2000 IG is not available in Bright White

 <b>44 Bright White</b> I ▲ ■ # ★ ✓	 <b>18 Sauterne</b> III ■ # ★	 <b>16 Siltstone</b> II ■	 <b>85 Almond</b> II ▲ ■ # ★	 <b>03 Silk</b> III ■ ★
 <b>23 Antique White</b> II ▲ ■ # ★	 <b>39 Mushroom</b> II ▲ ■ ★	 <b>41 Kashmir</b> II ■ ★	 <b>81 Butter Cream</b> II ■ ★	 <b>52 Toasted Almond</b> II ▲ ■ ★
 <b>55 Tawny</b> II ▲	 <b>17 Marble Beige</b> III ▲ ■ # ★	 <b>40 Latte</b> II ▲ ■ ★	 <b>61 Parchment</b> II ▲ ■ # ★	 <b>30 Sand Beige</b> I ▲ ★
 <b>56 Desert Khaki</b> II ▲ ■	 <b>38 River Rock</b> II ■	 <b>27 Hemp</b> III ★	 <b>57 Hot Cocoa</b> II ▲	 <b>92 Siltstone</b> III ★
 <b>58 Terra Cotta</b> II ▲	 <b>46 Quarry Red</b> I ★	 <b>43 Chocolate Truffle</b> III ★	 <b>66 Chestnut Brown</b> III ▲ ★	 <b>59 Espresso</b> II ▲
 <b>35 Mocha</b> I ▲ ★	 <b>50 Sea Glass</b> II ▲ ■ ★	 <b>67 Autumn Green</b> II ▲	 <b>53 Twilight Blue</b> III	 <b>42 Platinum</b> I ▲ ★
 <b>91 Slate Grey</b> II ★	 <b>88 Silver Shadow</b> I ▲ ■ # ★	 <b>89 Smoke Grey</b> III ▲ ■ ★	 <b>90 Light Pewter</b> II ■ ★	 <b>78 Sterling Silver</b> II ▲ ■ ★
 <b>24 Natural Grey</b> I ▲ ★	 <b>34 Sandstone</b> II ★	 <b>60 Dusty Grey</b> II ▲	 <b>45 Raven</b> II ★	 <b>22 Midnight Black</b> I ▲ ★

**NOTE: Grout color availability subject to change. Visit [www.laticrete.com](http://www.laticrete.com) for the most current color selections.**

† United States Patent No.: 6881768 (and other Patents).

‡ United States Patent No.: 6784229 B2 (and other Patents).



## LATICRETE® PERMACOLOR™ GROUT United States Patent No.: 6,784,229 B2 (and other Patents).

TILE SIZE	JOINT WIDTH				
	1/16"	1/8"	1/4"	3/8"	1/2"
1 x 1 x 1/4"	100	51	28	20	16
2 x 2 x 1/4"	196	100	51	36	28
4-1/4 x 4-1/4 x 5/16"	331	167	85	57	44
6 x 6 x 1/2"	291	146	74	50	38
12 x 12 x 3/8"	774	388	195	131	99
13 x 13 x 3/8"	839	420	211	141	107
16 x 16 x 3/8"	1032	517	259	174	131
18 x 18 x 3/8"	1160	581	292	195	147
	<b>1.5 mm</b>	<b>3 mm</b>	<b>6 mm</b>	<b>9 mm</b>	<b>12 mm</b>
25 x 25 x 6 mm	10.2	5.3	2.8	2.0	1.6
50 x 50 x 6 mm	20.1	10.2	5.3	3.6	2.8
106 x 106 x 7.5 mm	33.8	17.0	8.6	5.8	4.4
150 x 150 x 12 mm	29.8	15.0	7.6	5.2	3.9
300 x 300 x 9 mm	79.4	39.8	20.0	13.4	10.1
325 x 325 x 9 mm	86.0	43.1	21.6	14.5	10.9
400 x 400 x 9 mm	105.8	53.0	26.6	17.8	13.4
425 x 425 x 9 mm	112.4	56.3	28.2	18.9	14.2

Approximate ft<sup>2</sup> (m<sup>2</sup>) coverage per 25 lb (11.3 kg) unit.

## LATICRETE 1600 UNSANDED GROUT

TILE SIZE	JOINT WIDTH	
	1/16"	1/8"
4-1/4 x 4-1/4 x 5/16"	144	72
6 x 6 x 5/16"	202	102
	<b>1.5 mm</b>	<b>3 mm</b>
106 x 106 x 7.5 mm	14.7	7.4
150 x 150 x 7.5 mm	4.5	3.0

Approximate ft<sup>2</sup> (m<sup>2</sup>) coverage per 8 lb (3.6 kg) unit.

## LATICRETE SPECTRALOCK 2000 IG

TILE SIZE	JOINT WIDTH		
	1/4"	3/8"	1/2"
4 x 8 x 1-3/16"	30	21	16
6 x 6 x 1/2"	80	55	42
<b>TAMAÑO CERAMICA</b>	<b>6 mm</b>	<b>9 mm</b>	<b>12 mm</b>
100 x 200 x 30 mm	2.8	1.9	1.6
150 x 150 x 12 mm	7.4	5.1	3.9

Approximate ft<sup>2</sup> (m<sup>2</sup>) coverage per #2 unit.

## LATICRETE 1500 SANDED GROUT

TILE SIZE	JOINT WIDTH			
	1/16"	1/8"	1/4"	3/8"
1 x 1 x 1/4"	100	51	28	20
2 x 2 x 1/4"	196	100	51	36
4-1/4 x 4-1/4 x 5/16"	331	167	85	57
6 x 6 x 1/2"	291	146	74	50
12 x 12 x 3/8"	774	388	195	131
13 x 13 x 3/8"	839	420	211	141
16 x 16 x 3/8"	1032	517	259	174
18 x 18 x 3/8"	1160	581	292	195
	<b>1.5 mm</b>	<b>3 mm</b>	<b>6 mm</b>	<b>9 mm</b>
25 x 25 x 6 mm	10.2	5.3	2.8	2.0
50 x 50 x 6 mm	20.1	10.2	5.3	3.6
106 x 106 x 7.5 mm	33.8	17.0	8.6	5.8
150 x 150 x 12 mm	29.8	15.0	7.6	5.2
300 x 300 x 9 mm	79.4	39.8	20.0	13.4
325 x 325 x 9 mm	86.0	43.1	21.6	14.5
400 x 400 x 9 mm	105.8	53.0	26.6	17.8
425 x 425 x 9 mm	112.4	56.3	28.2	18.9

Approximate ft<sup>2</sup> (m<sup>2</sup>) coverage per 25 lb (11.3 kg) unit.

## LATICRETE SPECTRALOCK® PRO PREMIUM GROUT

### LATICRETE SPECTRALOCK PRO GROUT

United States Patent No.: 6881768 (and other Patents).

TILE SIZE	JOINT WIDTH				
	1/16"	1/8"	1/4"	3/8"	1/2"
1 x 1 x 1/4"	41	21	11	8	7
2 x 2 x 1/4"	80	41	21	15	11
4-1/4 x 4-1/4 x 5/16"	135	68	35	23	18
6 x 6 x 1/2"	119	60	30	20	15
12 x 12 x 3/8"	317	159	80	54	44
13 x 13 x 3/8"	344	172	87	58	43
16 x 16 x 3/8"	423	212	106	71	54
18 x 18 x 3/8"	475	238	119	80	60
	<b>1.5 mm</b>	<b>3 mm</b>	<b>6 mm</b>	<b>9 mm</b>	<b>12 mm</b>
25 x 25 x 6 mm	4.2	2.1	1.1	0.8	0.7
50 x 50 x 6 mm	8.2	4.2	2.1	1.5	1.1
106 x 106 x 7.5 mm	13.8	6.9	3.5	2.4	1.8
150 x 150 x 12 mm	12.2	6.1	3.1	2.1	1.6
300 x 300 x 9 mm	32.3	16.2	8.1	5.5	4.1
325 x 325 x 9 mm	35.0	17.6	8.8	5.9	4.5
400 x 400 x 9 mm	43.1	21.6	10.8	7.3	5.5
450 x 450 x 9 mm	48.5	24.3	12.2	8.1	6.1

Approximate ft<sup>2</sup> (m<sup>2</sup>) coverage per full unit.

## GROUT AND SEALANT COLOR GUIDELINES

Grout and sealant samples are guides only. LATICRETE does not warrant color matching to this color chart or to any color guide produced. Actual shade and texture will depend on job site conditions, lighting, installation techniques and types of tile or stone used, and may vary from this grout color chart, grout color channel kits and grout color swatch on product packaging. Verify actual appearance and compatibility with a test area before installing. Blend grouts with different control numbers. Follow ANSI A108.10/MMSA Bulletin #9 grouting practices. No claims for color shade variations will be honored.

Calculated coverage indicated is approximate, based on "nominal" tile size and is provided for purposes of estimation only. Actual coverage will vary depending on job site conditions, actual tile size and installed grout joint size. Add 10% for waste, spillage and clean-up, and another 10% – 15% when grouting unglazed quarry tile. Expanded coverage tables at [www.laticrete.com/coverage](http://www.laticrete.com/coverage).

# Product Selection and Substrate Guide

## SUBSTRATES<sup>1</sup>

Category	Product	Concrete	Portland Cement Mortar Bed	Ceramic Tile <sup>2</sup>	Masonry	Cement Backer Board
<b>UNDERLAYMENTS</b>	LATICRETE® 86 LatilLevel™ *	I <sup>2</sup>	I	I**	I	I
	LATICRETE 84 LatilLevel	I <sup>2</sup>	I	I**	I	I
	LATICRETE 816 Latipatch™ *	I	I	I <sup>9</sup>	I	I
<b>SOUND CONTROL</b>	LATICRETE 170 Sound & Crack Isolation Mat *	I	I	I	I	I
<b>ANTI-FRACTURE MEMBRANE</b>	LATICRETE Blue 92 Anti-Fracture Membrane	E	E	E**	E	E
<b>WATERPROOFING MEMBRANES</b>	LATICRETE Hydro Ban®	E	E	E**	E	E
	LATICRETE 9235 Waterproofing Membrane	E	E	E**	E	E
	LATICRETE Hydro Barrier™	E	E	E**	E	E
	LATAPOXY® Waterproof Flashing Mortar	E	E	^^	E	E
<b>VAPOR REDUCTION MEMBRANE</b>	LATAPOXY 312 Vapor Reduction Membrane	I	I	N	N	N
<b>EPOXY ADHESIVES</b>	LATAPOXY 300 Adhesive	E^	E^	E^	E^	E^
	LATAPOXY 210 Adhesive	E	E	E	E	E
<b>SPOT BOND ADHESIVES</b>	LATAPOXY 310 Stone Adhesive / LATAPOXY 310 Rapid Stone Adhesive	E†	N	I	E†	I
<b>LATEX THICK-BED</b>	LATICRETE 3701 Fortified Mortar Bed	E	E	E	E	E
	LATICRETE 3701 Mortar Admix with LATICRETE 226 Thick-Bed Mortar	E	E	E	E	E
<b>SOUND CONTROL/CRACK SUPPRESSION MORTAR</b>	LATICRETE 125 Sound & Crack Adhesive * *	I	I	I	I	I
<b>MEDIUM-BED</b>	LATICRETE 255 MultiMax™ x	E	E	E	E	E
	LATICRETE 4-XLT	E	E	E	E	E
	LATICRETE 4-XLT Rapid	E	E	E	E	E
	LATICRETE 220 Marble & Granite Mortar	E	E	E <sup>7</sup>	E	E
<b>LATEX THIN-BED</b>	LATICRETE 4237 Latex Additive with LATICRETE 211 Powder	E	E	E	E	E
	LATICRETE 3701 Mortar Admix with LATICRETE 272 Mortar, LATICRETE 317, or LATICRETE 220 Marble & Granite Mortar	E	E	E	E	E
<b>FLEXIBLE LATEX THIN-BED</b>	LATICRETE 333 Super Flexible Additive with LATICRETE 272 Mortar, LATICRETE 317, or LATICRETE 220 Marble & Granite Mortar	E <sup>6</sup>	E <sup>6</sup>	E <sup>6</sup>	E <sup>6</sup>	E <sup>6</sup>
<b>RAPID LATEX THIN-BED</b>	LATICRETE 101 Rapid Latex Admix with LATICRETE 272 Mortar, LATICRETE 317, or LATICRETE 220 Marble & Granite Mortar	E	E	E	E	E
<b>MULTIPURPOSE THIN-SET MORTARS</b>	LATICRETE 254 Platinum	E	E	E	E	E
	LATICRETE 255 MultiMax	E	E	E	E	E
	LATICRETE Sure Set™ *	I	I	I	I	I
	LATICRETE 253 Gold	E	E	E	E	E
	LATICRETE 254R Platinum Rapid	E	E	E	E	E
	LATICRETE 253R Gold Rapid	E	E	E	E	E
	LATICRETE 252 Silver	E	E	I	E	I
<b>GLASS TILE INSTALLATION MORTAR</b>	LATICRETE Glass Tile Adhesive Mortar	E	E	E	E	E
<b>THIN-SET MORTAR ADHESIVES</b>	LATICRETE 272 Mortar	E <sup>4</sup>	E <sup>4</sup>	I <sup>10</sup>	E <sup>4</sup>	E <sup>10</sup>
	LATICRETE 317	E <sup>4</sup>	E <sup>4</sup>	I <sup>10</sup>	E <sup>4</sup>	E <sup>10</sup>
	LATICRETE 15 Premium Mastic	I	I	N	I	I
<b>MASONRY VENEER INSTALLATION</b>	LATICRETE Hi-Bond Masonry Veneer Mortar	E	E	E	E	E
	LATICRETE Hi-Bond Rapid Masonry Veneer Mortar	E	E	E	E	E
	LATICRETE Masonry Veneer Mortar	E	E	N	E	E
	LATICRETE Thin Brick Mortar	E	E	E	E	E

E = Recommended for exterior and interior applications.

I = Recommended for interior applications only.

N = Not recommended for these applications.

1 Structurally sound, clean, free of dust, laitance, dirt, oil, grease, wax, sealers and curing compounds; floor systems over which tile or stone will be installed shall be in conformance with the International Residential Code (IRC) for residential applications, the International Building Code (IBC) for commercial applications, or applicable building codes; concrete must be 28 days old w/ 7 day damp cure unless using LATICRETE® 4237 Latex Thin-Set Mortars, LATICRETE 3701 Latex Thin-Set Mortars or LATICRETE 254 Platinum

2 For existing resilient flooring, ceramic tile, terrazzo, and non-water soluble cutback adhesive — see LATICRETE Technical Data Sheet 135 — Ceramic & Stone Tile Over Existing Flooring

3 For proper plywood floor construction — see LATICRETE Technical Data Sheet 152 — Bonding Ceramic Tile, Stone or Brick Over Wood Floors

4 Exterior use requires gauging with LATICRETE 333 Super Flexible Additive (residential and light commercial installations that are not continuously submerged)—see data sheet 266.0 or LATICRETE 3701 Mortar Admix — see data sheet 231.0

5 Use as an unbonded, wire-reinforced mortar bed or installed over diamond metal lath which has been mechanically fastened to the substrate for horizontal applications; or, as a scratch coat and brown coat over diamond metal lath which has been mechanically fastened into the studs, over cleavage membrane for vertical installations

6 Exterior use limited to residential and light commercial installations that are not continuously submerged

7 Requires gauging with LATICRETE 3701 Mortar Admix — see data sheet 231.0

8 Requires gauging with LATICRETE 333 Super Flexible Additive — see data sheet 266.0

9 Requires gauging with LATICRETE Admix and Primer — see data sheet 674.0

10 Requires gauging with a LATICRETE latex additive (see recommended combinations above) for all applications

11 Prime floor with LATICRETE Admix and Primer prior to mechanically fastening 3.2# diamond metal lath over entire substrate — see data sheet 238.9

12 All concrete surfaces must be bead blasted or mechanically abraded to ensure curing compounds, sealers or other potential bond breakers are removed — see data sheet 238.9

\* Horizontal use only. LATICRETE 170 Sound & Crack Isolation Mat can be turned up the wall (max. of 3" [75 mm]) in place of the perimeter isolation strip

\*\* Skim coat existing ceramic tile, stone or portland cement terrazzo with a latex thin-bed mortar first

^ Do not use on exterior facades or building envelopes

^^ Consult LATICRETE Technical Services for these substrates

† Consult LATICRETE Technical Services Dept. for exterior applications

<sup>1</sup> United States Patent No. 6784229 B2 (and other Patents).

# Product Selection and Substrate Guide

## SUBSTRATES<sup>1</sup>

Category	Product	Cement Terrazzo <sup>2</sup>	Exterior Glue Plywood <sup>2</sup>	Resilient Flooring <sup>2</sup>	Gypsum Wallboard	Hi- Pressure Laminate	Steel	Data Sheet #
<b>UNDERLAYMENTS</b>	LATICRETE 86 LatiLevel *	I <sup>12</sup>	I <sup>11</sup>	N	N	N	N	238.5
	LATICRETE 84 LatiLevel	I <sup>12</sup>	I <sup>11</sup>	N	N	N	N	084.0
	LATICRETE 816 LatiPatch *	I	I	I <sup>2</sup>	N	N	N	674.0
<b>SOUND CONTROL</b>	LATICRETE 170 Sound & Crack Isolation Mat *	I	I	N	N	N	N	170.0
<b>ANTI-FRACTURE</b>	LATICRETE Blue 92 Anti-Fracture Membrane	E**	I	N	I	N	N	647.0
<b>WATERPROOFING MEMBRANES</b>	LATICRETE Hydro Ban	E**	I	N	I	N	N	663.0
	LATICRETE 9235 Waterproofing Membrane	E**	I	N	I	N	N	236.0
	LATICRETE Hydro Barrier	E**	I	N	I	N	N	105.0
	LATAPOXY Waterproof Flashing Mortar	^^	^^	^^	^^	^^	^^	682.0
<b>VAPOR REDUCTION MEMBRANE</b>	LATAPOXY 312 Vapor Reduction Membrane	N	N	N	N	N	N	312.0
<b>EPOXY ADHESIVES</b>	LATAPOXY 300 Adhesive	E	I	I	I	I	E	633.0
	LATAPOXY 210 Adhesive	E	I	I	I	I	E	630.0
<b>SPOT BOND ADHESIVES</b>	LATAPOXY 310 Stone Adhesive / LATAPOXY 310 Rapid Stone Adhesive	N	I	N	N	N	I <sup>†</sup>	679.0/679.3
<b>LATEX THICK-BED</b>	LATICRETE 3701 Fortified Mortar Bed	E	I <sup>5</sup>	I <sup>5</sup>	I <sup>5</sup>	I <sup>5</sup>	I <sup>5</sup>	100.0
	LATICRETE 3701 Mortar Admix with LATICRETE 226 Thick-Bed Mortar	E	I <sup>5</sup>	I <sup>5</sup>	I <sup>5</sup>	I <sup>5</sup>	I <sup>5</sup>	231.0
<b>SOUND CONTROL /CRACK SUPPRESSION MORTAR</b>	LATICRETE 125 Sound & Crack Adhesive *	I	I	N	N	N	N	204.0
<b>MEDIUM-BED</b>	LATICRETE 255 MultiMax	N	I	N	I	N	N	255.0
	LATICRETE 4-XLT	N	I	N	I	N	N	080.0
	LATICRETE 4-XLT Rapid	N	I	N	I	N	N	081.0
	LATICRETE 220 Marble & Granite Mortar	E	I <sup>8</sup>	I <sup>8</sup>	I <sup>10</sup>	I <sup>8</sup>	N	297.0
<b>LATEX THIN-BED</b>	LATICRETE 4237 Latex Additive with LATICRETE 211 Crete Filler Powder	E	N	N	I	N	N	230.1/239.0
	LATICRETE 3701 Mortar Admix	E	N	N	I	N	N	231.0
	LATICRETE 272 Mortar, LATICRETE 317, or LATICRETE 220 Marble & Granite Mortar							259.0/ 317.0/297.0
<b>FLEXIBLE LATEX THIN-BED</b>	LATICRETE 333 Super Flexible Additive with LATICRETE 272 Mortar, LATICRETE 317, or LATICRETE 220 Marble & Granite Mortar	E <sup>5</sup>	I	I	I	I	N	266.0/259.0/ 317.0/297.0
<b>RAPID LATEX THIN-BED</b>	LATICRETE 101 Rapid Latex Admix with LATICRETE 272 Mortar, LATICRETE 317, or LATICRETE 220 Marble & Granite Mortar	E	I	N	I	N	N	264.0/259.0/ 317.0/297.0
<b>MULTIPURPOSE THIN-SET MORTARS</b>	LATICRETE 254 Platinum	E	I	I	I	I	N	677.0
	LATICRETE 255 MultiMax	E	I	N	I	N	N	255.0
	LATICRETE Sure Set *	I	I	N	N	N	N	261.0
	LATICRETE 253 Gold	E	I	I	I	I	N	296.0
	LATICRETE 254 Platinum Rapid	E	I	I	I	I	N	729.0
	LATICRETE 253R Gold Rapid	E	I	I	I	I	N	296.3
	LATICRETE 252 Silver	I	I	N	I	N	N	676.0
<b>GLASS TILE INSTALLATION MORTAR</b>	LATICRETE Glass Tile Adhesive Mortar	E	I	N	I	N	N	252.0
<b>THIN-SET MORTAR ADHESIVES</b>	LATICRETE 272 Mortar	I <sup>10</sup>	I <sup>8</sup>	I <sup>8</sup>	I	I <sup>8</sup>	N	259.0
	LATICRETE 317	I <sup>10</sup>	I <sup>8</sup>	I <sup>8</sup>	I	I <sup>8</sup>	N	317.0
	LATICRETE 15 Premium Mastic	N	I	N	I	N	N	286.0
<b>MASONRY VENEER INSTALLATION</b>	LATICRETE Hi-Bond Masonry Veneer Mortar	E	I	N	I	N	N	246.0
	LATICRETE Hi-Bond Rapid Masonry Veneer Mortar	E	I	N	N	N	N	247.0
	LATICRETE Masonry Veneer Mortar	N	N	N	N	N	N	060.0
	LATICRETE Thin Brick Mortar	N	I	N	N	N	N	248.0



**Innovative Tile and Stone  
Installation Systems**

Disponible en français.

Visiter [www.laticrete.com/fr](http://www.laticrete.com/fr) pour les informations complètes.

Disponible en español.

Visite [www.laticrete.com/sp](http://www.laticrete.com/sp) para la información completa.

#### Corporate Headquarters:

LATICRETE International, Inc.  
One LATICRETE Park North  
Bethany, CT 06524-3423 USA  
1.800.243.4788  
+1.203.393.0010

[www.laticrete.com](http://www.laticrete.com)

Asia Pacific: +852.2526.6660

Australia: +61.7.3865.1599

China: +86.21.5789.3300

Europe: +34.96.649.1908

India: +91.40.3041.3100

Latin America: +1.203.393.0010

Middle East: +971.7.244.6396

South East Asia: +65.6515.3028

DS-221.0-0612

©2012 LATICRETE International, Inc.  
All trademarks shown are the intellectual properties of their respective owners.

