



15 Year System Warranty

FOR INTERIOR PROJECTS ONLY

APPLICATION	PRODUCTS
Underlayment	DRYTEK® 7200 DRYTEK 7600 DRYTEK Multi-Purpose Primer DRYTEK 104S Epoxy Primer
Floor Warming	LATICRETE® Floor HEAT Mat (only)
Waterproofing/Anti-Fracture	LATICRETE 9235 Waterproofing Membrane LATICRETE Hydro Ban™ LATAPOXY® Waterproof Flashing Mortar
Sound Control/Anti-Fracture	LATICRETE 125 Sound & Crack Adhesive LATICRETE 170 Sound & Crack Isolation Mat * LATICRETE QT Sound Control Underlayment Patent No.: 6,920,723
Thin Bed Method	LATICRETE 254 Platinum (regular or rapid version) LATICRETE 255 MultiMax™ United States Invention Patent No.: 6,784,229 B2 LATAPOXY 300 Adhesive LATICRETE Sure Set™ LATICRETE Glass Tile Adhesive LATICRETE 4-XLT * LATICRETE 4237 Latex Additive mixed with any of the following <ul style="list-style-type: none"> ▪ LATICRETE 211 Powder; or ▪ LATICRETE 317; or ▪ LATICRETE 272 Mortar ; or ▪ LATICRETE PermaColor™ Grout (for installation of paper face mounted glass mosaics only) LATICRETE 4237 Latex Additive mixed with LATICRETE 272 Mortar LATICRETE 3701 Mortar Admix mixed with any of the following <ul style="list-style-type: none"> ▪ LATICRETE 272 Mortar; or ▪ LATICRETE 317; or ▪ LATICRETE 220 Marble & Granite Mortar * LATICRETE 325 Premium Tile Adhesive mixed with LATICRETE 333 Super Flexible Additive
Grouting	LATICRETE SpectraLOCK PRO Premium Grout (non-industrial applications)United States Invention Patent No.: 6881768 (and other Patents) LATICRETE SpectraLOCK® PRO Grout (non-industrial applications) LATAPOXY 2000 Industrial Grout LATICRETE SpectraLOCK 2000 IG LATICRETE PermaColor Grout * LATAPOXY SP-100
Sealant†	LATICRETE Latasil™ LATICRETE Latasil 9118 Primer

† Use of suitable flexible sealant is required per Tile Council of North America Detail EJ171 for use in expansion joints, coves, corners, changes in plane and other joints or wherever tile or stone abuts dissimilar materials or restraining surfaces.

* Available in the markets outside of the United States of America and Canada.

LIMITED WARRANTY

Subject to the conditions and limitations stated below, LATICRETE INTERNATIONAL, INC. ("LATICRETE") warrants that the products listed on this document will be free from manufacturing defects and will not break down or deteriorate under normal usage for a period of fifteen (15) years from the date of purchase when installed in accordance with the written specifications of LATICRETE and industry standard guidelines. For this limited warranty to apply, the applications that comprise the installation must be performed with the products listed in this document for each application (refer to chart).

DISCLAIMER

THIS LIMITED WARRANTY IS GIVEN IN LIEU OF ANY OTHER WARRANTY, EXPRESS OR IMPLIED. THERE ARE NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WARRANTIES BASED ON SAMPLES OR ORAL STATEMENTS, WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE OF THIS DOCUMENT. IMPLIED WARRANTIES OF MERCHANTABILITY AND OF FITNESS FOR A PARTICULAR PURPOSE ARE EXCLUDED.

EXCLUSIVE REMEDY

The sole and exclusive remedy for a breach of this limited warranty is replacement of only the specific portion of the installation that is proven to be defective**. LATICRETE will pay for replacement of its own products and replacement of finishing materials, as well as for labor for the replacement installation, but LATICRETE will not pay more, calculated on a square-foot (square-meter) basis, for the replacement than the original purchase price of the portion being replaced. LATICRETE will not pay for replacement of any portion of the installation that is not proven to be defective.

In the event that the sole and exclusive remedy described above fails of its essential purpose, the liability of LATICRETE is limited to the monetary value, on a square-foot (square-meter) basis, of the original purchase price of the portion being replaced.

**NOTE: Efflorescence is a normal condition of cement mortars and is not a defective condition.

EXCLUSIONS

LATICRETE is not responsible for workmanship not in accordance with the instructions of LATICRETE and industry standard guidelines. Cracking due to structural movement, excessive deflection or other failure in the substrate is also not covered.

LATICRETE IS NOT LIABLE FOR ANY INCIDENTAL DAMAGES OR CONSEQUENTIAL DAMAGES, INCLUDING LOSSES DUE TO DELAYS, INCURRED BY THE PURCHASER OR ANY OTHER PARTY.

NO ASSIGNMENT

This limited warranty is not transferable or assignable.

HOW TO MAKE A CLAIM

To make a claim under this limited warranty, you must notify LATICRETE in writing within thirty (30) days of the discovery of the alleged manufacturing defect. At the option of LATICRETE, you may be required, as a condition of this limited warranty, to provide proof of product purchase and use.

Address your claim to:

LATICRETE International, Inc.
1 LATICRETE Park
North Bethany, CT 06524-3423 USA
Attn.: Technical Services Department

TECHNICAL INFORMATION

Technical assistance and information is available by calling the LATICRETE Technical Services Line:

Toll Free: 1.800.243.4788, ext. 235
Telephone: +1.203.393.0010, ext. 235
Fax: +1.203.393.1948

LATICRETE International, Inc.
One LATICRETE Park North
Bethany, CT 06524-3423 USA
1.800.DRYTEK.1
+1.203.393.0010

www.drytek.com