

vinyl

ACCESSORIES



nosings

- #202 overlap stair nosing 1/8"**
- Square nosing; ribbed safety surface
 - Installation Radius: 11 ft.
 - 10 12-ft. secs. per ctn. (120 ft.) **ADA**
- #203 domestic stair nosing 1/8"**
- For light-duty applications; installs over vinyl tile or sheet goods
 - Installation Radius: 11 ft.
 - 5 12-ft. secs. per ctn. (60 ft.) **ADA**
- #204 undercut carpet nosing 1/4"**
- Heavy-duty for 1/4" and 5/16" carpet
 - Installation Radius: 11 ft.
 - 5 12-ft. secs. per ctn. (60 ft.) **ADA**
- #206 double undercut stair nosing 1/4"**
- For 1/4" and 5/16" carpet
 - Installation Radius: 11 ft.
 - 5 12-ft. secs. per ctn. (60 ft.) **ADA**
- #207 vinyl 3/8" butt stair nosing**
- 3/8" butt stair nosing for carpet and Rop-Cord™ tile
 - Installation Radius: 10 ft., color Black only
 - 5 12-ft. secs. per ctn. (60 ft.) **ADA**

cove caps

- #158 cove cap (square) 1/4"**
- Cap for coved carpets and wall paneling
 - Installation Radius: 1 ft.
 - 40 12-ft. secs. per ctn. (480 ft.)
- #161 carpet cove trim**
- For coved carpet; undercut 3/16" (flexible)
 - Installation Radius: 10 ft.
 - 20 12-ft. secs. per ctn. (240 ft.)
- #165 cove cap (square) 1/8"**
- Cap for coved sheet vinyl; undercut 1/8"
 - Installation Radius: 1 ft.
 - 50 12-ft. secs. per ctn. (600 ft.)
- #193 vinyl flash cap height: 4"**
- Vinyl fillet strip and cove cap in one product; use for vinyl sheet or carpet up to 1/4" thick
 - Installation Radius: 4 inches
 - 20 5-ft. secs. per ctn. (100 ft.)

fillets & tub moldings

- #167 fillet strip**
- Superb backing for flashing up the wall color may vary due to 100% recycled content; angle 45°
 - Installation Radius: 1 ft.
 - 5 20-ft. coils per ctn. (100 ft.) **ADA**
- #188 cove stick**
- Superb backing for flashing up the wall color Neutral only; angle 45°
 - Installation Radius: 2 ft.
 - 100 5-ft. pcs. per ctn. (500 ft.)
- #189 fillet molding**
- Superb backing for flashing up the wall color Snow only; angle 45°
 - Installation Radius: 1 ft.
 - 25 5-ft. pcs. per ctn. (125 ft.)
- #190 & #191 tub molding**
- High-gloss finish, self-stick backing, 1" or 1-1/2" cove for tubs, counters, shelves; colors Snow and Almond only; angle 45°
 - Installation Radius: 1 ft.
 - 24 5-ft. pcs. per ctn. (120 ft.)

reducers

- #156 glue-down reducer 5/16"**
- 5/16" butting gauge undercut; long flange, smooth taper
 - Installation Radius: 18 ft.
 - 5 12-ft. secs. per ctn. (60 ft.) **ADA**
- #160 glue-down reducer 3/16"**
- Undercut 3/16"; flange and transition combined; smooth transition
 - Installation Radius: 10 ft.
 - 20 12-ft. secs. per ctn. (240 ft.) **ADA**
- #168 underslung reducer**
- Binder-bar edging for resilient flooring; undercut .115" for use with 1/16" to 1/8" material
 - Installation Radius: 3 ft.
 - 2 35-ft. coils per ctn. (70 ft.) **ADA**
- #169 glue-down reducer 1/4"**
- 1/4" undercut; long flange, smooth taper
 - Installation Radius: 10 ft.
 - 5 12-ft. secs. per tube (60 ft.) **ADA**
- #172 tile reducer 1/8"**
- Beveled edge for resilient flooring; 1/8" butting edge
 - Installation Radius: 18 ft.
 - 50 3-ft. secs. per ctn. (150 ft.)

reducers (cont.)

- #174 glue-down reducer 1/4"**
- Undercut 1/4" with 2" transition
 - Installation Radius: 11 ft.
 - 10 12-ft. secs. per ctn. (120 ft.) **ADA**
- #176 multi-use reducer 1/2"**
- For carpet, ceramic tile or wood floors
 - Installation Radius: 6 ft.
 - 10 12-ft. secs. per ctn. (120 ft.) **ADA**
- #196 carpet reducer 3/8"**
- Designed especially for 3/8" carpet
 - Installation Radius: 10 ft.
 - 10 12-ft. secs. per ctn. (120 ft.) **ADA**

wall accessories

- #350 quarter round**
- Designed to outperform wood to complement a tread, tile or base job
 - 10 12-ft. pieces or 40' coil

corner guard

- #166 corner guard 1/8" length: 54" (standard)**
- 1-1/2" returns; standard length 54" (special order to 9 ft., minimum quantities required)
 - Installation Radius: Not Applicable.
 - 12 54" pcs. per ctn. (54 ft. on standard orders)

adapters / transitions

- #152 snap-down divider**
- 1-13/32" wide removable section for joining carpets
 - Installation Radius: 6 ft.
 - 20 12-ft. secs. per ctn. (240 ft.) **ADA**
- #154 snap-down edging**
- 1-9/64" wide removable section for joining carpet to tile
 - Installation Radius: 6 ft.
 - 20 12-ft. secs. per ctn. (240 ft.) **ADA**

adapters / transitions

- #159 tile carpet joiner**
- Provides smooth carpet/ tile transition
 - Installation Radius: 10 ft.
 - 20 12-ft. secs. per tube (240 ft.) **ADA**
- #175 snap-down edging**
- 1-1/4" wide removable section for joining tile to wood
 - Installation Radius: 6 ft.
 - 20 12-ft. secs. per ctn. (240 ft.) **ADA**
- #177 tile carpet joiner**
- Joins 1/4" carpet to 1/8" tile
 - Installation Radius: 10 ft.
 - 5 12-ft. secs. per ctn. (60 ft.) **ADA**
- #179 snap-down super edge**
- 1-7/8" wide removable section for joining carpet to wood/ceramic
 - Installation Radius: 6 ft.
 - 5 12-ft. secs. per ctn. (60 ft.) **ADA**
- #182 ceramic/wood carpet transition 3/8"**
- Molding for joining 5/16" carpet to 3/8" ceramic/wood flooring
 - Installation Radius: 12 ft.
 - 10 12-ft. secs. per tube (120 ft.) **ADA**

- #195 feature strip**
- Designed to transition between 1/8" tiles or add interest to floor design
 - Installation Radius: 3 ft.
 - 50 3-ft. pcs. per ctn. (150 ft.) **ADA**

tracks

- #155 single flange track**
- Works with #152, #154, #175 and #179; color Black only
 - Installation Radius: Zero
 - 10 12-ft. pcs. per ctn. (120 ft.)
- #178 flexi-track single flange track**
- Works with #152, #154, #175 and #179; flexible, contours easily; color Black only
 - Installation Radius: 6 ft.
 - 20 12-ft. pcs. per ctn. (240 ft.)