
## DATA SHEET BALI® 2" ALUMINUM SCHOOL BLINDS

## **Product Features**



- SureClose<sup>™</sup> headrail system
- · Cord tilt standard
- · Anti-static performance to repel dust
- Low HAP, low VOC paint process
- · Enclosed bottomrail
- 1½" reinforced vinyl tapes
- · Heavy duty lift and tilt cords
- GREENGUARD Gold Certified
- Limited Lifetime Warranty

## **Product Specifications**

**SureClose** Headrail shall be  $1^5/8$ " high x  $2^1/4$ " wide x .022" thick U-shaped steel with  $^1/8$ " light-blocking lip on the bottom center line. The steel finishing process includes phosphate treatment for corrosion resistance, a chromefree sealer, a low HAP urethane primer, and a topcoat of low HAP, polyester-baked enamel.

**Cord Tilter** shall be a snap-in component incorporating a worm and pulley of low-friction thermoplastic and a nylon gear. Standard tilt cords shall measure 2.2mm diameter.

**Tilt rod** shall be electro-zinc coated solid steel measuring ½" square.

**Cord lock** shall be metal of a snap-in design incorporating a floating, shaft-type locking pin and shall incorporate a crash-proof safety feature that will lock blind automatically upon release of cord.

**Drums** shall be made of high strength thermoplastic, which securely anchors vinyl tapes.

**Installation brackets** shall be made of phosphate-treated steel with a urethane primer and polyester-baked enamel finish to match headrail. The design shall incorporate a hinged front cover.

**Lift cord** shall be made of braided polyester measuring 2.2mm in diameter.

**Vinyl ladder tape** shall be  $1\frac{1}{2}$ " wide reinforced vinyl. Standard ladder spacing shall be 42mm.

**Slats** shall be 5000 Series cold-rolled aluminum containing the maximum allowable recycled content to produce a high strength and corrosion-resistant, flexible product. Slats shall be nominally 2" wide x .008" thick and processed to provide a smooth, hard, less porous surface with anti-static performance to repel dust. Slats shall be treated with a topcoat of polyester-baked enamel.

**Bottomrail** shall be C-shaped, 9/16" high x 2" wide x 0.40" thick anodized aluminum. It is fully enclosed with a dust cover slat and finished with a polyester-baked enamel to match headrail.

## Options:

- · Wand tilt
- · Ring tilt
- · Ring pull
- Cut-outs
- · Deluxe valance

