
ECHELON P

ALUMINUM ORNAMENTAL FENCING


Echelon Plus Rails: 1-7/16" W x 1-1/4" H (.090" side walls / .060" top wall) Echelon Plus Pickets: 3/4" x 3/4" x .045"

QUALITY • SECURITY • STRENGTH • APPEARANCE • MAINTENANCE-FREE



TYPICAL PANEL DRAWING

(Classic Style shown; Majestic, Genesis, Warrior & Conqueror also available)



See Echelon Plus Specification for Guidelines on Post Spacing by Bracket Type




1-888-333-3422 FAX: 1-877-926-3747

			IAND			
	· · · · · · · · · · · · · · · · · · ·	STANDARD EXT	FENDED PICKET ANI			LS
		Standard 	3-Rail Flush Bottom	4-Rail Stand	ard 	4-Rail Flush Bottom
Classic™					<u> </u>	
Majestic™						
Genesis™	##					
Warrior™	++++++					
Conquero	ППП					
Rail Quantity & Location	Nominal Panel Height	Item Number	Catalog Price (Black)	Catalog Price (Bronze/White)	Panel Weight	Supplemental Information
	3'	A <u>*</u> <u>X</u> 3368			21	Non-Stock
4 D "	3½'	A <u>*</u> <u>X</u> 3428			23	Non-Stock
3-Rail Standard	4'	A <u>*</u> <u>X</u> 3488			24	Stock-Black-All Styles
	5'	A <u>*</u> <u>X</u> 3608			27	Stock-Black-All Styles
	6'	A <u>*</u> <u>X</u> 3728			30	Non-Stock
	3'	A <u>*</u> <u>X</u> 3368F			21	Non-Stock
3-Rail	3½'	A <u>*</u> <u>X</u> 3428F			23	Non-Stock
Flush Bottom	4'	A <u>*</u> <u>X</u> 3488F			24	Non-Stock
	5'	A <u>*</u> <u>X</u> 3608F			27	Non-Stock
	6'	A <u>*</u> <u>X</u> 3728F			30	Non-Stock
4-Rail	4'	A <u>*</u> <u>X</u> 4488			29	Non-Stock
Standard	5'	A * X 4608			32	Non-Stock
	6'	A <u>*</u> <u>X</u> 4728			34	Stock-Black-Classic/Majestic
4-Rail	4'	A <u>*</u> <u>X</u> 4488F			29	Non-Stock
Flush Bottom	5'	A <u>*</u> <u>X</u> 4608F			32	Non-Stock
	6'	A <u>*</u> <u>X</u> 4728F			34	Non-Stock
			OLOR SELECTION: B=BLACK / YLE SELECTION: C=CLASSIC/			RRIOR/R=CONQUEROR



1-888-333-3422 FAX: 1-877-926-3747





X=COLOR SELECTION: B=BLACK /N=BRONZE/W=WHITE

*=STYLE SELECTION: C=CLASSIC/M=MAJESTIC/G=GENESIS/W=WARRIOR


POOL PANELS

Monarch™ 2-Rail










Rail Quantity & Location Page 1	Nominal Panel Height	Item Number	Catalog Price (Black)	Catalog Price (Bronze/White)	Panel Weight	Supplemental Information
Monarch™2-Rail	4'	AM <u>X</u> 2486			16	Stock-Black/Bronze
Majestic™3-Rail	41/2'	AM <u>X</u> 3548			25	Stock-Black/Bronze
Majestic™w/Rings	41/2'	AM <u>X</u> 3548R			30	Non-Stock
Conqueror [™] 3-Rail	41/2'	AR <u>X</u> 3548			25	Stock-Black/Bronze

X=COLOR SELECTION: B=BLACK /N=BRONZE/W=WHITE

SEE NOTICE ON CHECKING FOR POOL CODE COMPLIANCE

PUPPY PANELS



Rail Quantity & Location	Nominal Panel Height	Item Number	Catalog Price (Black)	Catalog Price (Bronze/White)	Panel Weight	Supplemental Information
3-Rail Puppy	4'	A <u>*</u> <u>X</u> 3488D			35	Non-Stock
5-Kan Fuppy	5'	A <u>*</u> <u>X</u> 3608D			38	Non-Stock
4-Rail Puppy	6'	A <u>*</u> <u>X</u> 4728D			45	Non-Stock

X=COLOR SELECTION: B=BLACK /N=BRONZE/W=WHITE

*STYLE SELECTION: C=CLASSIC/M=MAJESTIC/G=GENESIS



POOL CODE NOTICE

1-888-333-3422 FAX: 1-877-926-3747

The aluminum ornamental pool panels meet the 2003 International Building Code (IBC) for pool enclosures.

Pool enclosure codes vary widely and are <u>not</u> uniform nationally. Ameristar® cannot warrant nor guarantee its aluminum fencing to meet the many different code requirements for pool fencing, gates and particularly gate hardware (latches and hinges). Please make sure the hardware you purchase meets local pool codes. Ameristar® does not guarantee its gate hardware to meet local pool codes.

The applicable local codes must always be checked for compliance before ordering or installing any Ameristar® ornamental fence for pool use.

ECHELON PLUS®



WIND LOADING

1-888-333-3422 FAX: 1-877-926-3747

Height (FT)	Rail Length	Post Size	Echelon Plus Wind Load Capacity Factor (PSF)	Typical Wind Load Capacity Factor (MPH)
4'	6	2-1/2" x 2-1/2" Tube w/reinforced web	85	215
'	8	2-1/2" x 2-1/2" Tube w/reinforced web	68	193
5'	8	2-1/2" x 2-1/2" Tube w/reinforced web	47	159
6'	8	2-1/2" x 2-1/2" Tube w/reinforced web	42	151

Note: MPH values shown are provided for information only. They are calculated according to ANSI/ASCE 7-05, "American Society for Civil Engineers Minimum Design Loads for Buildings and Other Structures", Exposure Category C (open terrain with scattered obstructions having lengths generally less than 30 feet), based on post setting in 36" deep concrete footer in soil assumed to be of mid-range strength and compaction. Since specific project conditions such as jurisdictional building codes, elevation of installation, post base/footer design, soil strength, etc., may change from project to project, a structural engineering evaluation, unique to applicable requirements and conditions, should be performed. Consult with your Ameristar Service Representative for an estimate on Engineering Analysis and P.E. Certification.

1-888-333-3422 FAX: 1-877-926-3747

ECHELON PLUS®



BRACKETS AND PANEL ACCESSORIES

ITEM DESCRIPTION	PART NUMBI	ER/COLOR							
112.12 22.00.111 1101	BLACK WHIT	E BRONZE	PRICE	SIZE	BAG QTY	BOX QTY	, ,,	T A	BOX WT
Echelon Plus	ABB3 ABW	3 ABN3		2-1/2"	2	100	.4	1	21
Line Boulevard Bracket	Used as alum These include MUST BE P	e fasteners.				ost to join tw	o adjacent p	anels in lii	ie.
Echelon Plus	ABB4 ABW	4 ABN4		2-1/2'	, 2	80	.34	4	8.5
End Boulevard Bracket	Used as alum These include MUST BE P	e fasteners.				nd post to jo	in it to the l	ast panel in	ı a line.
Echelon Plus	ABB5 ABW	5 ABN5		2-1/2"	2	100	.41	1	10
Bracket	Used as alum angles. These	include fast	eners.			ost to Join 2	paneis meeti	ng at right	
Echelon Plus	ABB2 ABW	2 ABN2		1-1/2"	, 2	90	.1	4	7
	Enables pane MUST BE P * Note: Wh be taken to e This may rec	URCHASE en using sw nsure the sp	D IN BAC ivel brack pacing bet	G QUA kets on a ween p	NTITY. either or bot ost and adjo	h ends of a	panel instal	llation, car plicable co	re must des.
Echelon Plus	ABB1 ABW	1 ABN1		1-1/2"	2	240		.1	17
Flat Mount Bracket FOR WALLS, WOOD POSTS, ETC.	Can be used #14 x 3/4" se MUST BE P	elf-drilling so	rews and	aluminu	ım drive rive		" carriage bo	olt, 1/4" fla	nge nut,
Retaining Rod	H532P			1/8" x 7	71-3/8" 1		25	N/A	
0	H533P			1/8" x 9	01-3/4" 1	1 .32 .3	32	N/A	
	Galvanized o	ver steel; 1/8	3" in diam	eter.					
Grommets		PART I	NUMBEI	R / CO	LOR				
\sim	BLACK.	PRICE	WHIT	E_	BRONZE	PRICE	SIZE	BAG QTY	BAG WT
	BG7520P		WG7520)P	NG7520		3/4"	20	.25
	MUST BE P	URCHASE	D IN BAC	G QUA	NTITY.				

N/S = Non-Stock



1-888-333-3422 FAX: 1-877-926-3747

ADORNMENTS

			PART	NUMBER /	COLOR		SIZE	BOX	WT
ITEM DI	ESCRIPTION	BLACK	PRICE	WHITE	BRONZE	PRICE	SIZE	QTY	EA
Picket Plug		PB7519P (N/S)		PW7519P (N/S)	N/A		3/4" SQ	19/Bag	.05
				ckets. Plugs inclu E D IN BAG Q U			•		
Quad Flares	Ŷ	AB920		AW920 (N/S)	AN920 (N/S)		3/4" SQ		.12
(Aluminum)		Fits atop 3/4" adds the popu	The four sided flare design						
Triads	\wedge	AB900		AW900	AN900 (N/S)		3/4" SQ		.12
(Aluminum)		Fits atop 3/4" the strong loo		ckets (press-fit). bed spear.	Heavy-duty ca	ast aluminum.	Three distin	nct tips re	flect
Royalty	Å	AB921		AW921	AN921 (N/S)		3/4" SQ		.13
		Fits atop 3/4"	square pic	ekets (press-fit). I	Die cast alumii	num.			
Rings	Þ	AB901		AW901 (N/S)	AN901 (N/S)		4"		.72
(Aluminum)				inched slots unde when rods are in				ecial ring	rail.
Butterfly Scroll	90	HB506		HW506 (N/S)	HN506 (N/S)		4 X 3-1/2"		.2
(Aluminum)		Fastens onto	face of 3/4	l" square pickets.	Self drilling t	ek screws inc	luded.		
Florentine Scroll	%	HB507		HW507 (N/S)	HN507 (N/S)		7 X 14.25"		.9
(Aluminum)		Fastens onto	face of 3/4	4" square pickets	. Self drilling	tek screws inc	eluded.		

N/S = Non-Stock

FASTENERS

ITEM DESCRIPTION	PAR	T NUMBER/COL	OR	DEALER	LENGTH	BOX	WT
	BLACK	WHITE	BRONZE	PRICE		QTY	EA
Carriage Bolts	HB516P	HW516P	HN516P		1/4" x 2"	1	.03
()—mm	HB582P	HW582P	HN582P		5/16" x 3/4"	1	.025
	HB516P is for brack	kets, HB582P is for post b	oase.				
Self-Drilling Screws	HB524P	HW524P	HN524P		#14 x 3/4"	1	.012
(Ams	HB539P	HW539P	HN539P		#10 x 3/4"	1	.007
•	For mounting brack	ets					
Flange Nuts	HB541P	HW541P	HN541P		1/4"	1	.01
9	For mounting brack	ets.					
Hex Nuts	HB546P	HW546P	HN546P		5/16"	1	.011
•	For post base.						
Drive Rivets	HB559P	HW559P	HN559P		1/4" x 9/32"	1	.002
	Used for Echelon Pl	lus flat mount bracket.					
Phillips Screws	H519P				#10 x 5/8"	1	.005
⊕	Sets angle on swive	l bracket.					

EGHELUN PLUS

ECHELON PLUS ORNAMENTAL ALUMINUM FENCE

ECHELON PLUS®



1-888-333-3422 FAX: 1-877-926-3747

	PAR	T NUMBER/C	OLOR	DDICE		BOX	вох
ITEM DESCRIPTION	BLACK		BRONZE	PRICE PER BOX	LENGTH		WT
	ACB348	ACW348 (N/S)	ACN348 (N/S)		46"	114	65
Pointed Picket for Classic and Warrior (Full Length)	ACB360	ACW360 (N/S)			58"	114	83
for Classic and Warrior (I un Ecilgen)	ACB472 (N/S)	ACW472 (N/S)	ACN472 (N/S)		70"	114	99
	MUST BE PUR	CHASED IN FULL E	BOX QUANTITY.				
Flat-Topped Picket	AMB248	AMW248 (N/S)	AMN248 (N/S)		48"	114	65
for Monarch	MUST BE PUR	CHASED IN FULL I	BOX QUANTITY.				
Flat-Topped Picket	AMB348	AMW348 (N/S)	AMN348 (N/S)		46"	114	65
for Majestic	AMB354	AMW354 (N/S)	AMN354 (N/S)		54"	114	69
	AMB360	AMW360 (N/S)	AMN360 (N/S)		58"	114	83
	AMB472	AMW472 (N/S)	AMN472 (N/S)		70"	114	99
	MUST BE PUR	CHASED IN FULL E	BOX QUANTITY.				
B. (IB. I (AWB348	AWW348 (N/S)	AWN348 (N/	S)	43"	114	65
Pointed Picket for Warrior (Short)	AWB360	AWW360 (N/S)	AWN360 (N/	S)	55"	114	83
(33314)	AWB472 (N/S)	AWW472 (N/S)	AWN472 (N/	S)	67"	114	99
	A C D 2 4 0	L CW240 Q1/5)	A CN240 QUIC		46"	11.4	(5
Flat Topped Picket	AGB348	AGW348 (N/S)	AGN348 (N/S			114	65
for Genesis	AGB360	AGW360 (N/S)	AGN360 (N/S		58"	114	83
	` ,	AGW472 (N/S) CHASED IN FULL F	AGN472 (N/S	5)	70"	114	99
Flat Topped Picket	ALRB348 (N/S	S) ALRW348 (N/S	S) ALRN348 (N	N/S)	46"	114	65
for Conqueror	ALRB354 (N/S	S) ALRW354 (N/S	S) ALRN354 (N	N/S)	54"	114	69
	ALRB360 (N/S	S) ALRW360 (N/S	S) ALRN360 (N	J/S)	58"	114	83
	ALRB472 (N/S	S) ALRW472 (N/S	S) ALRN472 (N	V/S)	70"	114	99
	MUST BE PURC	CHASED IN FULL B	OX QUANTITY.				
Pointed Picket	ARB348 (N/S)	ARW348 (N/S)	ARN348 (N/	(S)	43"	114	61
for Conqueror	ARB354 (N/S)	ARW354 (N/S)	ARN354 (N/		51"	114	77
•	ARB360 (N/S)	ARW360 (N/S)	ARN360 (N/	S)	55"	114	83
	ARB472 (N/S)	ARW472 (N/S)	ARN472 (N/	S)	67"	114	99
	. ()	\ /	`	/			

N/S = Non-Stock



1-888-333-3422 FAX: 1-877-926-3747

BULK RAILS

	PAR	T NUMBER/C	OLOR	PRICE		BOX	BOX
ITEM DESCRIPTION	BLACK	WHITE	BRONZE	PER BOX	LENGTH	QTY	WT
Classic™ 8' Rail - Through-Punched	ACBR18R	ACWR18R (N/S)	ACNR18R		91-3/4"	18	62
		n Classic [™] , Genesis [™] , a [™] fence panels. MUST				rails on Ma	ijestic™
Majestic™ 8' Rail - Flush Top		AMWR18R (N/S)			91-3/4"	18	62
	For all Top Ra QUANTITY.	ails on Majestic™ and 0	Conqueror™ fence pa	nnels. MUST BE	Z PURCHASED	IN FULI	. BOX
8' Ring Rail - Through-Punched	ARBR18R	ARWR18R (N/S)	ARNR18R (N/S		91-3/4"	18	62
	A CIDDA CID	A CWID LCD QUO	ACMB10		72 1/14"	10	40
Classic [™] 6' Rail - Through-Punched		ACWR16R (N/S)	ACNR16R		73-1/16"	18	49
		Classic™, Genesis™, an Conqueror™ fence pand					narch™,
Majestic™ 6' Rail - Flush Top	AMBR16R				73-1/16"	18	49
Angeste o Auto Trust Top	For all Top Ra BOX QUANT	ils on Monarch ^{™,} Majes ITY.	tic [™] and Conqueror ⁿ	fence panels. M	UST BE PURC	HASED I	N FULL
6' Ring Rail - Through-Punched	ARBR16R (N/S) ARWR16R (N	/S) ARNR16R (I	N/S)	73-1/16"	18	49
S S S S S S S S S S S S S S S S S S S	Used as second	rail for ring panels. M	UST BE PURCHA	SED IN FULL BO	OX QUANTITY		

 $Rails = 540 \ Pallet \ Qty. \quad N/S = Non-Stock$

CUSTOM FINISHES

ITEM DESCRIPTION	BLAC	CK		COLOR		BOX	WT.
	PART NUMBER	PRICE EA.	BRONZE	WHITE	PRICE	QTY	EA.
Paint Pen	PB100		PN100	PW100		12	.5
Spray Paint	FB100		FN100	FW100		12	1.1



1-888-333-3422 FAX: 1-877-926-3747

ORNAMENTAL ALUMINUM SQUARE POST

 $\underline{\mathbf{X}}$ = COLOR SELECTION

B = BLACK N = BRONZE W = WHITE

Post Diameter	Ga. / Wall Thickness	Post Length	Item Number	Catalog Price (Black)	Catalog Price (Color)	Post Weight
		5'-9"	AP <u>X</u> 25069			5
		6'-3"	AP <u>X</u> 25075			6
2-1/2" SQ.		6'-9"	AP <u>X</u> 25081			6
(ALUMINUM)		7'-9"	AP <u>X</u> 25093			7
		8'-9"	AP <u>X</u> 25105			8
		7'	AP <u>X</u> 30084			12
		8'	AP <u>X</u> 30096			14
3" SQ. (ALUMINUM)	0.125	9'	AP <u>X</u> 30108			15
(ALUMINUM)	0.125	10'	AP <u>X</u> 30120			17
		7'	AP <u>X</u> 40084			31
4" SO		8'	AP <u>X</u> 40096			36
4" SQ. (ALUMINUM)	0.250	9'	AP <u>X</u> 40108			40
		10'	AP <u>X</u> 40120			43

ORNAMENTAL STEEL SQUARE POST

X = COLOR SELECTION

B = BLACK N = BRONZE W = WHITE

Post Diameter	Ga. / Wall Thickness	Post Length	Item Number	Catalog Price (Black)	Catalog Price (Color)	Post Weight
		5'	P <u>X</u> 30060			20
		6'	P <u>X</u> 30072			24
3" SQ.		7'	P <u>X</u> 30084			30
(STEEL)		8'	P <u>X</u> 30096			34
		9'	P <u>X</u> 30108			39
		10'	P <u>X</u> 30120			43
		6'	P <u>X</u> 40072			39
		7'	P <u>X</u> 40084			47
4" SQ.	11 GA.	8'	P <u>X</u> 40096			54
(STEEL)	(STEEL) (INDUSTRIAL)	9'	P <u>X</u> 40108			61
		10'	P <u>X</u> 40120			67





1-888-333-3422 FAX: 1-877-926-3747

X	= COLOR SELECTION
_	- COLOR SELECTION

B = BLACK N = BRONZE W = WHITE

Post Size	Base Size	Drill Holes	Item Number	Catalog Price (Black)	Catalog Price (Color)	Base Weight
Fits 2-1/2" SQ. Aluminum Post	5" X 5"	9/16"	AP <u>X</u> B25			2

POST CAPS

X = COLOR SELECTION

B = BLACK N = BRONZE W = WHITE

Cap Type	Cap Style	Size	Item Number	Catalog Price (Black)	Catalog Price (Color)	Cap Weight
ALUMINUM		2-1/2" SQ.	A <u>X</u> 600P			0.2
	STANDARD FLAT CAP	3" SQ.	A <u>X</u> 700P			0.3
		4" SQ.	A <u>X</u> 800P			0.4
ALUMINUM		2-1/2" SQ.	A <u>X</u> 513			0.7
		3" SQ.	A <u>X</u> 516			0.8
	BALL CAP	4" SQ.	A <u>X</u> 517			2

AMERISTAR FENCE PRODUCTS®

${\bf ECHELON\ PLUS}^{\circledast} - {\bf Aluminum\ Ornamental\ Fence\ System-Internally\ Secured}$ **Construction Specification - SECTION 32 31 19**

PART 1 - GENERAL

1.01 WORK INCLUDED

The contractor shall provide all labor, materials and all necessary items for the installation of the Echelon Plus® ornamental aluminum fence system defined herein at (specify project site).

1.02 RELATED WORK

Section _ _ - Earthwork Section _ _ - Concrete

1.03 SYSTEM DESCRIPTION

The manufacturer shall supply a total ornamental aluminum fencing system of the Ameristar Echelon Plus® (specify Classic™, Majestic™, Genesis™, Warrior™, Conqueror™, Monarch Pool™, Majestic Pool™, Conqueror Pool™, Classic Puppy[™], Majestic Puppy[™], or Genesis Puppy[™]) design. The system shall include all components (i.e., pickets, posts, rails, gates and hardware) required. 1.04 QUALITY ASSURANCE

The contractor shall provide laborers and supervisors who are thoroughly familiar with the type of construction involved and the materials specified. 1.05 REFERENCES

- ASTM B117 Practice for Operating Salt-Spray (Fog) Apparatus.
- ASTM B221 Standard Specification for Aluminum and Aluminum-Alloy Extruded Bars, Rods, Wire, Profiles and Tubes.
- ASTM D523 Test Method for Specular Gloss.
- ASTM D822 Practice for Conducting Tests on Paint and Related Coatings and Materials using Filtered Open-Flame Carbon-Arc Light and Water Exposure Apparatus.
- ASTM D1654 Test Method for Evaluation of Painted or Coated Specimens Subjected to Corrosive Environments.
- ASTM D2244 Test Method for Calculation of Color Differences from Instrumentally Measured Color Coordinates.
- ASTM D2794 Test Method for Resistance of Organic Coatings to the Effects of Rapid Deformation (Impact).
- ASTM D3359 Test Method for Measuring Adhesion by Tape Test. 1.06 SUBMITTAL

The manufacturer's submittal package shall be submitted prior to installation to confirm compliance with all requirements for materials specified in this

1.07 PRODUCT HANDLING AND STORAGE

Upon receipt at the job site, all materials shall be checked to ensure that no damages occurred during shipping or handling. Materials shall be stored in such a manner to ensure proper ventilation and drainage and to protect against damage, weather, vandalism and theft.

PART 2 - MATERIALS

2.01 MANUFACTURER

The ornamental fence system shall conform to Ameristar's Echelon Plus aluminum ornamental fencing, (specify Classic, Majestic, Genesis, Warrior, Conqueror, Monarch Pool, Majestic Pool, Conqueror Pool, Classic Puppy, Majestic Puppy, or Genesis Puppy) (specify 2-rail, 3-rail, 4-rail, 3-rail with rings, or 4-rail with rings) style manufactured by Ameristar Fence Products, Inc. in Tulsa, Oklahoma,

2.02 MATERIAL

A. Aluminum material for fence framework (i.e., tubular pickets, rails and posts) shall conform to the requirements of ASTM B221. The aluminum extrusions for posts and rails shall be Alloy and Temper Designation 6005-T52. The aluminum extrusions for pickets shall be Alloy and Temper Designation

B. Pickets shall be 3/4" square x .045" thick. Horizontal rails shall be 1-1/4" x 1-7/16" Forerunner™ channel with .060" thick top & internal web wall, and .090" thick side walls and shall be punched to allow picket to pass through the top of the rail. The Forerunner rail shall be constructed with an internal web insert providing a raceway for the pickets to be retained with a 1/8" retaining rod. The number of rails shall vary with the style, height and strength as determined by manufacturer. Fence posts and gate posts shall meet the minimum size requirements of Table 1.

C. Accessories: Aluminum castings shall be used for all post caps, scrolls, finials, and other miscellaneous hardware. Hinges and latches shall be fabricated from aluminum, steel or composite materials.

ECHELON°

A. Pickets, rails and posts shall be pre-cut to specified lengths. Fore-Runner rails shall be pre-punched to accept pickets. Grommets shall be inserted into the pre-punched holes in the rails and pickets shall be inserted through the grommets so that pre-drilled picket holes align with the internal upper raceway of the ForeRunner rails (Note: This can best be accomplished by using an alignment template). Retaining rods shall be inserted into each ForeRunner rail so that they pass through the pre-drilled holes in each picket, thus completing the panel assembly.

B. The manufactured framework shall be subjected to the Ameristar thermal stratification coating process (high-temperature, in-line, multi-stage, and multi-layer) including, as a minimum, a six-stage pretreatment/wash and an electrostatic spray application of a polyester finish. The topcoat shall be a "no-mar" TGIC polyester powder coat finish with a minimum thickness of 2 mils (0.0508mm). The color shall be (specify Black, Bronze, or White). The stratification-coated framework shall be capable of meeting the performance requirements for each quality characteristic shown in Table 2.

C. Finish: All fence components shall be subject to a six-stage pretreatment/wash followed by an electrostatic spray application of a "no-mar" TGIC polyester powder coat finish with a minimum thickness of 2-4 mils. The color shall be (specify black, bronze or white).

D. Completed panels shall be capable of supporting a 200 lb. load (applied at midspan) without permanent deformation. Panels without rings shall be biasable to a 12.5% change in grade.

E. Swing gates shall be fabricated using 1-1/4" x 1-7/16" Forerunner rail, 1.75" sq. x .125" gate ends, and 3/4" sq. x .080 pickets. Gates that exceed 6' in width will have a 1.75" sq. x .125" intermediate upright. All rail and upright intersections shall be joined by welding. All picket and rail intersections shall also be joined by welding.

PART 3 - EXECUTION

3.01 PREPARATION

All new installation shall be laid out by the contractor in accordance with the construction plans.

3.02 FENCE INSTALLATION

Fence post shall be spaced according to Table 3, plus or minus 1/2". For installations that must be raked to follow sloping grades, the post spacing dimension must be measured along the grade. Fence panels shall be attached to posts with brackets supplied by the manufacturer. Posts shall be set in concrete footers 33" depth recommended (Note: In some cases, local restrictions of freezing weather conditions may require a greater depth). The "Earthwork" and "Concrete" sections of this specification shall govern material requirements for the concrete footer. Posts setting by other methods such as plated posts or grouted core-drilled footers are permissible only if shown by engineering analysis to be sufficient in strength for the intended application.

3.03 FENCE INSTALLATION MAINTENANCE

When cutting/drilling rails or posts adhere to the following steps to seal the exposed surfaces; 1) Remove all metal shavings from cut area. 2) Apply custom finish paint matching fence color. Failure to seal exposed surfaces per steps 1 & 2 above will negate warranty. Ameristar spray cans or paint pens shall be used to finish exposed surfaces; it is recommended that paint pens be used to prevent overspray. Use of non-Ameristar parts or components will negate the manufactures' warranty.

3.04 GATE INSTALLATION

Gate posts shall be spaced according to the manufacturers' gate drawings, dependent on standard out-to-out gate leaf dimensions and gate hardware selected. Type and quantity of gate hinges shall be based on the application; weight, height, and number of gate cycles. The manufacturers' gate drawings shall identify the necessary gate hardware required for the application. Gate hardware shall be provided by the manufacture of the gate and shall be installed per manufacturer's recommendations.

3 05 CLEANING

The contractor shall clean the jobsite of excess materials; post-hole excavations shall be scattered uniformly away from posts.

AMERISTAR FENCE PRODUCTS® ECHELON PLUS® - Aluminum Ornamental Fence System – Internally Secured Construction Specification - SECTION 32 31 19

Table 1 – Minimum Sizes for Echelon Plus Posts									
Fence Posts	Panel Height								
2-1/2" x 2-1/2" x .060" w/ reinforced web	Up to 6' Height								
Gate Leaf	Gate Height								
Gate Lear	Up to & Including 4'	Over 4' Up to & Including 5'	Over 5' Up to & Including 6'						
Up to 4'	2 1/2" x 2-1/2" x .060" Alum.	3" x 3" x .120" Alum.	4" x 4" x .250" Alum. or 3" x 3" x 12ga. Steel						
4'1" to 6' 3" x 3" x .120" Alum.		4" x 4" x .250" Alum. or 3" x 3" x 12ga. Steel	3" x 3" x 12ga. Steel						
6'1" to 8' 4" x 4" x .250" Alum. or 3" x 3" x 12ga. Steel		4" x 4" x 11ga. Steel	4" x 4" x 11ga. Steel						

Table 2 – Coating Performance Requirements							
Quality Characteristics ASTM Test Method Performance Requirements							
Adhesion	D3359 – Method B	Adhesion (Retention of Coating) over 90% of test area (Tape and knife test).					
Corrosion Resistance	B117 & D1654	Corrosion Resistance over 1000 hours (Scribed per D1654; failure mode is accumulation of 1/8" coating loss from scribe or medium #8 blisters).					
Impact Resistance	D2794	Impact Resistance over 60 inch lb. (Forward impact using 0.625" ball).					
Weathering Resistance	D822, D2244, D523 (60° Method)	Weathering Resistance over 1,000 hours (Failure mode is 60% loss of gloss or color variance of more than 3 delta-E color units).					

	Table	3 – Echelon Plus – Po	st Spacing By Bracke	et Type					
Span 8' Nominal (91-3/4" Rail)									
Post Size	2-1/2"	2-1/2"	3"	2-1/2"	3"				
Bracket Type	Echelon Plus Line Boulevard (ABB3)	Echelo Swir (AB	vel*	Flat M	on Plus Mount BB1)				
Post Settings ± 1/2" O.C.	95"	*95"	*95-1/2"	95"	95-1/2"				
Span	6' Nominal (73-1/16"	Rail)							
Post Size	2-1/2"	2-1/2"	2-1/2" 3"		3"				
Bracket Type	Echelon Plus Line Boulevard (ABB3)	Echelo Swi (AB	vel*	Echelon Plus Flat Mount (ABB1)					
Post Settings ± 1/2" O.C.	76-1/4"	*76-1/4"	*76-3/4"	76-1/4"	76-3/4"				

*Note: When using ABB2 swivel brackets on either or both ends of a panel installation, care must be taken to ensure the spacing between post and adjoining pickets meets applicable codes. This will require trimming one or both ends of the panel.

ECHELON PLUS® ALUMINUM ORNAMENTAL FENCE LIMITED LIFETIME WARRANTY

Echelon Plus® Ornamental Aluminum Fencing System is manufactured from the highest quality materials by skilled craftsmen to meet the highest standards of workmanship in the industry. Extruded aluminum framework shall be subject to a six stage pretreatment/wash followed by an electrostatic spray application of a "no-mar" TGIC polyester powder coat finish, which provides the protection necessary to withstand adverse environmental conditions.

The powder coated surface on all aluminum framework (i.e., pickets, rails and posts) by AMERISTAR® is guaranteed under normal and proper usage, against cracking, peeling, chipping, blistering or corroding. Normal and proper usage does not include physical damage or abrasion to the protective coating.

Echelon Plus® Ornamental Aluminum Fencing System framework is also guaranteed for the same period of time against defects in workmanship or materials.

Should any ornamental aluminum fence framework manufactured by Ameristar® Fence Products fail in accordance with any of the above conditions, Ameristar® Fence Products warrants to the original purchaser their redemption through replacement or renewal. The decision as to which method of redemption is allowed is solely at the discretion of Ameristar. Notice of failure under the conditions of this warranty shall be sent to Ameristar® Fence Products or it authorized representative, in writing, together with proof of purchase and shall specify the nature of the defect and when it was first observed. If contractor uses non Ameristar parts/components this will negate the warranty. Should the fence be improperly installed, Ameristar® Fence Products shall not be responsible for guaranteed performance or appearance of the material. Neither does this guarantee apply when failure or damage is due to improper use or application, abuse or misuse, vandalism or acts of God. Ameristar® Fence Products reserves the right to inspect the material to determine validity of the claim.

Upon validation of the claim by Ameristar® Fence Products or its authorized representative, redemption by replacement or renewal shall be made by Ameristar® Fence Products. Reimbursement for the costs of removal and installation of materials are not included in the guarantee, nor will Ameristar® Fence Products provide those services.

The above constitutes the complete warranty by the manufacturer. No other agreement, written or implied, is valid. Ameristar® Fence Products does not authorize any other person or agent to make any other express warranties. Ameristar® Fence Products neither assumes nor authorizes any other person or agent to assume any other liability in connection with Echelon Plus® Ornamental Aluminum Fencing System. Some jurisdictions do not allow limitations on how long an implied warranty lasts, nor do they allow an exclusion or limitation of incidental or consequential damages; therefore, the limitations and exclusions noted herein may not apply.

PURCHASE DATE		
DEALER SIGNATURE		
DEALER SIGNATURE	 	



P. O. BOX 581000 TULSA, OKLAHOMA 74158-1000



1-888-333-3422 FAX: 1-877-926-3747

GATE SPECIFICATIONS


STANDARD


ARCHED


.125" Wall Aluminum .250" Wall Aluminum Gate Ends Rails Echelon Plus ForeRunner[™] Rail .250" Wall Aluminum

Pickets .080" Wall Aluminum .125" Wall Aluminum

NOTE: See Sales Policy for additional information pertaining to gate orders. GATE DRAWING DIMENSIONAL FORMAT







W = Outside To Outside Width of Finished Gate Leaf

 $\mathbf{H} = \text{Height}; \ \mathbf{HC} = \text{Hinge Clearance}; \ \mathbf{LC} = \text{Latch Clearance}; \ \mathbf{P_s} = \text{Post Interspace (Single)}; \ \mathbf{P_d} = \text{Post Interspace (Double)}$

HARDWARE KITS & POST INTERSPACES FOR ECHELON PLUS <u>SINGLE SWING</u> ARCHED ALUMINUM GATES								
NOMINAL GAT OPENING	3-1/2'	4'	5'	6'	7'			
W = LEAF WIDT	Н	40"	49-1/2"	58-3/4"	68"	86-3/4"		
LOKKLATCH WITH	HC			3/4"				
TRU-CLOSE HINGE KIT	LC			3/4"				
#TCSGK	P _s	41-1/2"	51"	60-1/4"	69-1/2"	88-1/4"		
TOP PULL LATCH WITH TRU-CLOSE HINGE KIT #TCPGK	HC			3/4"				
	LC			3/4"				
	P _s	41-1/2"	51"	60-1/4"	69-1/2"	88-1/4"		
BOLT-ON	НС	2"						
HARDWARE KITS	LC		2"					
#EGBS25 OR #EGBS3	P _s	44"	53-1/2"	62-3/4"	72"	90-3/4"		
FORK LATCH/	HC			2-3/8"				
BOX HINGE KITS #EGBSX25 OR	LC			2"				
#EGBSX25 OR #EGBSX3	P _s	44-3/8"	53-7/8"	63-1/8"	72-3/8"	91-1/8"		
AMERISTAR LOCK/	HC			2"				
BOLT-ON HINGE KIT #EGBS25A OR	LC			5/8"				
#EGBS3A	P _s	42-5/8"	52-1/8"	61-3/8"	70-5/8"	89-3/8"		
AMERISTAR LOCK/	HC			2-3/8"				
BOX HINGE KIT #EGBSXA	LC			5/8"				
KII #EGBSAA	P _s	43"	52-1/2"	61-3/4"	71"	89-3/4"		
P _d (Gate Post Spacing (Inside-To-Inside) for Double Gate = 2 x HC (Hinge Clearance) + 2 x W (Out-To-Out Gate Width) + LC (Latch Clearance)								

NOMBLE CATE	\equiv					
NOMINAL GATI OPENING	£	3-1/2'	4'	5'	6'	7'
W = LEAF WIDTI	Н	40"	49-1/2"	58-3/4"	68"	86-3/4
LOKKLATCH WITH	HC			3/4"		
TRU-CLOSE HINGE KIT	LC			3/4"		
#TCSGK	P _s	41-1/2"	51"	60-1/4"	69-1/2"	88-1/4
TOP PULL LATCH WITH TRU-CLOSE HINGE KIT	HC			3/4"		
	LC			3/4"		
#TCPGK	P _s	41-1/2"	51"	60-1/4"	69-1/2"	88-1/4
BOLT-ON	нс			2"		
HARDWARE KITS #SGBS25 OR #SGBS3	LC			2"		
#3GD520 GT	P _s	44"	53-1/2"	62-3/4"	72"	90-3/4
AMERISTAR LOCK/	HC			2"		
BOLT-ON HINGE KITS #SGBS25A OR	LC			5/8"		
#SGBS3A	P _s	42-5/8"	52-1/8"	61-3/8"	70-5/8"	89-3/8
AMERISTAR LOCK/	HC			2-3/8"		
BOX HINGE KIT #EGBSX4	LC			5/8"		
,,202	P _s	43"	52-1/2"	61-3/4"	71"	89-3/4

P _s (Gate Post Spacing (Inside-To-Inside) for Single Gate = HC (Hinge Clearance)
+ W (Out-To-Out Gate Width) + LC (Latch Clearance)

HARDWARE KITS & POST INTERSPACES FOR ECHELON PLUS <u>DOUBLE SWING</u> WELDED ALUMINUM GATES								
NOMINAL GAT OPENING	E	7'	8'	10'	12'	14'		
W = LEAF WIDT	H	40"	49-1/2"	58-3/4"	68"	86-3/4"		
BOLT-ON HINGE KIT #AGBD	HC			2-3/8"				
	LC		2"					
	P _s	86"	105"	123-1/2"	142"	179-1/2"		
BOX HINGE KIT	HC	2-3/8"						
WITH UPRIGHT #AGBDX	LC	2"						
	P _s	86-3/4"	105-3/4"	124-1/4"	142-3/4"	180-1/4"		
COMMERCIAL	HC	1"						
HINGE KIT WITH STRONGARM	LC			2"				
#CGBD	P _s	84"	103"	121-1/2"	140"	177-1/2"		
P, (Gate Post Spaci			de) for Singl			learance)		

AMERISTAR FENCE PRODUCTS WELDED GATES

1-888-333-3422 FAX: 1-877-926-3747

	STANDARD EXTENDED PICKET AND FLUSH BOTTOM GATES									
(3-Rail) (1) Flu	(3-Rail) sh Bottom 4-Rail) sh Bottom	Majestic™ Style Ga (3-Rail) (3-R Flush B (4-Rail) (4-Rail) (4-Rail)	ail) ottom	(3-Rail)	(3-Rail) Flush Bottom (4-Rail) Flush Bottom	(4-Rail)	(3-Rail) ush Botto (4-Rail) sh Botto	om (3-Rail) (3-Rail) Flush Bottom (4-Rail) (4-Rail)		
Gate Height / Rail Quantity	Nominal Gate Opening	Actual Gate Leaf Width	N	Item Jumber	Catalog Price (Black)	Catalog Price (Bronze/White)	Gate Weight	Supplemental Information		
	3½'	40"	A <u>*</u>	<u>X</u> 336-42	, ,	,	19	Non-Stock		
3' Tall 3-Rail	4'	49-1/2"	A <u>*</u>	<u>X</u> 336-48			24	Non-Stock		
Standard	5'	58-3/4"	A <u>*</u>	<u>X</u> 336-60			28	Non-Stock		
	6'	68"	A <u>*</u>	<u>X</u> 336-72			31	Non-Stock		
21.75.11	3½'	40"	A <u>*</u>	<u>X</u> 336-42F			19	Non-Stock		
3' Tall 3-Rail	4'	49-1/2"	A <u>*</u>	X 336-48F			24	Non-Stock		
Flush Bottom	5'	58-3/4"	A <u>*</u>	X 336-60F			28	Non-Stock		
	6'	68"	A <u>*</u>	<u>X</u> 336-72F			31	Non-Stock		
21/1 m u	3½'	40"	A <u>*</u>	<u>X</u> 342-42			21	Non-Stock		
3½' Tall 3-Rail	4'	49-1/2"	A <u>*</u>	<u>X</u> 342-48			26	Non-Stock		
Standard	5'	58-3/4"	A <u>*</u>	<u>X</u> 342-60			30	Non-Stock		
	6'	68"	A <u>*</u>	<u>X</u> 342-72			33	Non-Stock		
21/1 T. II	3½'	40"	A <u>*</u>	<u>X</u> 342-42F			21	Non-Stock		
3½' Tall 3-Rail	4'	49-1/2"	A <u>*</u>	<u>X</u> 342-48F			26	Non-Stock		
Flush Bottom	5'	58-3/4"	A <u>*</u>	<u>X</u> 342-60F			30	Non-Stock		
	6'	68"	A <u>*</u>	<u>X</u> 342-72F			33	Non-Stock		
42.75-11	3½'	40"	A <u>*</u>	<u>X</u> 348-42			23	Some styles stocked in black		
4' Tall 3-Rail	4'	49-1/2"	A <u>*</u>	<u>X</u> 348-48			28	for some openings; call for		
Standard	5'	58-3/4"	A <u>*</u>	<u>X</u> 348-60			32	specific information		
	6'	68"	A <u>*</u>	<u>X</u> 348-72			36	specific information		
4' Tall	3½'	40"		<u>X</u> 348-42F			23	Non-Stock		
3-Rail	4'	49-1/2"	A <u>*</u>	<u>X</u> 348-48F			28	Non-Stock		
Flush Bottom	5'	58-3/4"	A <u>*</u>	<u>X</u> 348-60F			32	Non-Stock		
	6'	68"		<u>X</u> 348-72F			36	Non-Stock		
42 Ta II	3½'	40"	A <u>*</u>	<u>X</u> 448-42			25	Non-Stock		
4' Tall 4-Rail	4'	49-1/2"	A <u>*</u>	<u>X</u> 448-48			29	Non-Stock		
Standard	5'	58-3/4"		<u>X</u> 448-60			35	Non-Stock		
	6'	68"		<u>X</u> 448-72			40	Non-Stock		
4' Tall	3½'	40"		<u>X</u> 448-42F			25	Non-Stock		
4 Tan 4-Rail	4'	49-1/2"	A <u>*</u>	<u>X</u> 448-48F			29	Non-Stock		
Flush Bottom	5'	58-3/4"		<u>X</u> 448-60F			35	Non-Stock		
	6'	68"	A <u>*</u>	<u>X</u> 448-72F			40	Non-Stock		

 $*=STYLE \ SELECTION: \ C=CLASSIC/M=MAJESTIC/G=GENESIS/W=WARRIOR/R=CONQUEROR$

Note: Gate hardware is not included. Available gate hardware kits are in the Gate Hardware Section of the Catalog. Effective: 01/01/13



1-888-333-3422 FAX: 1-877-926-3747

	STANDARD EXTENDED PICKET AND FLUSH BOTTOM GATES										
Classic [™] Style Gates		Majestic™ Style Gates (3-Rail) (3-Rail) Flush Bottom		Genesis [™] Style Gates		Warrior™ Style Gates		(3-Rail) (3-Rail)			
(4-Rail)	(4-Rail) sh Bottom	(4-Rail) (4-R. Flush B	ail)	(4-Rail)	Flush Bottom (4-Rail) Flush Bottom	Flush Botton (4-Rail) (4-Rail) Flush Bottom		(4-Rail) (4-Rail)			
Gate Height / Rail Quantity	Nominal Gate Opening	Actual Gate Leaf Width	N	Item Number	Catalog Price (Black)	Catalog Price (Bronze/White)	Gate Weight	Supplemental Information			
51 T- II	3½'	40"	A <u>*</u>	<u>X</u> 360-42			27	Some styles stocked in black			
5' Tall 3-Rail	4'	49-1/2"	A <u>*</u>	<u>X</u> 360-48			32	for some openings; call for			
Standard	5'	58-3/4"		<u>X</u> 360-60			36	specific information			
	6'	68"		<u>X</u> 360-72			41	specific information			
5' Tall	3½'	40"	A <u>*</u>	<u>X</u> 360-42F			27	Non-Stock			
3-Rail	4'	49-1/2"		<u>X</u> 360-48F			32	Non-Stock			
Flush Bottom	5'	58-3/4"	_	<u>X</u> 360-60F			36	Non-Stock			
	6'	68"		X 360-72F			41	Non-Stock			
5' Tall	3½'	40"		<u>X</u> 460-42			29	Non-Stock			
4-Rail	4'	49-1/2"	A <u>*</u> <u>X</u> 460-48				34	Non-Stock			
Standard	5'	58-3/4"	A <u>*</u>	<u>X</u> 460-60			39	Non-Stock			
	6'	68"		<u>X</u> 460-72			45	Non-Stock			
5' Tall	3½'	40"		<u>X</u> 460-42F			29	Non-Stock			
4-Rail	4'	49-1/2"	A <u>*</u> <u>X</u> 460-48F				34	Non-Stock			
Flush Bottom	5'	58-3/4"	A <u>*</u> <u>X</u> 460-60F					Non-Stock			
	6'	68"		X 460-72F			45	Non-Stock			
6' Tall	3½'	40"		<u>X</u> 372-42			31	Non-Stock			
3-Rail	4'	49-1/2"		<u>X</u> 372-48			36	Non-Stock			
Standard	5'	58-3/4"		<u>X</u> 372-60			40	Non-Stock			
	6'	68"		<u>X</u> 372-72			46	Non-Stock			
6' Tall	3½'	40"		<u>X</u> 372-42F			31	Non-Stock			
3-Rail	4'	49-1/2"		<u>X</u> 372-48F			36	Non-Stock			
Flush Bottom	5'	58-3/4"		<u>X</u> 372-60F			40	Non-Stock			
	6'	68"		<u>X</u> 372-72F			46	Non-Stock			
6' Tall	3½'	40"		<u>X</u> 472-42			33	Some styles stocked in black			
4-Rail	4'	49-1/2"		<u>X</u> 472-48			39	for some openings; call for			
Standard	5'	58-3/4"		<u>X</u> 472-60			45	specific information			
	6'	68"		<u>X</u> 472-72			52	_			
6' Tall	3½'	40"		<u>X</u> 472-42F			33	Non-Stock			
4-Rail	4'	49-1/2"		<u>X</u> 472-48F			39	Non-Stock			
Flush Bottom	5'	58-3/4"		<u>X</u> 472-60F			45	Non-Stock			
	6'	68"	A <u>*</u>	<u>X</u> 472-72F			52	Non-Stock			

X=COLOR SELECTION: B=BLACK /N=BRONZE/W=WHITE

*=STYLE SELECTION: C=CLASSIC/M=MAJESTIC/G=GENESIS/W=WARRIOR/R=CONQUEROR

Effective: 01/01/13 Note: Gate hardware is not included. Available gate hardware kits are in the Gate Hardware Section of the Catalog.

AMERISTAR FENCE PRODUCTS **WELDED GATES**

ECHELON PLUS®

1-888-333-3422 FAX: 1-877-926-3747

RING GATES											
Classic [™] Sty	le Ring Gates	Majestic™	Style Ring Gates	Genesis™S	Style Ring Gate	s	Warrior™ Style Ring Gates				
(3-Rail)	(4-Rail)	(3-Rail		(3-Rail) (4-Rail)			(3-Rail) (4-Rail)				
Gate Height / Rail Quantity	Nominal Gate Opening	Actual Gate Leaf Width	Item Number	Catalog Price (Black)	Catalog Price (Bronze/White)	Gate Weight	Supplemental Information				
	3½'	40"	A <u>*</u> <u>X</u> 348-42R			25	Non-Stock				
4' Tall 3-Rail	4'	49-1/2"	A <u>*</u> <u>X</u> 348-48R			31	Non-Stock				
w/Rings	5'	58-3/4"	A * X 348-60R			35	Non-Stock				
	6'	68"	A * X 348-72R			40	Non-Stock				
	3½'	40"	A * X 360-42R			29	Non-Stock				
5' Tall 3-Rail	4'	49-1/2"	A * X 360-48R			35	Non-Stock				
w/Rings	5'	58-3/4"	A * X 360-60R			39	Non-Stock				
	6'	68"	A * X 360-72R			45	Non-Stock				
(1.T. II	3½'	40"	A <u>*</u> <u>X</u> 472-42R			33	Non-Stock				
6' Tall 4-Rail	4'	49-1/2"	A <u>*</u> <u>X</u> 472-48R			42	Non-Stock				
w/Rings	5'	58-3/4"	A <u>*</u> <u>X</u> 472-60R			48	Non-Stock				
	6'	68"	A <u>*</u> <u>X</u> 472-72R			56	Non-Stock				

X = COLOR SELECTION: B = BLACK / N = BRONZE / W = WHITE

 $*=STYLE\: SELECTION: \: C=CLASSIC/M=MAJESTIC/G=GENESIS/W=WARRIOR$

Note: Gate hardware is not included. Available gate hardware kits are in the Gate Hardware Section of the Catalog.

POOL GATES											
Mo	narch™ 2-Rai	1	Majestic [™] 3-Rail	Majestic [™] w/Rings		Conqueror [™] 3-Rail					
Gate Height / Rail Quantity	Nominal Gate Opening	Actual Gate Leaf Width	Item Number	Catalog Price (Black)	Catalog Price (Bronze/White	Gate Weight	Supplemental Information				
4' Tall	3½'	40"	AM <u>X</u> 248-42			25	Non-Stock				
Monarch [™]	4'	49-1/2"	AM <u>X</u> 248-48			31	Stock-Black				
2-Rail for Pools	5'	58-3/4"	AM <u>X</u> 248-60			35	Stock-Black				
for Pools	6'	68"	AM <u>X</u> 248-72			40	Non-Stock				
4½' Tall	31/2'	40"	AM <u>X</u> 354-42			29	Stock-Black				
Majestic™	4'	49-1/2"	AM <u>X</u> 354-48			35	Stock-Black				
3-Rail for Pools	5'	58-3/4"	AM <u>X</u> 354-60			39	Stock-Black				
ior roots	6'	68"	AM <u>X</u> 354-72			45	Non-Stock				
4½' Tall	3½'	40"	AM <u>X</u> 354-42R			33	Non-Stock				
Majestic [™]	4'	49-1/2"	AM <u>X</u> 354-48R			42	Non-Stock				
w/Rings for Pools	5'	58-3/4"	AM <u>X</u> 354-60R			48	Non-Stock				
for Pools	6'	68"	AM <u>X</u> 354-72R			56	Non-Stock				
4½' Tall	3½'	40"	AR <u>X</u> 354-42			29	Non-Stock				
Conqueror™	4'	49-1/2"	AR <u>X</u> 354-48			35	Stock-Black				
3-Rail	5'	58-3/4"	AR <u>X</u> 354-60			39	Non-Stock				
for Pools	6'	68"	AR <u>X</u> 354-72			45	Non-Stock				

- X=COLOR SELECTION: B=BLACK /N=BRONZE/W=WHITE

SEE NOTICE ON CHECKING FOR POOL CODE COMPLIANCE

Note: Gate hardware is not included. Available gate hardware kits are in the Gate Hardware Section of the Catalog. Effective: 01/01/13



1-888-333-3422 FAX: 1-877-926-3747

PUPPY GATES											
Classic [™]	Classic™ Style Puppy Gates Majestic™ Style Puppy Gates Genesis™ Style Puppy Gates										
(3-Rail) (4-Rail)		l-Rail)	(3-Rail) (4-Rail)		(3-Rail)						
Gate Height / Rail Quantity	Nominal Gate Opening	Actual Gate Leaf Width	Item Number	Catalog Price (Black)	Catalog l (Bronze/V		Supplemental Information				
42 T- II	3½'	40"	A <u>*</u> <u>X</u> 348-42D			27	Non-Stock				
4' Tall 3-Rail	4'	49-1/2"	A <u>*</u> <u>X</u> 348-48D			33	Non-Stock				
Puppy	5'	58-3/4"	A <u>*</u> <u>X</u> 348-60D			37	Non-Stock				
	6'	68"	A <u>*</u> <u>X</u> 348-72D			43	Non-Stock				
5' Tall	3½'	40"	A <u>*</u> <u>X</u> 360-42D			31	Non-Stock				
3-Rail	4'	49-1/2"	A <u>*</u> <u>X</u> 360-48D			37	Non-Stock				
Puppy	5'	58-3/4"	A <u>*</u> <u>X</u> 360-60D			42	Non-Stock				
	6'	68"	A <u>*</u> <u>X</u> 360-72D			48	Non-Stock				
6' Tall	3½'	40"	A <u>*</u> <u>X</u> 472-42D			37	Non-Stock				
4-Rail	4'	49-1/2"	A <u>*</u> <u>X</u> 472-48D			44	Non-Stock				
Puppy	5'	58-3/4"	A <u>*</u> <u>X</u> 472-60D			51	Non-Stock				
	6'	68"	A <u>*</u> <u>X</u> 472-72D			59	Non-Stock				

X=COLOR SELECTION: B=BLACK /N=BRONZE/W=WHITH

*-STYLE SELECTION: C=CLASSIC /M=MAIRSTIC /C=CENESIS

Note: Gate hardware is not included. Available gate hardware kits are in the Gate Hardware Section of the Catalog.

1-888-333-3422

FAX: 1-877-926-3747

ECHELON PLUS®



ARCHED WELDED GATES

ARCHED WELDED GATES												
STANDARD ARCHED GATES												
Classic [™] Arched Gates	Majestic [™] Arched Gates	Genesis [™] Arched Gates	Warrior [™] Arched Gates	Conqueror™ Arched Gates								

(3-Rail)	(3-Rail)	(3-Rail)	(3-Rail)	(3-Rail)
(4-Rail)	(4-Rail)	(4-Rail)	(4-Rail)	(4-Rail)

(4-	Rail)		(4-Rail)		(4-	Rail)	(4-Rail)			(4-Rail)	
Nominal Gate Height / Rail Quantity	Nominal Gate Opening	Actual Gate Leaf Width	Amount of Rise in Arch	N	Item Number	Catalog Price (Black)	Catalog Price (Bronze/White)	Gate Weight		Supplemental Information	
	3½'	40"	4"	A * 2	<u>X</u> 348-42A			42	No	n-Stock	
	4'	49-1/2"	5"	A <u>*</u> <u>Y</u>	<u>X</u> 348-48A			48	No	n-Stock	
4' Tall 3-Rail	5'	58-3/4"	6"	A <u>*</u> <u>Y</u>	<u>X</u> 348-60A			55	No	n-Stock	
	6'	68"	8"	A <u>*</u> <u>Y</u>	<u>X</u> 348-72A			62	No	n-Stock	
	7'	86-3/4"	10"	A <u>*</u> <u>Y</u>	<u>X</u> 348-84A			75	No	n-Stock	
	3½'	40"	4"	A <u>*</u> <u>Y</u>	<u>X</u> 360-42A			49	No	Non-Stock	
	4'	49-1/2"	5"	Α <u>*</u> Σ	<u>X</u> 360-48A			57	No	n-Stock	
5' Tall 3-Rail	5'	58-3/4"	6"	A <u>*</u> <u>Y</u>	<u>X</u> 360-60A			65	No	n-Stock	
	6'	68"	8"	A <u>*</u> <u>Y</u>	<u>X</u> 360-72A			72	No	n-Stock	
,	7'	86-3/4"	10"	A <u>*</u> <u>Y</u>	<u>X</u> 360-84A			88	No	n-Stock	
	3½'	40"	4"	A <u>*</u> <u>Y</u>	<u>X</u> 472-42A			57	No	n-Stock	
	4'	49-1/2"	5"	A <u>*</u> <u>Y</u>	<u>X</u> 472-48A			66	No	n-Stock	
6' Tall 4-Rail	5'	58-3/4"	6"	A <u>*</u> <u>Y</u>	<u>X</u> 472-60A			74	No	Non-Stock	
	6'	68"	8"	A <u>*</u> <u>Y</u>	<u>X</u> 472-72A			83	No	n-Stock	
	7'	86-3/4"	10"	A <u>*</u> <u>Y</u>	<u>X</u> 472-84A			101	No	n-Stock	
				1 1							

X=COLOR SELECTION: B=BLACK /N=BRONZE/W=WHITE

*=STYLE SELECTION: C=CLASSIC/M=MAJESTIC/G=GENESIS/W=WARRIOR/R=CONQUEROR

Note: Gate hardware is not included. Available gate hardware kits are in the Gate Hardware Section of the Catalog. Effective: 01/01/13



ARCHED WELDED GATES

1-888-333-3422 FAX: 1-877-926-3747

	ARCHED RING GATES										
Classic [™] A	assic™ Arched Ring Gates Majestic™ Arched Ring Gates Genesis™ Arched Ring Gates				es	Warrior [™] Arched Ring Gates					
	(3-Rail) (3-Rail) (3-Rail)			(3-Rail)							
	(4-Rail)		(4-Rail)		(4-Rail) (4-Rail)			(4-Rail)			
Nominal Gate Height / Rail Quantity	Nominal Gate Opening	Actual Gate Leaf Width	Amount of Rise in Arch	Item Number	Catalog Price (Black)	Catalog Price (Bronze/White)	Gate Weight	Supplemental Information			
	3½'	40"	4"	A <u>*</u> <u>X</u> 348-42AR			44	Non-Stock			
	4'	49-1/2"	5"	A <u>*</u> <u>X</u> 348-48AR			50	Non-Stock			
4' Tall 3-Rail w/Rings	5'	58-3/4"	6"	A * X 348-60AR			58	Non-Stock			
, wrames	6'	68"	8"	A <u>*</u> <u>X</u> 348-72AR			65	Non-Stock			
	7'	86-3/4"	10"	A <u>*</u> <u>X</u> 348-84AR			79	Non-Stock			
	3½'	40"	4"	A * X 360-42AR			51	Non-Stock			
	4'	49-1/2"	5"	A * X 360-48AR			59	Non-Stock			
5' Tall 3-Rail w/Rings	5'	58-3/4"	6"	A * X 360-60AR			68	Non-Stock			
W/Kings	6'	68"	8"	A * X 360-72AR			75	Non-Stock			
	7'	86-3/4"	10"	A <u>*</u> <u>X</u> 360-84AR			92	Non-Stock			
	3½'	40"	4"	A <u>*</u> <u>X</u> 472-42AR			59	Non-Stock			
	4'	49-1/2"	5"	A <u>*</u> <u>X</u> 472-48AR			68	Non-Stock			
6' Tall 4-Rail w/Rings	5'	58-3/4"	6"	A <u>*</u> <u>X</u> 472-60AR			77	Non-Stock			
	6'	68"	8"	A <u>*</u> <u>X</u> 472-72AR			86	Non-Stock			
	7'	86-3/4"	10"	A <u>*</u> <u>X</u> 472-84AR			105	Non-Stock			

X=COLOR SELECTION: B=BLACK /N=BRONZE/W=WHITE

*=STYLE SELECTION: C=CLASSIC/M=MAJESTIC/G=GENESIS/W=WARRIOR

Note: Gate hardware is not included. Available gate hardware kits are in the Gate Hardware Section of the Catalog.

1-888-333-3422

FAX: 1-877-926-3747

ECHELON PLUS®



ARCHED WELDED GATES

ARCHED WELDED GATES											
ARCHED POOL GATES											
	Monarch™ Arched Pool Gates			estic™ Arched ool Gates		stic [™] Arched tes with/Rings		Conqueror™ Arched Pool Gates			
		_			100751						
(2-Rail)			(3-Rail)		(3-Rail)			(3-Rail)			
Nominal Gate Height / Rail Quantity	Nominal Gate Opening	Actual Gate Leaf Width	Amount of Rise in Arch	Item Number	Catalog Price (Black)	Catalog Price (Bronze/White)	Gate Weight	Supplemental Information			
	3½'	40"	4"	AM <u>X</u> 248-42A			38	Non-Stock			
Monarch™	4'	49-1/2"	5"	AM <u>X</u> 248-48A			44	Non-Stock			
4' Tall 2-Rail	5'	58-3/4"	6"	AM <u>X</u> 248-60A			50	Non-Stock			
Arched	6'	68"	8"	AM <u>X</u> 248-72A			56	Non-Stock			
	7'	86-3/4"	10"	AM <u>X</u> 248-84A			68	Non-Stock			
	3½'	40"	4"	AM <u>X</u> 354-42A			45	Non-Stock			
Majestic™	4'	49-1/2"	5"	AM <u>X</u> 354-48A			53	Non-Stock			
4½' Tall 3-Rail	5'	58-3/4"	6"	AM <u>X</u> 354-60A			60	Non-Stock			
Arched	6'	68"	8"	AM <u>X</u> 354-72A			67	Non-Stock			
	7'	86-3/4"	10"	AM <u>X</u> 354-84A			81	Non-Stock			
	3½'	40"	4"	AM <u>X</u> 354-42AR			47	Non-Stock			
Majestic™ 4½' Tall	4'	49-1/2"	5"	AM <u>X</u> 354-48AR			55	Non-Stock			
3-Rail Arched	5'	58-3/4"	6"	AM <u>X</u> 354-60AR			63	Non-Stock			
w/Rings	6'	68"	8"	AM <u>X</u> 354-72AR			70	Non-Stock			
	7'	86-3/4"	10"	AM <u>X</u> 354-84AR			85	Non-Stock			
	3½'	40"	4"	AR <u>X</u> 354-42A			45	Non-Stock			
Conqueror™	4'	49-1/2"	5"	AR <u>X</u> 354-48A			53	Non-Stock			
4½' Tall 3-Rail Arched	5'	58-3/4"	6"	AR <u>X</u> 354-60A			60	Non-Stock			
Archeu	6'	68"	8"	AR <u>X</u> 354-72A			67	Non-Stock			
	7'	86-3/4"	10"	AR <u>X</u> 354-84A			81	Non-Stock			

X = COLOR SELECTION: B = BLACK /N = BRONZE/W = WHITE

Note: Gate hardware is not included. Available gate hardware kits are in the Gate Hardware Section of the Catalog.

Effective: 01/01/13