

GAFGLAS®  
Stratavent® Eliminator™  
Perforated Base Sheet

Data Sheet

Updated: 1/10



*Quality You Can Trust Since 1886...*  
*From North America's Largest Roofing Manufacturer™*



# GAFGLAS®

## STRATAVENT® ELIMINATOR™

### PERFORATED BASE SHEET

#### Description

GAFGLAS® STRATAVENT® Eliminator™ Perforated Base Sheet is a premium-grade roofing felt constructed around a strong glass fiber mat and high quality asphalt. The bottom of the sheet is granule-surfaced to provide positive venting of any trapped gases under the roof membrane.

- GAFGLAS® STRATAVENT® Eliminator™ Perforated Base Sheet is available for nailable and non-nailable substrates.
- GAFGLAS® STRATAVENT® Eliminator™ Perforated Base Sheet is unique in the industry: its patent-pending perforated design allows mopping asphalt to flow through to the substrate as the next ply of the roof system is installed. The flow-through asphalt uniformly bonds the STRATAVENT® Eliminator™ Perforated Base Sheet and the subsequent roof system to the substrate.

#### Uses

GAFGLAS® STRATAVENT® Eliminator™ Perforated Base Sheet is a venting base sheet designed to be used in various GAFGLAS® built-up and RUBEROID® modified bitumen roofing systems. It can be used over both nailable and non-nailable substrates, including certain existing old roof surfaces and isocyanurate foams.



#### Advantages

- Provides for venting of pressurized gases beneath the roofing membrane.
- Fire resistant—for use in UL, ULC Class A rated assemblies.
- In recover applications, provides an effective means for separating the new roofing membrane from the existing roof system.
- GAFGLAS® STRATAVENT® Eliminator™ Perforated Base Sheet provides consistent, uniform spot-attachment of the roofing membrane.
- Wind uplift-resistant; FMRC Approved up to Class 1-345 (See FM Approval Guide for details)
- Meets requirements for application in all climate zones
- System guarantees are available for up to 20 years.

#### Applicable Standards

Meets ASTM D4897, Type II and ASTM D3672, Type II
FM Approved
Meets CGSB-37-GP-56M
ICC ESR#1274
Miami-Dade County Product Control Approval
State of Florida Product Approval
Texas Department of Insurance
UL/ULc Listed

#### Products Specifications (nominal)

Roll Size	1.26 squares (133.4 gross sq.ft.) (12.4m²)
Roll Length	40.6' (12.4m)
Roll Width	39.375" (1.0m)
Approx. Roll Weight	67 lbs (30.39kg)