# EverGuard<sup>TM</sup> PVC Accessories

**Information Sheet** 



### Product Data Sheet EverGuard® PVC Accessories

#### **Description**

The GAF EverGuard® PVC single-ply roofing system includes an extensive line of EverGuard PVC flashing accessories for use with EverGuard PVC roofing systems. EverGuard flashing accessories are heat welded to the EverGuard roofing membrane. They are easy to install and provide secure protection from roof edge to parapet to penetration to wall. The following EverGuard PVC flashing accessories are available in standard colors of white and gray:

Product	Description	Benefit/Application	Quantity/Size	Weight
Prefabricated Expansion Joint Covers	.060" thick reinforced membrane with foam supported bellows	Two standard sizes to accommodate most common joint widths of o' continuous length minimizes joints Universal style suitable for both field and wall expansion joints Factory-fabricated terminations and transitions available	Small  • 4" bellows for 1-2" joints • 50' continuous roll  Large • 6" bellows for 2-3" joints • 50' continuous roll	Small: 60 lbs/roll Large: 75 lbs/roll
Walkway Rolls	1/8" thick (125 mil) extruded and embossed PVC	Herringbone traction surfacing in gray color     Available in both pads and rolls     Heat welds directly to membrane	Pads • 30" x 36"; 30 pads/carton Rolls • 30" x 50'	8 lbs/pad or 118 lbs/roll
Preformed Pipe Boot	Molded PVC un- reinforced membrane	Three standard sizes to accommodate most common pipes and conduit	6 Boots/Carton 1"-4" 3"-7" 7"-12" (White Only)	4 lbs/carton 4.5 lbs/carton 5 lbs/carton
Preformed Inside Corner	Molded PVC unreinforced membrane	For use in flashing inside corners of base and curb flashings	2-3/4" x 3.5" with 6' flange 20 corners/carton	1.8 lbs/carton
Preformed Outside Corner	Molded PVC unreinforced membrane	For use in flashing outside corners of base and curb flashings	8" diameter 20 corners/carton	2.4 lbs/carton
Coated Metal Sheets	24 gauge steel with .040" thick membrane film	PVC un-reinforced membrane is laminated to galvanized sheet metal Cuts and forms like standard sheet metal. Field and flashing membranes heat weld directly to coated metal For metal gravel stops, and drip edges; metal base and curb flashings; sealant pans and scupper sleeves	4' x 10' sheets, 10 sheets/pallet 30 sheets/pallet (White Only)	520 lbs/pallet, 1560 lbs/pallet
UN-80 T-Joint Cover Patches	.080" thick un- reinforced membrane: white/gray and white/tan	Conforming membrane seal over t-joints in 60 and 80 mil membrane applications	6-3/4" diameter 100 patches/carton	9.3 lbs/carton
UN -80 24" Detailing Membrane	.080" thick un- reinforced membrane: white/gray and white/tan	Alternative flashing material for penetrations and corners     Required wherever preformed vent boots can not be used	24" x 50' roll	42 lbs/roll
UN -80 12" Flashing Membrane	.080" thick un- reinforced membrane: white/gray and white/tan	Alternative flashing material for penetrations and corners     Required wherever preformed vent boots can not be used	12" x 50' roll	21 lbs/roll

#### Storage

Store accessory flashing materials in original cartons, rolls or sheets on pallets or shelving, in a dry area.

Product Data Sheet 15

## Product Data Sheet EverGuard® PVC Accessories

Product	Description	Benefit/Application	Quantity/Size	Weight
UN -80 6" Detailing Strip	.080" thick un- reinforced mem- brane: white/gray and white/tan	For use in stripping in PVC coated metal	• 6" x 150' roll	40 lbs/roll
Cut Edge Sealant	Semi-clear liquid thermoplastic sealant	For sealing the cut edges of reinforced PVC membrane.	• 12 pint bottles/carton • (4) 1 gallon cans/carton	• 14 lbs/carton • 38 lbs/carton
Preformed Pitch Pocket	Molded rigid PVC pocket, 6-1/2" in diameter by 3-3/4" high	Split prefabricated PVC pitch pocket for easy installation around single or multiple pipes	• 12 pockets/carton (White Only)	24 lbs/carton

Product Data Sheet 16 30