

TopCoat® Sky-Lite

Information Sheet

Updated: 2/06



*Quality You Can Trust Since 1886...
From North America's Largest Roofing Manufacturer™*



*“Don’t Repair Or Replace It...
Restore It And Save”*

SKY-LITE

CLEAR, SYNTHETIC RUBBER SEALER

Used by roofing contractors who demand the highest quality



Designed For Use On:

- Weathered Plastic Skylights
- Masonry • Fiberglass

Specially designed to protect and waterproof deteriorated fiber-glass reinforced skylight panels, in addition to weathered plastic skylights and masonry.

TOPCOAT® Sky-Lite:

- Seals out water and prevents leaking of porous skylights
- Seals and binds reinforcing fibers and extends the life of skylight panels
- Reconditions leaky panels
- Assists in the restoration of original skylight clarity
- Available in 5 gallon pails
- Warranties available for up to 10 years*

Recommended uses:

Protects and reconditions translucent skylight panels found on roofs and walls. Do not use to repair cracked or broken skylight panels.

*See limited warranties for complete coverage and restrictions.



NO SEAMS. NO LEAKS. NO PROBLEMS.

Quality You Can Trust
Since 1886... from
North America's Largest
Roofing Manufacturer



PRODUCT DATA

TOPCOAT® SKY-LITE

Clear, solvent-based synthetic rubber sealer designed to protect and waterproof porous, deteriorated fiberglass reinforced skylight panels in addition to weathered plastic skylights. Do not apply at temperatures below 42°F. Substrate temperatures must be below 120°F when applying this product. Also available in water-based version when flammability and V.O.C. content are a concern.

Application Rate:	1 gallon/100 sq. ft. per coat
Application Method:	Roller or brush
Application Temperature (air, surface):	42° - 120°F
Drying Time (75°F, 50% RH):	Approximately 1 hour per coat
Wet Mil Thickness:	16 wet mils
Dry Mil Thickness:	6 dry mils
Total Solids (by weight):	40.2% +/- 2%
Total Solids (by volume):	35% +/- 2%
Specific Gravity:	0.91 +/- 0.1
Weight per gallon:	7.6 +/- 0.5 lbs
Viscosity (75°F):	3,000 +/- 400 cps
Clean-up:	Mineral Spirits, Toluene, Xylene
ASTM D-2196, ASTM D-1475, ASTM D-1644	

NOTE: Repair leaks promptly to avoid adverse effects including mold growth.



Call for more information and a **FREE** brochure and video.

1-800-323-0009

www.gaf.com

