# Drill-Tec<sup>TM</sup> Steel and Plastic Plates

**Data Sheet** 

Updated: 1/10





## **DRILL-TEC**™ STEEL AND PLASTIC PLATES

### Pressure Plates

Drill-Tec™ **Steel Plates** 









Drill-Tec™ Steel Plates are made of Galvalume® coated steel. The round design provides an even distribution of loads and eliminates sharp corners that can damage the insulation or membrane. Drill-Tec™ 23/8" and 23/4" plates should be used for lap seam fastening. Drill-Tec™ 3" plates should be used when fastening insulation. These plates are designed to be used with Drill-Tec™ fasteners.

#### **Code Approvals**





Product Data				
Plate	SKU#	Diameter	Packaging	Weight
2" Barbed Plate	8676	2"	1000	29 lbs
2" Double- Barbed Plate	46DB	2 1/8"	1000	34 lbs
2 3/8" XHD Barbed Seam Plate	8678	2 3/8"	1000	45 lbs
2 3/4" Super XHD Plate	8679	2 3/4"	500	37 lbs
3" Galvalume® Plate	4577	2 7/8"	1000	37 lbs
3" Lite-Deck Plate	457B	3"	500	19 lbs
3" Base Sheet Plate	45JJ	3"	1000	46 lbs

#### **Physical Data**

#### 2" Barbed Plate

Application: Attaches EverGuard® membrane to the substrate.

Drill-Tec™ HD #14 Fasteners, XHD #15 Fasteners and Drill-Tec™ CD-10 Fasteners Fastener:

#### 2" Double-Barbed Plate

Application: Attaches EverGuard® membrane to the substrate.

Drill-Tec™ XHD #15 Fasteners, SXHD #21 Fasteners and Drill-Tec™ CD-10 Fasteners. Fastener:

#### 23/8" XHD Barbed Seam Plate

Application: Attaches EverGuard® membrane to the substrate.

Drill-Tec<sup>™</sup> XHD #15 Fasteners and Drill-Tec<sup>™</sup> CD-10 Fasteners. Fastener:

#### 23/4" Super XHD Double-Barbed Seam Plate

Application: Attaches EverGuard® membrane to the substrate.
Fastener: Drill-Tec™ SXHD #21 Fasteners and Drill-Tec™ CD-10 Fasteners.

#### 3" Galvalume® Plate

Application: Attaches insulation to the substrate.

Fastener: Drill-Tec<sup>™</sup> Standard, #12 Fasteners, HD #14 Fasteners,

CD-10 Fasteners, Fluted Nail.

#### Lite-Deck Plate

Application: Attaches insulation to gypsum, Tectum® and lightweight concrete decks.

Drill-Tec™ Lite-Deck Fastener. Fastener:

#### **Base Sheet Plate**

Drill-Tec<sup>™</sup> fasteners.

Application: Attaches base sheets to lightweight insulating concrete and various gypsums.

3" Plastic

3" Locking

Plastic Plate

Plate

**Product Data** 

4578

3 1/16'

45JK 3 1/16"

Drill-Tec™ Standard or 1.2 Base Sheet Fastener. Fastener:









Drill-Tec™ 3" plates should be used when

fastening insulation. All Drill-Tec™ plates are round and designed to be used with

#### **Physical Data**

Description

3" Polypropylene Plastic Plate

Attaches insulation to the substrate. Application:

Fastener: Drill-Tec Standard, Heavy Duty, CD-10, Fluted Nail or Toggle Bolt fastener.

3" Polypropylene Locking Plastic Plate

Attaches insulation to the substrate. Application:

Drill-Tec Standard, Heavy Duty or Toggle Bolt fastener. Fastener:



Packaging

25 lbs

25 lbs

1000

1000