

## SINGLE COVER SPECIFICATIONS

- **COVER** : .090 ALUMINUM (11 GA) COVER IS STIFFENED TO WITHSTAND A LIVE LOAD OF 40 PSF WITH A MAX DEFLECTION OF 1/150 OF THE SPAN. COVER WITHSTANDS A MAX. WIND UPLIFT OF 20 PSF. MAX DEGREE OF OPENING IS 78°
- **LINER** : .040 ALUMINUM
- **CURB** : .090 ALUMINUM
- **COUNTERFLASH** : .090 ALUMINUM WITH EZ TAB FLASHING SYSTEM
- **FINISH**: MILL FINISH
- **HARDWARE**: ZINC PLATED STEEL
- **HINGE**: ZINC PLATED STEEL TAMPER PROOF HINGE ASSEMBLED ON THE INSIDE OF HATCH AS PART OF SPRING ASSEMBLY
- **LATCH**: SLAM LATCH WITH POSITIVE RETURN TURN HANDLE, PADLOCKING OUTSIDE & INSIDE
- **SPRING(S)**: STEEL GREASED COMPRESSION SPRING ENCLOSED IN TELESCOPIC TUBES WHICH COUNTER BALANCE THE DOOR
- **MOUNTING FLANGE**: 3.50"
- **INSULATION**: 1" THICK INSULATION IN COVER AND 1" ON CURB PERIMETER

## OPTIONS

- OSS - STAINLESS STEEL HARDWARE

## CURB OPTIONS

- 1 - SINGLE WALL CURB (AS SHOWN)
- 2 - DOUBLE WALL CURB
- 3 - CURB MOUNT FLANGE
- 4 - DOUBLE WALL NO COUNTERFLASH
- 5 - APRON MOUNT

THIS PRODUCT MAY BE INSTALLED ON EITHER A FLAT OR SLOPING ROOF, WHEN INSTALLED ON A SLOPE, THE HINGE SIDE MUST RUN PARALLEL WITH THE SLOPE, IF THE SLOPE EXCEEDS A 3:12 PITCH, ADVISE FACTORY FOR MODIFICATION.

## SIZE

WIDTH:                      LENGTH:

\*HINGE ON LENGTH SIDE  
WIDTH AND LENGTH DIMENSIONS ARE FROM THE INSIDE FACES OF CURB

