



- ① COVER - 11 GAUGE ALUMINUM COVER STIFFENED TO WITHSTAND A LIVE LOAD OF 40 PSF WITH A MAX DEFLECTION OF 1/150 OF THE SPAN. COVER WITHSTANDS A MAX WIND UPLIFT OF 20 PSF.
- ② LINER - 18 GAUGE ALUMINUM
- ③ CURB - 11 GAUGE ALUMINUM
4. HARDWARE - ZINC PLATED STEEL
- ⑤ LATCH - SINGLE POINT LATCH WITH PROVISION FOR PADLOCK SECURITY

- ⑥ INSULATION - 1" THICK IN COVER AND 1" THICK ON CURB PERIMETER
- ⑦ MOUNTING FLANGE - 3.50 INCHES
- ⑧ HINGE - ZINC PLATED STEEL TAMPER PROOF HINGE CONTAINED WITHIN HATCH AS PART OF SPRING ASSEMBLY
9. SPRING - GREASED HEAVY DUTY COMPRESSION SPRING.
10. FINISH - MILL FINISH
11. CURB OPENING - 48 X 48 INCHES MEASURE INSIDE CURB TO INSIDE CURB

**NYSTROM**  
Right to site.  
9300 73rd Avenue North  
Brooklyn Park, MN 55428

## RHPA48X48S1T

TITLE: Roof Hatch, Personnel Access,  
48x48, Sngl Dr,  
Alum, Mill, Sngl Wall Curb,

	NAME	DATE	SIZE	DWG. NO.	REV
DRAWN	DWO	10/20/09	B	RHPA48X48S1T	A
RELEASED	DWO	10/20/09	WEIGHT: 168.66		
			SHEET 20 OF 21		

