





SECTION A-A

SPECIFICATIONS:

- (1) COVER: 11 GAUGE ALUMINUM STIFFENED

 TO WITHSTAND A LIVE LOAD OF 40 PSF WITH A MAX
 DEFLECTION OF 1/150 OF THE SPAN
- $\langle 2 \rangle$ **LINER:** 18 GAUGE ALUMINUM
- (3) CURB AND COUNTERFLASH W/ EZ TAB:14 GAUGE GALVANNEAL
- 4 FINISH: COVER-MILL

CURB-POWDER COAT PAINT, ANSI 70 GRAY

- (5) GAS SPRING WITH DAMPER: DESIGNED TO OPEN AGAINST A 10PSF SNOW LOAD IN NOT LESS THAN 2 SECONDS
- (6) HOLD OPEN ARM: LOCK COVER IN FULLY OPEN POSITION ZINC PLATED STEEL
- (7) LATCH: ZINC PLATED ROTARY LATCH ASSEMBLY DESIGNED TO HOLD COVERS CLOSED AGAINST 90 PSF WIND UPLIFT ZINC PLATED STEEL LATCH STRIKERS ON COVERS

- (8) HINGES: ZINC PLATED STEEL WITH STAINLESS STEEL HINGE PINS
- (9) INSULATION:POLYISOCYANURATE IN COVER AND AROUND CURB PERIMETER, R-VALUE 6
- (10) GASKET: ADHESIVE BACKED EPDM RUBBER EXTRUSION
- THERMAL RELEASE MECHANISM: VENT COVERS OPEN
 THERMALLY BY HEAT AT FUSIBLE LINK TEMPERATURE ° F
- (12) MANUAL OPENING: VENT COVERS OPEN WITH INTERNAL AND EXTERNAL MANUAL PULL HANDLE, 1/16" DIA SST CABLE
- (13) ELECTRICAL RELEASE: VENT COVERS OPEN ELECTRICALLY WHEN ENERGIZED WITH

SMOKE VENT SIZE (WIDTH) X (LENGTH)

EFFECTIVE VENTING AREA 80% SQFT

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MYSTROM IS PROHIBITED.



				02700				
PROJECT:								
ARCHITECT:								
CONTRACTOR:								
QTY:								
PART#:				SVSB	X	D1	R	
NYSTROM Right to site. 9300 73rd Avenue North Brooklyn Park, MN 55428				TITLE: Smoke Vent, SmokEscape Series Galvanneal, Dbl Dr, Single Wall Curb Electrical				
	NAME	DATE	SIZE	DWG. NO.				REV
DRAWN	-	05/04/11	Α		SVSB_X_D	1R		-
RELEASED	DS	05/04/11	WE	IGHT: VARIE	S		SHEET 1 (OF 2

