

(SINGLE STAGE RIBBED ABRASIVE BARS)

SPECIFICATIONS:

- 1 BASE: HEAT TREATED EXTRUDED ALUMINUM ALLOY 6063 T-5
- $\langle 2 \rangle$ **ABRASIVE**: ALUMINUM OXIDE SILICON CARBIDE GRANULES IN A UV PROTECTED, 2 PART EPOXY, LOCKED INTO EXTRUDED CHANNELS
- 3. BASE FINISH: MILL
- 4. POURED CONCRETE STAIRS: NOSING SHALL
 TERMINATE NO MORE THEN 3" FROM END OF STEPS

 5. CONCRETE FILLED STEEL PAN STAIRS: NOSING
 SHALL BE FULL LENGTH OF STEPS, LESS 1/8" CLEARANCE
- 6. **COLOR:** BLACK (STANDARD), SAFETY YELLOW, GRAY, RED, BROWN, GREEN, BURGUNDY, BLUE, BUFF
- 7. LENGTH: 12'0" MAXIMUM

LENGTH	QTY	COLOR

	PROJECT:							
ARCHITECT: CONTRACTOR: QTY:								
	PART#:				STSB-C1.875E			
Right to site. 9300 73rd Avenue North Brooklyn Park, MN 55428					TITLE: Short	V331, Stair Tread, Bar Ribbed Abrasive Nose, Alum Extruded	e, I Anchor,	
		NAME	DATE	SIZE	DWG. NO.			REV
	DRAWN	ВМН	3/11/11	Α		STSB-C1.875E		Α
	RELEASED	PE	3/11/11	WE	IGHT: .69 LB		SHEET 1 C	OF 1

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.