1/16" MIN ]/11 /2 3/11

MODEL C4E

(SINGLE STAGE RIBBED ABRASIVE BARS)

## **SPECIFICATIONS:**

- 1) BASE: HEAT TREATED EXTRUDED ALUMINUM ALLOY 6063 T-5
- (2) ABRASIVE: ALUMINUM OXIDE SILICON CARBIDE GRANULES IN A UV PROTECTED, 2 PART EPOXY, LOCKED INTO EXTRUDED CHANNELS
- 3. BASE FINISH: MILL
- 4. POURED CONCRETE STAIRS: NOSING SHALL TERMINATE NO MORE THEN 3" FROM END OF STEPS
- 5. CONCRETE FILLED STEEL PAN STAIRS: NOSING
  SHALL BE FULL LENGTH OF STEPS, LESS 1/8"
  CLEARANCE

- 6. **COLOR:** BLACK (STANDARD), SAFETY YELLOW, GRAY, RED, BROWN, GREEN, BURGUNDY, BLUE, BUFF
- 7. LENGTH: 12'0" MAXIMUM

LENGTH	QIY	COLOR
	•	•

PROJECT: ARCHITECT: CONTRACTOR: QTY: PART#:								
					STSB-C4E			
Right to site. 9300 73rd Avenue North Brooklyn Park, MN 55428			-	, Stair Tread, bbed Abrasive lum Extruded	,			
Ī		NAME	DATE	SIZE	DWG. NO.			REV
Ī	DRAWN	вмн	3/11/11	Α	STS	B-C4E		Α
	RELEASED	PE	3/11/11	WE	IGHT: 1.50 LB		SHEET 1	OF 1

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.

1