

SPECIFICATIONS:

- (1) BASE: HEAT TREATED EXTRUDED ALUMINUM ALLOY 6063 T-5
- $\langle 2 \rangle$ **ABRASIVE**: ALUMINUM OXIDE SILICON CARBIDE GRANULES IN A UV PROTECTED, 2 PART EPOXY, LOCKED INTO EXTRUDED CHANNELS
- 3. BASE FINISH: MILL
- 4. POURED CONCRETE STAIRS: NOSING SHALL TERMINATE NO MORE THEN 3" FROM END OF STEPS
- 5. CONCRETE FILLED STEEL PAN STAIRS: NOSING SHALL BE FULL LENGTH OF STEPS, LESS 1/8" CLEARANCE

- 6. **COLOR:** BLACK (STANDARD), SAFETY YELLOW, GRAY, RED, BROWN, GREEN, BURGUNDY, BLUE, BUFF
- 7. LENGTH: 12'0" MAXIMUM

LENGTH	QTY	COLOR

	F	PROJECT:						
	ARCHITECT:							
	CONTRACTOR:							
	QTY:							
	PART#: NYSTRUM Right to site. 9300 73rd Avenue North Brooklyn Park, MN 55428				STSB-A3E			
					TITLE: V851, Stair Tread, Bar Ribbed Abrasive,			
					Long Nose Angled, Alum Extruded Anchor,			
		NAME	DATE	SIZE	DWG. NO.			REV
l	DRAWN	ВМН	3/11/11	Α		STSB-A3E		Α
	RELEASED	PE	3/11/11	WE	IGHT: 1.33 LB		SHEET 1 (OF 1

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.