

SPECIFICATIONS:

- (1) BASE: HEAT TREATED EXTRUDED ALUMINUM ALLOY 6063 T-5
- $\langle 2 \rangle$ **ABRASIVE**: ALUMINUM OXIDE SILICON CARBIDE GRANULES IN A UV PROTECTED, 2 PART EPOXY, LOCKED INTO EXTRUDED CHANNELS
- 3. BASE FINISH: MILL
- 4. POURED CONCRETE STAIRS: NOSING SHALL TERMINATE NO MORE THEN 3" FROM END OF STEPS
- 5. CONCRETE FILLED STEEL PAN STAIRS: NOSING SHALL BE FULL LENGTH OF STEPS, LESS 1/8" CLEARANCE
- 6. COLOR: BLACK (STANDARD), SAFETY YELLOW, GRAY, RED, BROWN, GREEN, BURGUNDY, BLUE,

- 7. LENGTH: 12'0" MAXIMUM8. COUNTER SUNK HOLES PRE-DRILLED FOR A #10 FASTENER SPACED 3" FROM ENDS AND APPROXIMATELY 12" TO 15" O.C.

| LENGTH | QTY | COLOR |
|--------|-----|-------|
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |

| F | PROJEC | CT: | | | | | |
|---|--------|------------|---|---------------|----------|---------|------|
| ARCHITECT: | | | | | | | |
| CONTRACTOR: | | | | | | | |
| QTY: | | | | | | | |
| | PART# | # : | | STSB-N3D | | | |
| Right to site. 9300 73rd Avenue North Brooklyn Park, MN 55428 | | | TITLE: V150, Stair Tread, Bar Ribbed Abrasive, No Nose, Drilled For Bolt In | | | | |
| | NAME | DATE | SIZE | DWG. NO. | | | REV |
| DRAWN | вмн | 3/11/11 | Α | | STSB-N3D | | Α |
| RELEASED | PE | 3/11/11 | WE | IGHT: 1.27 LB | | SHEET 1 | OF 1 |

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.

1