

## MODEL C2.125E


(SINGLE STAGE FULL ABRASIVE)

### SPECIFICATIONS:

- ① **BASE:** HEAT TREATED EXTRUDED ALUMINUM  
ALLOY 6063 T-5
- ② **ABRASIVE:** ALUMINUM OXIDE SILICON CARBIDE  
GRANULES IN A UV PROTECTED, 2 PART EPOXY,  
LOCKED INTO EXTRUDED CHANNELS
3. **BASE FINISH:** MILL
4. **POURED CONCRETE STAIRS:** NOSING SHALL  
TERMINATE NO MORE THEN 3" FROM END OF STEPS
5. **CONCRETE FILLED STEEL PAN STAIRS:** NOSING  
SHALL BE FULL LENGTH OF STEPS, LESS 1/8"  
CLEARANCE

6. **COLOR:** BLACK (STANDARD), SAFETY YELLOW,  
GRAY, RED, BROWN, GREEN, BURGUNDY, BLUE, BUFF
7. **LENGTH:** 120" MAXIMUM

LENGTH	QTY	COLOR

PROJECT:					
ARCHITECT:					
CONTRACTOR:					
QTY:					
PART#:		STSF-C2.125E			
 <small>Right to site.</small> 9300 73rd Avenue North Brooklyn Park, MN 55428		TITLE:			
		VFA21, Stair Tread, Full Abrasive, Short Nose, Alum Extruded Anchor,			
	NAME	DATE	SIZE	DWG. NO.	REV
DRAWN	BMH	3/11/11	A	STSF-C2.125E	A
RELEASED	PE	3/11/11	WEIGHT: .75 LB	SHEET 1 OF 1	