31/3" /8 5/II /8 1 1/8"

MODEL L3.125E

(SINGLE STAGE FULL ABRASIVE)

## **SPECIFICATIONS:**

- (1) **BASE**: HEAT TREATED EXTRUDED ALUMINUM ALLOY 6063 T-5
- (2) ABRASIVE: ALUMINUM OXIDE SILICON CARBIDE GRANULES IN A UV PROTECTED, 2 PART EPOXY, LOCKED INTO EXTRUDED CHANNELS
- 3. BASE FINISH: MILL
- 4. POURED CONCRETE STAIRS: NOSING SHALL TERMINATE NO MORE THEN 3" FROM END OF STEPS
- 5. CONCRETE FILLED STEEL PAN STAIRS: NOSING SHALL BE FULL LENGTH OF STEPS, LESS 1/8" CLEARANCE

- 6. **COLOR:** BLACK (STANDARD), SAFETY YELLOW, GRAY, RED, BROWN, GREEN, BURGUNDY, BLUE, BUFF
- 7. LENGTH: 12'0" MAXIMUM

LENGTH	QTY	COLOR

	F	PROJEC	CT:					
	A	RCHITE	CT:					
	СО	NTRAC	TOR:					
		QTY:						
	PART#:  NYSTROM  Right to site.  9300 73rd Avenue North Brooklyn Park, MN 55428			STSF-L3.125E				
				TITLE: VFAL31, Stair Tread, Full Abrasive,				
				Long Nose, Alum Extruded Anchor,				
		NAME	DATE	SIZE	DWG. NO.			REV
l	DRAWN	ВМН	3/11/11	Α		STSF-L3.125E		Α
	RELEASED	PE	3/11/11	WE	IGHT: 1.35 L	В	SHEET 1	OF 1

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.

1