

SPECIFICATIONS:

- (1) BASE: HEAT TREATED EXTRUDED ALUMINUM ALLOY 6063 T-5
- (2) ABRASIVE: ALUMINUM OXIDE SILICON CARBIDE
 GRANULES IN A UV PROTECTED, 2 PART EPOXY,
 LOCKED INTO EXTRUDED CHANNELS
- 3. BASE FINISH: MILL
- 4. POURED CONCRETE STAIRS: NOSING SHALL TERMINATE NO MORE THEN 3" FROM END OF STEPS
- 5. CONCRETE FILLED STEEL PAN STAIRS: NOSING SHALL BE FULL LENGTH OF STEPS, LESS 1/8" CLEARANCE

- 6. **COLOR:** BLACK (STANDARD), SAFETY YELLOW, GRAY, RED, BROWN, GREEN, BURGUNDY, BLUE, BUFF
- 7. **LENGTH:** 12'0" MAXIMUM

QTY	COLOR
	QTY

	PROJECT:							
	ARCHITECT: CONTRACTOR: QTY:							
	PART#:				STSF-N2.25E			
	Right to site. 9300 73rd Avenue North Brooklyn Park, MN 55428				TITLE:	V24, Stair Tread, Full Abrasive, Nose, Alum Extruded <i>i</i>	Anchor,	
		NAME	DATE	SIZE	DWG. NO.			REV
	DRAWN	ВМН	3/14/11	Α		STSF-N2.25E		Α
	RELEASED	PE	3/14/11	WE	IGHT: .90 LB		SHEET 1 (OF 1

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.

1