



MODEL P3.375E

(TWO STAGED FULL ABRASIVE)

SPECIFICATIONS:

- ① **BASE:** HEAT TREATED EXTRUDED ALUMINUM
ALLOY 6063 T-5
- ② **ABRASIVE:** ALUMINUM OXIDE SILICON CARBIDE
GRANULES IN A UV PROTECTED, 2 PART EPOXY,
LOCKED INTO EXTRUDED CHANNELS
3. **BASE FINISH:** MILL
4. **POURED CONCRETE STAIRS:** NOSING SHALL
TERMINATE NO MORE THEN 3" FROM END OF
STEPS
5. **CONCRETE FILLED STEEL PAN STAIRS:** NOSING
SHALL BE FULL LENGTH OF STEPS, LESS 1/8"
CLEARANCE

6. **COLOR:** BLACK (STANDARD), SAFETY YELLOW,
GRAY, RED, BROWN, GREEN, BURGUNDY, BLUE, BUFF
7. **LENGTH:** 12'0" MAXIMUM

LENGTH	QTY	COLOR

PROJECT:				
ARCHITECT:				
CONTRACTOR:				
QTY:				
PART#:		STTF-P3.375E		
NYSTROM <small>Right to site.</small> 9300 73rd Avenue North Brooklyn Park, MN 55428		TITLE: Two Stage FA, Stair Tread, Full Abrasive, Short Nose, Alum Extruded Anchor,		
	NAME	DATE	SIZE	DWG. NO.
DRAWN	BMH	3/14/11	A	STTF-P3.375E
RELEASED	PE	3/14/11	WEIGHT: 2 LB	SHEET 1 OF 1