

## NOTES:

2.

- PROFILE: HIGH IMPACT VINYL ACRYLIC EXTRUSION LOCKED IN PLACE, NOMINAL 0.078" (1.98mm) THICK
  - CLASS A FIRE RATING, TESTED TO ASTM E84
- 3. **RETAINER**: CONTINUOUS 6063 T-5 ALUMINUM, NOMINAL 0.060" (1.52mm) THICK
- 4. **EXTRUSION**: PEBBLE GRAIN FINISH WHICH CONTAINS EPA REGISTERED MICRO-CHEK ANTIMICROBIAL AGENT
- 5. MAXIMUM LENGTH: VINYL CORNER GUARDS 20'
- 6. **HARDWARE**: #6 X 1-5/8" DRYWALL SCREWS INCLUDED
- 7. END CAP: #CGVS3S-D135-EC (2X REQUIRED FOR COMPLETE ASSEMBLY)
- 8. PARTITION COMPONENTS PROVIDED BY OTHERS. FINISHED LENGTH INCLUDES END CAPS

PROJECT: ARCHITECT: CONTRACTOR: 3" VINYL CORNER GUARD NÝSTROM SURFACE MOUNT Right to site. 135 DEGREE 9300 73rd Avenue North Brooklyn Park, MN 55428 NAME DATE SIZE DWG. NO. REV CGVS3S-D135 Α DRAWN MDS 24APR13 RELEASED PGE 01MAY13 WEIGHT: 1.05 lbs/ft SHEET 1 OF 1

**QUANTITY** 

LENGTH

**COLOR** 

В

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.

2

1