

Standard Features:

- Door: 16 gauge cold rolled steel
 - Frame: 16 gauge cold rolled steel with 22 gauge galvanized drywall corner bead
 - Hinge: Concealed pivoting rod hinge
 - Latch: Screwdriver operated cam latch(es)
Optional: Key operated cam lock (installed by others after infill of material)
Mortise preparation to accept 1.50" (min) cylinder (cylinder provided by factory or by others, cylinder installed by others after infill of material)
 - Finish: Gray baked on powder coat
 - Pan: 5/8" pan for infill of material
-

Specifications:

Frame shall be 16 gauge cold rolled steel with 22 gauge galvanized steel drywall corner bead. Door shall be fabricated from 16 gauge cold rolled steel, recessed 5/8" for infill of material. Hinge shall be concealed pivoting rod type. Latch(es) shall be screwdriver operated cam type (optional: key operated cam lock-installed by others after infill of material or mortise preparation to accept 1.50" (min) cylinder-installed by others after infill of material). Finish shall be gray baked on powder coat.

Installation shall be in accordance with manufacturers instructions. Manufacturer shall guarantee against defects in material and workmanship for a period of one year.

Standard Sizes:

Std Sizes (in)	Std Sizes (mm)	Weight/Latches
08x08	203x203	7/1
12x12	305x305	8/1
12x24	305x610	11/2
16x16	406x406	11/1
18x18	457x457	13/2
22x30	559x762	25/2
24x24	610x610	22/2
24x36	610x914	32/3

All units are hinged on the second dimension (height). Rough opening is size plus 1/4".