

Portable

Call Nystrom for current listings and approvals. Dimensions are subject to manufacturer's tolerances, and change without notice. We assume no responsibility for use of superseded or void data.

FIRE EXTINGUISHERS (Not Tagged)

COMMERCIAL GRADE EXTINGUISHERS WITH METAL VALVES



ABC DRY CHEMICAL

ABC MULTI-PURPOSE DRY CHEMICAL: Used to provide protection against class A, B, and C fires; Red, glossy, polyester-coated steel cylinder with pressure gauge, wall mounting bracket, and hose or nozzle as indicated. Contents stored under pressure at approximately 195 PS.I.

MODEL NUMBER	NOMINAL CAPACITY	UL RATING	FM APPROVAL	HEIGHT	CYLINDER DIAMETER	RANGE OF STREAM	TYPE DISCHARGE
EX-3002	2 1/2 lbs.	1A:10B:C	YES	14 3/4"	3"	9'-15'	Nozzle
EX-3005	5 lbs.	2A:10B:C	YES	15 1/4"	4 1/4"	12'-18'	Hose
EX-3005-3	5 lbs.	3A:40B:C	NO	15 1/4"	4 1/4"	12'-18'	Hose
EX-3006	6 lbs.	3A:40B:C	YES	16"	5"	15'-21'	Hose
EX-3010	10 lbs.	4A:80B:C	YES	20"	5"	15'-21'	Hose
EX-3020	20 lbs.	20A:120B:C	YES	23 1/4"	7"	15'-21'	Hose

MODEL NUMBER	FITS SIZE
EX-3901	5 lb.
EX-3902	6 lb.
EX-3903	10 lb.
EX-3904	20 lb.
EX-3909	5, 6, 10 lb.
EX-3910	20 lb.



HALOTRON 1

HALOTRON 1: EPA approved "Clean Agent" for class A, B, and C fires; Red, glossy, polyester-coated steel cylinder with discharge nozzle and bracket. Contents pressurized at approximately 125 PS.I.

MODEL NUMBER	NOMINAL CAPACITY	UL RATING	FM APPROVAL	HEIGHT	CYLINDER DIAMETER	RANGE OF STREAM	TYPE DISCHARGE
EX-3101	1.4 lbs.	1B:C	NO	10"	2 7/8"	6'-8'	Nozzle
EX-3102	2.5 lbs.	2B:C	NO	14 3/4"	3"	6'-10'	Nozzle
EX-3105	5 lbs.	5B:C	NO	15 1/4"	4 1/4"	9'-15'	Nozzle
EX-3111	11 lbs.	1A:10B:C	NO	21 1/2"	6"	9'-15'	Hose & Nozzle
EX-3115	15.5 lbs.	2A:10B:C	NO	21 1/2"	6"	12'-18'	Hose & Nozzle

Call for information on water mist "Clean Agent" and wet chemical "Kitchen Use" extinguishers



WATER/FOAM

PRESSURIZED WATER / FFP FOAM: Used to provide protection against class A fires; Stainless steel shell with pressure gauge and wall mounting bracket (foam unit furnished with combination cartridge holder, cartridge, and nozzle). Shipped empty, to be charged at destination by authorized personnel.

MODEL NUMBER	NOMINAL CAPACITY	UL RATING	FM APPROVAL	HEIGHT	CYLINDER DIAMETER	RANGE OF STREAM	TYPE DISCHARGE
EX-3202 (Water)	2 1/2 gals.	2A	YES	24 1/2"	7"	45'-55'	Hose
EX-3252 (Foam)	2 1/2 gals.	3A:20B	NO	24 1/2"	7"	10'-15'	Hose

MODEL NUMBER	FITS SIZE
EX-3904	2 1/2 gals.

* **OPTION: -AF** Anti-freeze charge



BC DRY CHEMICAL

BC DRY CHEMICAL: Used to provide protection against class B and C fires; Same as multi-purpose shown above.

MODEL NUMBER	NOMINAL CAPACITY	UL RATING	FM APPROVAL	HEIGHT	CYLINDER DIAMETER	RANGE OF STREAM	TYPE DISCHARGE
EX-3302	2 1/2 lbs.	10B:C	YES	14 3/4"	3"	9'-15'	Nozzle
EX-3305	5 lbs.	10B:C	YES	15 1/4"	4 1/4"	12'-18'	Nozzle
EX-3305-3	5 1/2 lbs.	40B:C	NO	15 1/4"	4 1/4"	12'-18'	Hose
EX-3306	6 lbs.	40B:C	YES	16 3/4"	5"	15'-21'	Hose
EX-3310	10 lbs.	60B:C	YES	20"	5"	15'-21'	Hose
EX-3320	20 lbs.	120B:C	YES	23 1/4"	7"	15'-21'	Hose

MODEL NUMBER	FITS SIZE
EX-3901	5 lb.
EX-3902	6 lb.
EX-3903	10 lb.
EX-3904	20 lb.
EX-3909	5, 6, 10 lb.
EX-3910	20 lb.



CARBON DIOXIDE

CARBON DIOXIDE: Used to provide protection against class B and C fires; Red, glossy, polyester-coated aluminum cylinder, with discharge horn and wall bracket. Contents pressurized at approximately 735 PS.I.

MODEL NUMBER	NOMINAL CAPACITY	UL RATING	FM APPROVAL	HEIGHT	CYLINDER DIAMETER	OVERALL WIDTH	RANGE OF STREAM	TYPE DISCHARGE
EX-3405	5 lbs.	5B:C	YES	17 3/4"	5 1/4"	8 1/4"	3'-8'	Horn
EX-3410	10 lbs.	10B:C	YES	24"	7"	12"	3'-8'	Hose & Horn
EX-3415	15 lbs.	10B:C	YES	30"	7"	12"	3'-8'	Hose & Horn
EX-3420	20 lbs.	10B:C	YES	30"	8"	13"	3'-8'	Hose & Horn

MODEL NUMBER	FITS SIZE
EX-3903	5 lb.
EX-3904	10, 15 lb.
EX-3905	20 lb.
EX-3909	5 lb.

**MODEL NUMBER
3002-3420 SERIES**



Right to site.

Call: 800-547-2635 Fax: 800-317-8770
USA or Canada
Web: www.nystrom.com
E-mail: info@nystrom.com

PROJECT: _____

CONTRACTOR: _____

ARCHITECT: _____

INITIALS: QTY: DATE: PART NUMBER: