



SPECIFICATIONS:

- DOOR: STEEL, 3/16" DIAMOND PLATE, GRAY PRIMER COAT WITH A LIVE LOAD OF 300 PSF WITH A MAXIMUM DEFLECTION OF L/160
- (2) FRAME: STEEL, 3/16" FORMED, GRAY PRIMER COAT
- (3) HINGES: TYPE 316 STAINLESS STEEL
- (4) SLAM LATCH: TYPE 316 STAINLESS STEEL WITH INSIDE LEVER HANDLE AND OUTSIDE REMOVABLE 5/16" SQUARE L HANDLE
- (5) COUNTER-BALANCE SPRING: TYPE 17-7 STAINLESS STEEL SPRING ENCLOSED IN A TYPE 316 STAINLESS STEEL TELESCOPING TUBE
- (6) HOLD-OPEN ARM: TYPE 316 STAINLESS STEEL WITH RED VINYL GRIP HANDLE
- (7) ANCHOR: 4" CONCRETE ANCHOR STRAPS PROVIDED

- (8) FLUSH LIFTING HANDLE: TYPE 316 STAINLESS STEEL
- (9) **DRAINAGE COUPLING:** 1-1/2", FOR CONNECTION TO RUN
- 10) FLUSH TYPE PLUG SEAL: TYPE 316 STAINLESS STEEL

FLOOR DOOR SIZE:

" (WIDTH) x " (LENGTH)

CLEAR UNOBSTRUCTED OPENING:

" (WIDTH) x " (LENGTH)

OPENING:

" (WIDTH) x " (LENGTH)

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED. THIS IS A GENERIC SHOP DRAWING AND MAY NOT BE AN ACTUAL REPRESENTATION OF THE FINAL PRODUCT.

PROJECT:

ARCHITECT:

CONTRACTOR:

QTY:

PART#:

FDDPP X SAL

TITLE: Floor Door, Drainable Series,
Sngl Dr, 316 SST Hdw,
Steel, Prime Coat, Pedestrian, Cast-In Anchors,
Slam Latch Removbl L Hdl

