



SPECIFICATIONS:

- (1) DOOR: 316 SST, 3/16" DIAMOND PLATE, MILL FINISH WITH A LIVE LOAD OF 300 PSF WITH A MAXIMUM DEFLECTION OF L/160
- 2 FRAME: 316 SST, 3/16" FORMED, MILL FINISH
- (3) HINGES: TYPE 316 STAINLESS STEEL
- 4 SLAM LATCH: TYPE 316 STAINLESS STEEL WITH INSIDE LEVER HANDLE AND OUTSIDE REMOVABLE 5/16" SQUARE L HANDLE
- (5) COUNTER-BALANCE SPRING: TYPE 17-7 STAINLESS STEEL SPRING ENCLOSED IN A TYPE 316 STAINLESS STEEL TELESCOPING TUBE
- (6) HOLD-OPEN ARM: TYPE 316 STAINLESS STEEL WITH RED VINYL GRIP HANDLE
- $\langle 7 \rangle$ **ANCHOR:** 4" CONCRETE ANCHOR STRAPS PROVIDED

- (8) FLUSH LIFTING HANDLE: TYPE 316 STAINLESS STEEL
- (9) **DRAINAGE COUPLING:** 1-1/2", FOR CONNECTION TO RUN
- 10) FLUSH TYPE PLUG SEAL: TYPE 316 STAINLESS STEEL

FLOOR DOOR SIZE:

" (WIDTH) x " (LENGTH)

CLEAR UNOBSTRUCTED OPENING:

" (WIDTH) x " (LENGTH)

OPENING:

" (WIDTH) x " (LENGTH)

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED. THIS IS A GENERIC SHOP DRAWING AND MAY NOT BE AN ACTUAL REPRESENTATION OF THE FINAL PRODUCT.

PROJECT:

ARCHITECT:

CONTRACTOR:

QTY:

PART#:

FDDPV X SAL

TITLE: Floor Door, Drainable Series,
Sngl Dr, 316 SST Hdw,
SST 316, Mill, Pedestrian, Cast-In Anchors,
Slam Latch Removbl L Hdl

| NAME | DATE | SIZE | DWG. NO. | FDDPV_X_SAL | REV | A | RELEASED | TR | 7-11-13 | WEIGHT: Varies | SHEET 1 OF 2

