

MODEL C1.875E

(SINGLE STAGE RIBBED ABRASIVE BARS)

SPECIFICATIONS:

- $\langle 1 \rangle$ **BASE**: HEAT TREATED EXTRUDED ALUMINUM ALLOY 6063 T-5
- (2) ABRASIVE: ALUMINUM OXIDE SILICON CARBIDE GRANULES IN A UV PROTECTED, 2 PART EPOXY, LOCKED INTO EXTRUDED CHANNELS
- 3. BASE FINISH: MILL
- 4. POURED CONCRETE STAIRS: NOSING SHALL TERMINATE NO MORE THEN 3" FROM END OF STEPS
- 5. CONCRETE FILLED STEEL PAN STAIRS: NOSING SHALL BE FULL LENGTH OF STEPS, LESS 1/8" CLEARANCE
- 6. COLOR: BLACK (STANDARD), SAFETY YELLOW, GRAY, RED, BROWN, GREEN, BURGUNDY, BLUE, BUFF, LUMINESCENT
- 7. **LENGTH**: 12'0" MAXIMUM
- 8. UL 1994 LISTED: COMBINED WIDTH OF PHOTO-LUMINESCENT MATERIAL SHALL NOT BE LESS THAN 1"

LENGIH	QII	COLOR
	•	

PROJECT: ARCHITECT: CONTRACTOR: QTY: PART#: STSB-C1.875E TITLE: V331, Stair Tread, NÝSTROM Bar Ribbed Abrasive, Short Nose, Alum Extruded Anchor, 9300 73rd Avenue North Brooklyn Park, MN 55428 NAME DATE SIZE DWG. NO. REV STSB-C1.875E Α 3/11/11 Α DRAWN BMHRELEASED PE WEIGHT: .69 LB SHEET 1 OF 1 3/11/11

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.