



**MODEL C3E**

(SINGLE STAGE RIBBED ABRASIVE BARS)

**SPECIFICATIONS:**

- ① **BASE:** HEAT TREATED EXTRUDED ALUMINUM  
ALLOY 6063 T-5
- ② **ABRASIVE:** ALUMINUM OXIDE SILICON CARBIDE  
GRANULES IN A UV PROTECTED, 2 PART EPOXY,  
LOCKED INTO EXTRUDED CHANNELS
3. **BASE FINISH:** MILL
4. **POURED CONCRETE STAIRS:** NOSING SHALL  
TERMINATE NO MORE THEN 3" FROM END OF  
STEPS
5. **CONCRETE FILLED STEEL PAN STAIRS:** NOSING  
SHALL BE FULL LENGTH OF STEPS, LESS 1/8"  
CLEARANCE
6. **COLOR:** BLACK (STANDARD), SAFETY YELLOW,  
GRAY, RED, BROWN, GREEN, BURGUNDY, BLUE,  
BUFF, LUMINESCENT
7. **LENGTH:** 12"0" MAXIMUM
8. **UL 1994 LISTED:** COMBINED WIDTH OF PHOTO-  
LUMINESCENT MATERIAL SHALL NOT BE LESS  
THAN 1"

LENGTH	QTY	COLOR

PROJECT:					
ARCHITECT:					
CONTRACTOR:					
QTY:					
PART#:		STSB-C3E			
<b>NYSTROM</b> <small>Right to site.</small> 9300 73rd Avenue North Brooklyn Park, MN 55428		TITLE:			
		V351, Stair Tread, Bar Ribbed Abrasive, Short Nose, Alum Extruded Anchor,			
NAME	DATE	SIZE	DWG. NO.	REV	
DRAWN BMH	3/11/11	A	STSB-C3E	A	
RELEASED	PE	3/11/11	WEIGHT: 1.17LB	SHEET 1 OF 1	