

**MODEL L3.125D**


(SINGLE STAGE FULL ABRASIVE)

**SPECIFICATIONS:**

- ① **BASE:** HEAT TREATED EXTRUDED ALUMINUM  
ALLOY 6063 T-5
- ② **ABRASIVE:** ALUMINUM OXIDE SILICON CARBIDE  
GRANULES IN A UV PROTECTED, 2 PART EPOXY,  
LOCKED INTO EXTRUDED CHANNELS
3. **BASE FINISH:** MILL
4. **POURED CONCRETE STAIRS:** NOSING SHALL  
TERMINATE NO MORE THEN 3" FROM END OF  
STEPS
5. **CONCRETE FILLED STEEL PAN STAIRS:** NOSING  
SHALL BE FULL LENGTH OF STEPS, LESS 1/8"  
CLEARANCE
6. **COLOR:** BLACK (STANDARD), SAFETY YELLOW,  
GRAY, RED, BROWN, GREEN, BURGUNDY, BLUE,  
BUFF, LUMINESCENT

7. **LENGTH:** 12'0" MAXIMUM
8. COUNTER SUNK HOLES PRE-DRILLED FOR A #10  
FASTENER SPACED 3" FROM ENDS AND  
APPROXIMATELY 12" TO 15" O.C.
9. UL 1994 LISTED: COMBINED WIDTH OF PHOTO-  
LUMINESCENT MATERIAL SHALL NOT BE LESS  
THAN 1"

LENGTH	QTY	COLOR

PROJECT:				
ARCHITECT:				
CONTRACTOR:				
QTY:				
PART#:		<b>STSF-L3.125D</b>		
 <small>Right to site. 9300 73rd Avenue North Brooklyn Park, MN 55428</small>		TITLE: VFAL30, Stair Tread, Full Abrasive, Long Nose, Drilled For Bolt In,		
	NAME	DATE	SIZE	DWG. NO.
DRAWN	BMH	3/11/11	A	STSF-L3.125D
RELEASED	PE	3/11/11	WEIGHT: 1.35 LB	SHEET 1 OF 1