



MODEL L4.125E

(SINGLE STAGE FULL ABRASIVE)

SPECIFICATIONS:

1. **BASE:** HEAT TREATED EXTRUDED ALUMINUM ALLOY 6063 T-5
2. **ABRASIVE:** ALUMINUM OXIDE SILICON CARBIDE GRANULES IN A UV PROTECTED, 2 PART EPOXY, LOCKED INTO EXTRUDED CHANNELS
3. **BASE FINISH:** MILL
4. **POURED CONCRETE STAIRS:** NOSING SHALL TERMINATE NO MORE THEN 3" FROM END OF STEPS
5. **CONCRETE FILLED STEEL PAN STAIRS:** NOSING SHALL BE FULL LENGTH OF STEPS, LESS 1/8" CLEARANCE
6. **COLOR:** BLACK (STANDARD), SAFETY YELLOW, GRAY, RED, BROWN, GREEN, BURGUNDY, BLUE, BUFF, LUMINESCENT
7. **LENGTH:** 12'0" MAXIMUM (STANDARD)
8. **UL 1994 LISTED:** COMBINED WIDTH OF PHOTO-LUMINESCENT MATERIAL SHALL NOT BE LESS THAN 1"

LENGTH	QTY	COLOR

PROJECT:					
ARCHITECT:					
CONTRACTOR:					
QTY:					
PART#:				STSF-L4.125E	
NYSTROM <small>Right to site.</small> 9300 73rd Avenue North Brooklyn Park, MN 55428				TITLE: VFAL41, Stair Tread, Full Abrasive, Long Nose, Alum Extruded Anchor,	
	NAME	DATE	SIZE	DWG. NO.	REV
DRAWN	BMH	3/14/11	A	STSF-L4.125E	A
RELEASED	PE	3/14/11	WEIGHT: 1.65 LB		SHEET 1 OF 1