





## **SPECIFICATIONS:**

- 1 BASE: 319 CAST ALUMINUM
- (2) ABRASIVE: SILICON CARBIDE ABRASIVE, CROSSHATCH PATTERN 1/8" DEEP
- 3. FINISH: SAND CAST
- 4. POURED CONCRETE STAIRS: NOSING SHALL TERMINATE NO MORE THEN 3" FROM END OF STEPS
- 5. LENGTH: 6" MINIMUM 6'-0" MAXIMUM
- 6. WING ANCHORS: STANDARD FOR POURED CONCRETE APPLICATIONS; STEEL ANCHORS AND STAINLESS STEEL HARDWARE

LENGTH ±1/8	QTY

l l	PROJEC	CT:					
ARCHITECT:							
CONTRACTOR:							
QTY:							
PART#:				STCA-C4W			
Right to site.  9300 73rd Avenue North Brooklyn Park, MN 55428		TITLE: Stair Tread, Cast Series 4", Cast Aluminum Crosshatch Short Nosing for Concrete, Wing Anchor					
DRAWN	NAME SJB	DATE 3/31/11	SIZE A	DWG. NO. STCA-C4W	RE B		
RELEASED	DWO	3/31/11	WE	IGHT: 1.34 LB/FT	SHEET 1 OF		

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.